Supplementary Information

The following information is associated with Network Rail Standard:
NR CIV/SD/2143-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2143-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS
Full document details: NR NR-CIV-SD-2143-2 ISSUE B 2012

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 19:52:15 MDT

Drg No. 2143

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B20	1	8	8	4000	99	985	425	1175	425	(985)	
							65		0 RAD		65	
103	B32	1	8	8	8175	99	1325		5520		1325	
							32800 RAD		26715 RAD		32800 RAD	
105	B40	1	4	4	5650	99	3685	3665	(1965)	395	26810	
106	B32	1	12	12	5650	99	3685	3665	(1965)	395	26820	
							B, A, D, R, (C)					
							MKS 105 & 106					
107	B32	1	4	4	3575	25	1265	1150	690	855	(1145)	
108	B25	1	12	12	2900	25	930	815	505	605	(1145)	
109	B32	1	4	4	2600	23	465	2000	(305)			
110	B25	1	12	12	2475	23	365	2000	(240)			
115	B16	1	16	16	1425	21	600	270	(600)			
131a	B12	1	38	38	2750	51	940	335	160			
131b	B12	1	2	2	2775	51	940	345	160			
131c	B12	1	2	2	2800	51	940	355	160			
131d	B12	1	2	2	2825	51	940	365	160			
131e	B12	1	2	2	2850	51	940	385	160			
131f	B12	1	2	2	2900	51	940	405	160			
131g	B12	1	2	2	2950	51	940	435	160			
131h	B12	1	2	2	3025	51	940	465	160			
131j	B12	1	2	2	3100	51	940	505	160			
132a	B16	1	38	38	1750	51	520	225	210			
132b	B16	1	2	2	1775	51	520	230	210			
132c	B16	1	2	2	1800	51	520	240	210			
132d	B16	1	2	2	1800	51	520	250	210			
132e	B16	1	2	2	1850	51	520	270	210			
132f	B16	1	2	2	1900	51	520	290	210			
132g	B16	1	2	2	1950	51	520	320	210			
132h	B16	1	2	2	2000	51	520	350	210			
132j	B16	1	2	2	2100	51	520	390	210			
133a	B16	1	2	2	3600	99	915	610	500	585	225	
133b	B16	1	2	2	3725	99	915	665	500	635	245	
133c	B16	1	2	2	3825	99	915	720	500	690	270	
133d	B16	1	2	2	3975	99	915	790	500	750	295	
133e	B16	1	2	2	4075	99	915	840	500	795	315	
134a	B16	1	2	2	2275	99	495	505	210	490	185	
134b	B16	1	2	2	2375	99	495	560	210	535	205	
134c	B16	1	2	2	2500	99	495	615	210	590	230	
134d	B16	1	2	2	2625	99	495	685	210	650	255	
134e	B16	1	2	2	2450	99	495	600	210	575	220	
							A, C, D, B, E, A					
				Mks. 133, 134, 135, 136								

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
135a	B16	1	20	20	3575	99	905	600	500	550	280	
135b	B16	1	4	4	3100	99	905	370	500	350	280	
136	B16	1	24	24	1975	99	485	370	210	350	165	
137	B16	1	19	19	1850	21	865	160	(865)			
138a	B16	1	1	1	1850	21	865	160	(865)			
138b	B16	1	1	1	1850	21	865	170	(865)			
138c	B16	1	1	1	1850	21	865	180	(865)			
138d	B16	1	1	1	1875	21	865	195	(865)			
138e	B16	1	1	1	1900	21	865	220	(865)			
138f	B16	1	1	1	1925	21	865	245	(865)			
138g	B16	1	1	1	1950	21	865	275	(865)			
138h	B16	1	1	1	2000	21	865	310	(865)			
139a	B16	1	1	1	2075	29	840	430	(865)	415	150	
139b	B16	1	1	1	2150	29	840	485	(865)	465	175	
139c	B16	1	1	1	2200	29	840	545	(865)	520	195	
139d	B16	1	1	1	2275	29	840	610	(865)	585	225	
139e	B16	1	1	1	2175	29	840	525	(865)	505	190	
140	B20	1	12	12	2225	29	945	260	(1010)	280	95	
									A, D, B, E, (C)			
						Mks. 139, 140						
141	B16	1	30	30	1850	21	865	160	(865)			
142	B16	1	8	8	1125	21	300	575	(300)			
143	B12	1	8	8	1350	21	400	575	(400)			
144	B12	1	4	4	2075	11	780	(1300)				
147	B20	1	12	12	3325	29	1485	795	(1140)	800	130	
									A, D, B, E, (C)			
						Mk. 147,151,153						
148	B20	1	12	12	2225	21	290	800	(1225)			
149	B20	1	12	12	3175	21	1500	365	(1400)			
150	B12	1	18	18	2800	99	250	795	805	410	715	
									C, D, B, E, B, D, A			
						Mk. 150						
151	B12	1	20	20	3475	29	1560	365	(1585)	340	170	
153	B12	1	4	4	3475	29	1560	365	(1585)	340	170	
154	B20	1	12	12	3025	11	1580	(1500)				
155	B20	1	12	12	3150	21	1230	790	(1230)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2143-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013
	Name	Position	Signature	Date

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS
7.4m EXTERNAL UNIT
LEFT SKEW 30°

SHEET 2

Scale 1:25

Drawing Number NR/CIV/SD/2143-2 B

Full document details: NR NR-CIV-SD-2143-2 ISSUE B 2012

AVA Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or networking permitted unless licence from IHS
Licensee: Network Rail (Consultants) Limited, User name: ukgb