Supplementary Information

The following information is associated with Network Rail Standard:
NR CIV/SD/2155-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2155-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS
Full document details: NR NR-CIV-SD-2155-2 ISSUE B 2012

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 20:00:31 MDT

Drg No. 2155

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B20	1	8	8	3800	99	985	425	975	425	(985)	
							65		0 RAD		65	
103	B32	1	4	4	7375	99	1205	4955			1205	
							2705 RAD		21500 RAD		2705 RAD	
104	B25	1	4	4	7375	99	1200	4955			1200	
							2705 RAD		21500 RAD		2705 RAD	
105	B32	1	8	8	5700	99	3835	3800	(1855)	500	21635	
106	B25	1	8	8	5700	99	3840	3800	(1855)	500	21645	
							B; D; A; R; (C)					
							MKS 105 & 106					
107	B32	1	8	8	3775	25	1275	640	755	460	(1850)	
108	B25	1	8	8	3450	25	940	640	555	455	(1850)	
109	B25	1	16	16	2225	23	365	1750	(240)			
115	B16	1	16	16	1400	21	600	255	(600)			
131a	B12	1	34	34	2550	51	840	335	160			
131b	B12	1	2	2	2575	51	840	345	160			
131c	B12	1	2	2	2600	51	840	355	160			
131d	B12	1	2	2	2625	51	840	370	160			
131e	B12	1	2	2	2675	51	840	390	160			
131f	B12	1	2	2	2725	51	840	420	160			
131g	B12	1	2	2	2800	51	840	455	160			
131h	B12	1	2	2	2875	51	840	495	160			
132a	B16	1	34	34	1650	51	465	225	210			
132b	B16	1	2	2	1650	51	465	230	210			
132c	B16	1	2	2	1675	51	465	240	210			
132d	B16	1	2	2	1700	51	465	255	210			
132e	B16	1	2	2	1750	51	465	275	210			
132f	B16	1	2	2	1800	51	465	305	210			
132g	B16	1	2	2	1875	51	465	340	210			
132h	B16	1	2	2	1950	51	465	380	210			
133a	B16	1	2	2	3400	99	830	590	500	585	105	
133b	B16	1	2	2	3500	99	830	640	500	640	115	
133c	B16	1	2	2	3625	99	830	700	500	695	130	
133d	B16	1	2	2	3750	99	830	765	500	760	140	
133e	B16	1	2	2	3900	99	830	845	500	840	155	
133f	B16	1	2	2	4100	99	830	935	500	925	175	
133g	B16	1	2	2	4250	99	830	1020	500	1010	190	
133h	B16	1	2	2	4425	99	830	1105	500	1095	205	
133j	B16	1	2	2	4225	99	830	1005	500	995	185	
133k	B16	1	2	2	4000	99	830	890	500	885	165	
133l	B16	1	2	2	3775	99	830	775	500	770	145	
134a	B16	1	2	2	2150	99	455	490	210	490	85	
134b	B16	1	2	2	2250	99	455	540	210	540	95	
134c	B16	1	2	2	2375	99	455	600	210	600	110	

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
134d	B16	1	2	2	2525	99	455	670	210	665	120	
134e	B16	1	2	2	2675	99	455	745	210	745	135	
134f	B16	1	2	2	2850	99	455	835	210	830	155	
134g	B16	1	2	2	3025	99	455	925	210	915	170	
134h	B16	1	2	2	2950	99	455	890	210	885	165	
134j	B16	1	2	2	2725	99	455	775	210	770	145	
134k	B16	1	2	2	2500	99	455	660	210	660	120	
134l	B16	1	2	2	2275	99	455	545	210	550	100	
							A; C; D; B; E; A					
					Mks. 133,	134,	135, 136					
135a	B16	1	10	10	3325	99	825	555	500	550	135	
135b	B16	1	4	4	2900	99	825	350	500	550	135	
136	B16	1	14	14	1875	99	450	350	210	350	80	
137	B16	1	17	17	1650	21	775	160	(775)			
138a	B20	1	1	1	1900	13	905	180	(905)			
138b	B20	1	1	1	1900	13	905	180	(905)			
138c	B20	1	1	1	1900	13	905	185	(905)			
138d	B20	1	1	1	1925	13	905	205	(905)			
138e	B20	1	1	1	1950	13	905	230	(905)			
138f	B20	1	1	1	1975	21	905	260	(905)			
138g	B20	1	1	1	2000	21	905	300	(905)			
139a	B20	1	1	1	2100	29	885	405	(905)	415	60	
139b	B20	1	1	1	2150	29	885	460	(905)	470	70	
139c	B20	1	1	1	2200	29	885	520	(905)	530	85	
139d	B20	1	1	1	2275	29	885	590	(905)	595	95	
139e	B20	1	1	1	2350	29	885	670	(905)	675	115	
139f	B20	1	1	1	2450	29	885	760	(905)	765	130	
139g	B20	1	1	1	2525	29	885	845	(905)	850	145	
139h	B20	1	1	1	2500	29	885	815	(905)	815	140	
139j	B20	1	1	1	2400	29	885	700	(905)	705	120	
139k	B20	1	1	1	2275	29	885	585	(905)	595	95	
139l	B20	1	1	1	2150	29	885	470	(905)	480	75	
140	B20	1	7	7	1950	29	880	265	(905)	280	50	
									A; D; B; E; (C)			
					Mks. 139,	140						
141	B16	1	32	32	1625	21	775	160	(775)			
142	B16	1	8	8	1075	21	300	520	(300)			
143	B12	1	8	8	1275	21	400	520	(400)			
144	B12	1	4	4	2075	11	780	(1300)				
146a	B12	1	4	4	2125	21	205	1755	(205)			
146b	B12	1	4	4	1775	21	205	1395	(205)			
146c	B12	1	4	4	1400	21	205	1030	(205)			
146d	B12	1	4	4	1050	21	205	665	(205)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
147	B16	1	12	12	3175	29	1490	730	(1020)	715	150	
									A; D; B; E; (C)			
							Mk. 147,151,153					
148	B16	1	12	12	1975	21	210	715	(1105)			
149	B16	1	12	12	3175	21	1500	325	(1400)			
150	B12	1	16	16	2600	99	250	725	730	190	715	
							C; D; R; E; B; D; A					
							Mk. 150					
151	B12	1	18	18	3300	29	1485	340	(1500)	340	80	
153	B12	1	4	4	3300	29	1485	340	(1500)	340	80	
154	B16	1	12	12	2975	11	1495	(1500)				
155	B16	1	12	12	2875	21	1110	710	(1110)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2155-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

	Name	Position	Signature	Date
Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS 8.4m EXTERNAL UNIT RIGHT SKEW 15°

SHEET 2

Scale 1:25

Drawing Number NR/CIV/SD/2155-2 B

Full document details: NR NR-CIV-SD-2155-2 ISSUE B 2012

Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or networking permitted without licence from IHS
Licensee=Mott MacDonald Group Limited, User=sam, allan
No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, without the prior written permission of the copyright owner.