The following information is associated with Network Rail Standard:
NR CIV/SD/2156-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2156-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

--`,,,,,,`,,,,,,`,,`,,,,,,,,`-`-`-,,`,,`,`,,`---

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 19:58:40 MDT

Full document details: NR NR-CIV-SD-2156-2 ISSUE B 2012

Drg No. 2156

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B20	1	8	8	4000	99	985	425	1175	425	(985)	
							65		0 RAD		65	
103	B32	1	8	8	8175	99	1325		5520		1325	
							3280 RAD		26715 RAD		3280 RAD	
105	B32	1	8	8	6125	99	4270	4245	(1855)	500	26780	
106	B25	1	8	8	6150	99	4275	4245	(1855)	500	26785	
							B, D, A, R, (C)					
							MKS 105 & 106					
107	B32	1	12	12	3875	25	1265	640	690	485	(1950)	
108	B25	1	4	4	3525	25	930	640	505	480	(1950)	
109	B25	1	4	4	2225	23	365	1750	(240)			
110	B20	1	12	12	2150	23	290	1750	(200)			
115	B16	1	16	16	1425	21	600	285	(600)			
131a	B12	1	38	38	2750	51	940	335	160			
131b	B12	1	2	2	2775	51	940	345	160			
131c	B12	1	2	2	2800	51	940	355	160			
131d	B12	1	2	2	2825	51	940	365	160			
131e	B12	1	2	2	2850	51	940	385	160			
131f	B12	1	2	2	2900	51	940	405	160			
131g	B12	1	2	2	2950	51	940	435	160			
131h	B12	1	2	2	3025	51	940	465	160			
131j	B12	1	2	2	3100	51	940	505	160			
132a	B16	1	38	38	1750	51	520	225	210			
132b	B16	1	2	2	1775	51	520	230	210			
132c	B16	1	2	2	1800	51	520	240	210			
132d	B16	1	2	2	1800	51	520	250	210			
132e	B16	1	2	2	1850	51	520	270	210			
132f	B16	1	2	2	1900	51	520	290	210			
132g	B16	1	2	2	1950	51	520	320	210			
132h	B16	1	2	2	2000	51	520	350	210			
132j	B16	1	2	2	2100	51	520	390	210			
133a	B16	1	2	2	3600	99	915	610	500	585	225	
133b	B16	1	2	2	3725	99	915	665	500	635	245	
133c	B16	1	2	2	3825	99	915	720	500	690	270	
133d	B16	1	2	2	3975	99	915	790	500	750	295	
133e	B16	1	2	2	4125	99	915	865	500	820	325	
133f	B16	1	2	2	4300	99	915	955	500	900	360	
133g	B16	1	2	2	4475	99	915	1040	500	980	395	
133h	B16	1	2	2	4650	99	915	1130	500	1060	430	
133j	B16	1	2	2	4625	99	915	1115	500	1045	420	
133k	B16	1	2	2	4400	99	915	1000	500	940	375	
133l	B16	1	2	2	4150	99	915	880	500	835	330	
133m	B16	1	2	2	3925	99	915	765	500	730	285	
134a	B16	1	2	2	2275	99	495	505	210	490	185	
134b	B16	1	2	2	2375	99	495	560	210	535	205	
134c	B16	1	2	2	2500	99	495	615	210	590	230	
134d	B16	1	2	2	2625	99	495	685	210	650	255	
134e	B16	1	2	2	2775	99	495	760	210	725	285	

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
134f	B16	1	2	2	2950	99	495	850	210	805	320	
134g	B16	1	2	2	3150	99	495	940	210	885	355	
134h	B16	1	2	2	3225	99	495	985	210	930	370	
134j	B16	1	2	2	3000	99	495	870	210	825	325	
134k	B16	1	2	2	2775	99	495	755	210	715	280	
134l	B16	1	2	2	2550	99	495	640	210	610	235	
134m	B16	1	2	2	2300	99	495	525	210	505	190	
							A, C, B, D, E, A					
					Mks. 133, 134, 135, 136							
135a	B16	1	10	10	3600	99	905	600	(500)	550	280	
135b	B16	1	4	4	3125	99	905	370	(500)	350	280	
136	B16	1	14	14	1875	99	485	370	(210)	350	165	
137	B16	1	19	19	1850	21	865	160	(865)			
138a	B20	1	1	1	2100	13	1010	180	(1010)			
138b	B20	1	1	1	2100	13	1010	180	(1010)			
138c	B20	1	1	1	2100	13	1010	180	(1010)			
138d	B20	1	1	1	2125	13	1010	195	(1010)			
138e	B20	1	1	1	2150	13	1010	220	(1010)			
138f	B20	1	1	1	2175	13	1010	245	(1010)			
138g	B20	1	1	1	2200	21	1010	275	(1010)			
138h	B20	1	1	1	2225	21	1010	310	(1010)			
139a	B20	1	1	1	2275	29	965	405	(1010)	415	130	
139b	B20	1	1	1	2325	29	965	460	(1010)	465	150	
139c	B20	1	1	1	2400	29	965	520	(1010)	520	175	
139d	B20	1	1	1	2475	29	965	590	(1010)	585	200	
139e	B20	1	1	1	2550	29	965	670	(1010)	655	230	
139f	B20	1	1	1	2625	29	965	755	(1010)	735	265	
139g	B20	1	1	1	2725	29	965	845	(1010)	820	300	
139h	B20	1	1	1	2775	29	965	895	(1010)	865	320	
139j	B20	1	1	1	2650	29	965	780	(1010)	755	275	
139k	B20	1	1	1	2525	29	965	660	(1010)	650	230	
139l	B20	1	1	1	2425	29	965	545	(1010)	545	185	
139m	B20	1	1	1	2300	29	965	430	(1010)	435	140	
140	B20	1	7	7	2125	29	945	260	(1010)	280	95	
							A, D, B, E, (C)					
					Mks. 139, 140							
141	B16	1	34	34	1850	21	865	160	(865)			
142	B16	1	12	12	1125	21	300	575	(300)			
143	B12	1	8	8	1350	21	400	575	(400)			
144	B12	1	4	4	2075	11	780	(1300)				
146a	B12	1	4	4	2175	21	230	1755	(230)			
146b	B12	1	4	4	1825	21	230	1395	(230)			
146c	B12	1	4	4	1450	21	230	1030	(230)			
146d	B12	1	4	4	1100	21	230	665	(230)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
147	B16	1	12	12	3275	29	1490	805	(1020)	800	155	
							A, D, B, E, (C)					
							Mk. 147,151,153					
148	B16	1	12	12	2075	21	210	800	(1105)			
149	B16	1	12	12	3225	21	1500	365	(1400)			
150	B12	1	16	16	2800	99	250	795	805	410	715	
							C, D, R, E, B, D, A					
							Mk. 150					
151	B12	1	18	18	3475	29	1560	365	(1585)	340	170	
153	B12	1	4	4	3475	29	1560	365	(1585)	340	170	
154	B16	1	12	12	3050	11	1580	(1500)				
155	B16	1	12	12	2975	21	1110	795	(1110)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2156-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013
	Name	Position	Signature	Date

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS 8.4m EXTERNAL UNIT RIGHT SKEW 30°

SHEET 2

Scale	1:25	
Drawing Number	NR/CIV/SD/2156-2	B

Full document details: NR NR-CIV-SD-2156-2 ISSUE B 2012

AVA Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or networking permitted without licence from IHS
Licensee=Mapon Volkovich/5959412001, User=sam, allan
Not for resale
2013-04-24 11:27:11 +0000