Supplementary Information

The following information is associated with Network Rail Standard:
NR CIV/SD/2157-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2157-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS
Full document details: NR NR-CIV-SD-2157-2 ISSUE B 2012

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 19:59:34 MDT

Drg No. 2157

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B25	1	2	2	4950	99	1225	425	1650	425	(1225)	
							50		0 RAD		50	
102	B20	1	6	6	4475	99	985	425	1650	425	(985)	
							50		0 RAD		50	
103	B32	1	8	8	9950	99	1590		6755		1590	
								4685 RAD		40010 RAD	4665 RAD	
105	B40	1	12	12	7075	99	5250	5195	(1855)	500	39880	
106	B32	1	4	4	7075	99	5250	5195	(1855)	500	39885	
							B; D; A; R; (C)					
							MKS 105 & 106					
107	B32	1	16	16	4075	25	1235	645	570	530	(2180)	
109	B32	1	4	4	2350	23	465	1750	(305)			
110	B25	1	12	12	2225	23	365	1750	(240)			
115	B16	1	16	16	1475	21	600	330	(600)			
131a	B12	1	46	46	3175	51	1150	335	160			
131b	B12	1	2	2	3200	51	1150	345	160			
131c	B12	1	2	2	3200	51	1150	350	160			
131d	B12	1	2	2	3225	51	1150	355	160			
131e	B12	1	2	2	3250	51	1150	370	160			
131f	B12	1	2	2	3275	51	1150	380	160			
131g	B12	1	2	2	3300	51	1150	400	160			
131h	B12	1	2	2	3350	51	1150	420	160			
131j	B12	1	2	2	3400	51	1150	445	160			
131k	B12	1	2	2	3450	51	1150	470	160			
131l	B12	1	2	2	3525	51	1150	505	160			
132a	B16	1	46	46	2000	51	635	225	210			
132b	B16	1	2	2	2000	51	635	230	210			
132c	B16	1	2	2	2000	51	635	235	210			
132d	B16	1	2	2	2025	51	635	240	210			
132e	B16	1	2	2	2050	51	635	255	210			
132f	B16	1	2	2	2075	51	635	265	210			
132g	B16	1	2	2	2100	51	635	285	210			
132h	B16	1	2	2	2150	51	635	305	210			
132j	B16	1	2	2	2200	51	635	330	210			
132k	B16	1	2	2	2250	51	635	355	210			
132l	B16	1	2	2	2325	51	635	390	210			
133a	B16	1	2	2	4125	99	1105	675	500	585	385	
133b	B16	1	2	2	4225	99	1105	730	500	625	415	
133c	B16	1	2	2	4350	99	1105	785	500	670	450	
133d	B16	1	2	2	4475	99	1105	850	500	725	485	
133e	B16	1	2	2	4625	99	1105	925	500	780	530	
133f	B16	1	2	2	4800	99	1105	1010	500	850	580	
133g	B16	1	2	2	4975	99	1105	1100	500	920	635	
133h	B16	1	2	2	5150	99	1105	1190	500	995	685	
133j	B16	1	2	2	5325	99	1105	1275	500	1065	740	
133k	B16	1	2	2	5300	99	1105	1260	500	1055	730	

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
133l	B16	1	2	2	5050	99	1105	1145	500	960	660	
133m	B16	1	2	2	4825	99	1105	1025	500	865	590	
133n	B16	1	2	2	4600	99	1105	910	500	770	520	
							A; C; B; D; E; A					
					Mks. 133, 134, 135, 136							
134a	B16	1	2	2	2550	99	590	555	210	485	310	
134b	B16	1	2	2	2675	99	590	610	210	530	345	
134c	B16	1	2	2	2775	99	590	665	210	575	380	
134d	B16	1	2	2	2900	99	590	730	210	625	415	
134e	B16	1	2	2	3050	99	590	805	210	685	460	
134f	B16	1	2	2	3225	99	590	890	210	755	510	
134g	B16	1	2	2	3400	99	590	980	210	825	565	
134h	B16	1	2	2	3600	99	590	1070	210	900	615	
134j	B16	1	2	2	3650	99	590	1100	210	925	635	
134k	B16	1	2	2	3425	99	590	985	210	830	565	
134l	B16	1	2	2	3175	99	590	865	210	735	495	
134m	B16	1	2	2	2950	99	590	750	210	640	425	
134n	B16	1	2	2	2700	99	590	630	210	545	355	
135a	B16	1	10	10	4150	99	1080	710	500	550	480	
135b	B16	1	4	4	3575	99	1080	425	500	350	480	
136	B16	1	14	14	2250	99	565	425	210	350	280	
137	B16	1	23	23	2225	21	1060	160	(1060)			
138a	B20	1	1	1	2550	13	1235	180	(1235)			
138b	B20	1	1	1	2550	13	1235	180	(1235)			
138c	B20	1	1	1	2550	13	1235	180	(1235)			
138d	B20	1	1	1	2550	13	1235	180	(1235)			
138e	B20	1	1	1	2575	13	1235	195	(1235)			
138f	B20	1	1	1	2575	13	1235	210	(1235)			
138g	B20	1	1	1	2600	13	1235	230	(1235)			
138h	B20	1	1	1	2625	13	1235	255	(1235)			
138j	B20	1	1	1	2650	21	1235	280	(1235)			
138k	B20	1	1	1	2675	21	1235	310	(1235)			
139a	B20	1	1	1	2700	29	1145	425	(1235)	410	215	
139b	B20	1	1	1	2750	29	1145	480	(1235)	455	250	
139c	B20	1	1	1	2825	29	1145	540	(1235)	505	285	
139d	B20	1	1	1	2875	29	1145	605	(1235)	555	325	
139e	B20	1	1	1	2950	29	1145	680	(1235)	620	365	
139f	B20	1	1	1	3050	29	1145	765	(1235)	685	420	
139g	B20	1	1	1	3150	29	1145	860	(1235)	760	470	
139h	B20	1	1	1	3225	29	1145	950	(1235)	830	525	
139j	B20	1	1	1	3250	29	1145	980	(1235)	855	545	
139k	B20	1	1	1	3150	29	1145	860	(1235)	760	475	
139l	B20	1	1	1	3025	29	1145	745	(1235)	670	405	
139m	B20	1	1	1	2900	29	1145	625	(1235)	575	355	
139n	B20	1	1	1	2800	29	1145	510	(1235)	480	265	
140	B20	1	7	7	2525	29	1110	270	(1235)	280	155	
										A; D; B; E; (C)		
					Mks. 139, 140							
141	B20	1	42	42	2550	13	1235	180	(1235)			
142	B16	1	16	16	1250	29	300	705	(300)			
143	B12	1	8	8	1475	21	400	705	(400)			
144	B12	1	4	4	2075	11	780	(1300)				

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
146a	B12	1	4	4	2250	21	280	1730	(280)			
146b	B12	1	4	4	1900	21	280	1370	(280)			
146c	B12	1	4	4	1525	21	280	1005	(280)			
146d	B12	1	4	4	1175	21	280	640	(280)			
147	B20	1	14	14	3525	29	1485	1160	(985)	1160	180	
									A; D; B; E; (C)			
							Mk. 147,151,153					
148	B20	1	14	14	2425	21	290	1160	(1070)			
149	B20	1	14	14	3250	21	1500	455	(1400)			
150	B12	1	16	16	3650	99	250	1135	(965)	840	840	
									C; D; R; E; B; D; A			
							Mk. 150					
151	B12	1	18	18	3875	29	1720	425	(1770)	340	290	
153	B12	1	4	4	3875	29	1720	425	(1770)	340	290	
154	B20	1	12	12	3225	11	1770	(1500)				
155	B20	1	16	16	3025	21	1075	975	(1075)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2157-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013
	Name	Position	Signature	Date

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS
8.4m EXTERNAL UNIT
RIGHT SKEW 45°

SHEET 2

Scale	AS SHOWN	
Drawing Number	NR/CIV/SD/2157-2	B

Full document details: NR NR-CIV-SD-2157-2 ISSUE B 2012

AVA Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or networking permitted without licence from IHS
Licensee=Network Rail Group, User=sian.walsh@networkrail.co.uk
2013-04-15 11:11:11 +0000