Supplementary Information

The following information is associated with Network Rail Standard:
NR CIV/SD/2165-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2165-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

--`,,,,,,`,,,,,,`,,`,,,,,,,,`-`-`,,`,,`,`,,`---

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS
Full document details: NR NR-CIV-SD-2165-2 ISSUE B 2012

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 19:57:41 MDT

Drg No. 2165

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B20	1	8	8	3800	99	985	425	975	425	(985)	
							63		0 RAD		63	
103	B32	1	4	4	7375	99	1205	4955			1205	
							2705 RAD		2500 RAD		2705 RAD	
104	B25	1	4	4	7375	99	1200	4955			1200	
							2705 RAD		2500 RAD		2705 RAD	
105	B32	1	8	8	6100	99	4370	4320	(1730)	625	21630	
106	B25	1	8	8	6100	99	4370	4320	(1730)	625	21635	
107	B32	1	8	8	3875	25	1275	755	(2600)			
108	B25	1	8	8	3540	25	940	555	(2600)			
109	B25	1	16	16	1475	23	365	1000	(240)			
115	B16	1	16	16	1400	21	600	255	(600)			
131a	B12	1	34	34	2550	51	840	335	160			
131b	B12	1	2	2	2575	51	840	345	160			
131c	B12	1	2	2	2600	51	840	355	160			
131d	B12	1	2	2	2625	51	840	370	160			
131e	B12	1	2	2	2675	51	840	390	160			
131f	B12	1	2	2	2725	51	840	420	160			
131g	B12	1	2	2	2800	51	840	455	160			
131h	B12	1	2	2	2875	51	840	495	160			
132a	B16	1	34	34	1650	51	465	225	210			
132b	B16	1	2	2	1650	51	465	230	210			
132c	B16	1	2	2	1675	51	465	240	210			
132d	B16	1	2	2	1700	51	465	255	210			
132e	B16	1	2	2	1750	51	465	275	210			
132f	B16	1	2	2	1800	51	465	305	210			
132g	B16	1	2	2	1875	51	465	340	210			
132h	B16	1	2	2	1950	51	465	380	210			
133a	B16	1	2	2	3400	99	830	590	500	585	105	
133b	B16	1	2	2	3500	99	830	640	500	640	115	
133c	B16	1	2	2	3625	99	830	700	500	695	130	
133d	B16	1	2	2	3750	99	830	765	500	760	140	
133e	B16	1	2	2	3900	99	830	845	500	840	155	
133f	B16	1	2	2	4100	99	830	935	500	925	175	
133g	B16	1	2	2	4250	99	830	1020	500	1010	190	
133h	B16	1	2	2	4425	99	830	1105	500	1095	205	
133j	B16	1	2	2	4600	99	830	1190	500	1175	225	
133k	B16	1	2	2	4750	99	830	1270	500	1260	240	
133l	B16	1	2	2	4925	99	830	1355	500	1340	255	
133m	B16	1	2	2	4925	99	830	1350	500	1335	255	
133n	B16	1	2	2	4700	99	830	1235	500	1225	230	
133p	B16	1	2	2	4450	99	830	1120	500	1110	210	
133q	B16	1	2	2	4225	99	830	1005	500	1000	190	
133r	B16	1	2	2	4000	99	830	895	500	885	165	
133s	B16	1	2	2	3775	99	830	780	500	775	145	

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
								A				
					Mks. 133, 134, 135, 136				C			
								B		D		
								E	A			
134a	B16	1	2	2	2150	99	455	490	210	490	85	
134b	B16	1	2	2	2250	99	455	540	210	540	95	
134c	B16	1	2	2	2375	99	455	600	210	600	110	
134d	B16	1	2	2	2525	99	455	670	210	665	120	
134e	B16	1	2	2	2675	99	455	745	210	745	135	
134f	B16	1	2	2	2850	99	455	835	210	830	155	
134g	B16	1	2	2	3025	99	455	925	210	915	170	
134h	B16	1	2	2	3200	99	455	1010	210	1000	190	
134j	B16	1	2	2	3375	99	455	1095	210	1085	205	
134k	B16	1	2	2	3525	99	455	1175	210	1165	220	
134l	B16	1	2	2	3650	99	455	1240	210	1225	230	
134m	B16	1	2	2	3425	99	455	1125	210	1115	210	
134n	B16	1	2	2	3200	99	455	1010	210	1000	190	
134p	B16	1	2	2	2975	99	455	895	210	890	165	
134q	B16	1	2	2	2750	99	455	780	210	775	145	
134r	B16	1	2	2	2500	99	455	665	210	665	120	
134s	B16	1	2	2	2275	99	455	550	210	550	100	
135a	B16	1	2	2	3325	99	825	555	500	550	135	
135b	B16	1	4	4	2900	99	825	350	500	350	135	
136	B16	1	6	6	1875	99	450	350	210	350	80	
137	B16	1	17	17	1650	21	775	160	(775)			
138a	B20	1	1	1	1900	13	905	180	(905)			
138b	B20	1	1	1	1900	13	905	180	(905)			
138c	B20	1	1	1	1900	13	905	185	(905)			
138d	B20	1	1	1	1925	13	905	205	(905)			
138e	B20	1	1	1	1950	13	905	230	(905)			
138f	B20	1	1	1	1975	21	905	260	(905)			
138g	B20	1	1	1	2000	21	905	300	(905)			
139a	B20	1	1	1	2100	29	885	405	(905)	415	60	
139b	B20	1	1	1	2150	99	885	460	(905)	470	70	
139c	B20	1	1	1	2200	99	885	520	(905)	530	85	
139d	B20	1	1	1	2275	99	885	590	(905)	595	95	
139e	B20	1	1	1	2350	99	885	670	(905)	675	115	
139f	B20	1	1	1	2450	99	885	760	(905)	765	130	
139g	B20	1	1	1	2525	99	885	845	(905)	850	145	
139h	B20	1	1	1	2625	99	885	935	(905)	935	165	
139j	B20	1	1	1	2700	99	885	1020	(905)	1015	180	
139k	B20	1	1	1	2800	99	885	1100	(905)	1095	195	
139l	B20	1	1	1	2850	99	885	1160	(905)	1155	210	
139m	B20	1	1	1	2750	99	885	1050	(905)	1045	185	
139n	B20	1	1	1	2625	99	885	935	(905)	935	165	
139p	B20	1	1	1	2500	99	885	820	(905)	820	140	
139q	B20	1	1	1	2400	99	885	705	(905)	710	120	
139r	B20	1	1	1	2275	99	885	590	(905)	595	95	
139s	B20	1	1	1	2175	99	885	475	(905)	485	75	
140	B20	1	3	3	1950	29	880	265	(905)	280	50	
									A			
					Mks. 139, 140				D B E (C)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
141	B16	1	34	34	1650	21	775	160	(775)			
142	B16	1	8	8	1075	21	300	520	(300)			
143	B12	1	8	8	1275	21	400	520	(400)			
144	B12	1	4	4	2075	11	780	(1300)				
146a	B12	1	4	4	2875	21	205	2495	(205)			
146b	B12	1	4	4	2500	21	205	2135	(205)			
146c	B12	1	4	4	2150	21	205	1775	(205)			
146d	B12	1	4	4	1775	21	205	1405	(205)			
146e	B12	1	4	4	1400	21	205	1030	(205)			
146f	B12	1	4	4	1025	21	205	650	(205)			
147	B16	1	12	12	3050	29	1490	725	(885)	715	170	
									A			
					Mk. 147,151,153				D B E (C)			
148	B16	1	12	12	1850	21	210	715	(970)			
149	B16	1	12	12	3175	21	1500	325	(1400)			
150	B12	1	14	14	2600	99	250	725	730	190	715	
									C D B			
					Mk. 150				E B D A			
151	B12	1	16	16	3300	29	1485	340	(1500)	340	80	
153	B12	1	4	4	3300	29	1485	340	(1500)	340	80	
154	B16	1	12	12	2975	11	1495	(1500)				
155	B16	1	12	12	2600	21	975	710	(975)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2165-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

	Name	Position	Signature	Date
Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS 9.4m EXTERNAL UNIT RIGHT SKEW 15°

SHEET 2

Scale	AS SHOWN	
Drawing Number	NR/CIV/SD/2165-2	B

Full document details: NR NR-CIV-SD- 2165-2 ISSUE B 2012

AVA Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or distribution permitted without prior licence from IHS

Licensee=Mott MacDonald Group Limited 5911111001, User=sam, allan
No reproduction or distribution permitted without prior licence from IHS