The following information is associated with Network Rail Standard:
NR CIV/SD/2167-2 Rev B

Additional Content Access

Click the link below to access CAD version of this drawing.

CAD Drawing

- CIV/SD/2167-2

If you have any questions, or need assistance, please contact **IHS Support**

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

Documents
Document Sharing Hub

Copyright Network Rail
Provided by IHS under license with Network Rail
No reproduction or networking permitted without license from IHS
Full document details: NR NR-CIV-SD-2167-2 ISSUE B 2012

Licensee=Weston Williamson/5989497001, User=sam, albett
Not for Resale, 03/27/2016 19:54:24 MDT

Drg No. 2167

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
101	B25	1	2	2	4950	99	1225	425	1650	425	(1225)	
							52		0 RAD		52	
102	B20	1	6	6	4475	99	985	425	1650	425	(985)	
							52		0 RAD		52	
103	B32	1	8	8	9950	99	1590		6755		1590	
							4635 RAD		40010 RAD		4665 RAD	
105	B40	1	12	12	7675	99	5935	5905	(1730)	625	39760	
106	B32	1	4	4	7675	99	5935	5905	(1730)	625	39765	
							B; A; D; R; (C)					
							MKS 105 & 106					
107	B32	1	16	16	4310	15	1235	570	(3075)			
109	B32	1	4	4	1600	23	465	1000	(305)			
110	B25	1	12	12	1475	23	365	1000	(240)			
115	B16	1	16	16	1475	21	600	330	(600)			
131a	B12	1	46	46	3175	51	1150	335	160			
131b	B12	1	2	2	3200	51	1150	345	160			
131c	B12	1	2	2	3200	51	1150	350	160			
131d	B12	1	2	2	3225	51	1150	355	160			
131e	B12	1	2	2	3250	51	1150	370	160			
131f	B12	1	2	2	3275	51	1150	380	160			
131g	B12	1	2	2	3300	51	1150	400	160			
131h	B12	1	2	2	3350	51	1150	420	160			
131j	B12	1	2	2	3400	51	1150	445	160			
131k	B12	1	2	2	3450	51	1150	470	160			
131l	B12	1	2	2	3525	51	1150	505	160			
132a	B16	1	46	46	2000	51	635	225	210			
132b	B16	1	2	2	2000	51	635	230	210			
132c	B16	1	2	2	2000	51	635	235	210			
132d	B16	1	2	2	2025	51	635	240	210			
132e	B16	1	2	2	2050	51	635	255	210			
132f	B16	1	2	2	2075	51	635	265	210			
132g	B16	1	2	2	2100	51	635	285	210			
132h	B16	1	2	2	2150	51	635	305	210			
132j	B16	1	2	2	2200	51	635	330	210			
132k	B16	1	2	2	2250	51	635	355	210			
132l	B16	1	2	2	2325	51	635	390	210			
133a	B16	1	2	2	4125	99	1105	675	500	585	385	
133b	B16	1	2	2	4225	99	1105	730	500	625	415	
133c	B16	1	2	2	4350	99	1105	785	500	670	450	
133d	B16	1	2	2	4475	99	1105	850	500	725	485	
133e	B16	1	2	2	4625	99	1105	925	500	780	530	
133f	B16	1	2	2	4800	99	1105	1010	500	850	580	
133g	B16	1	2	2	4975	99	1105	1100	500	920	635	
133h	B16	1	2	2	5150	99	1105	1190	500	995	685	
133j	B16	1	2	2	5325	99	1105	1275	500	1065	740	

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
133k	B16	1	2	2	5500	99	1105	1365	500	1135	790	
133l	B16	1	2	2	5675	99	1105	1450	500	1205	840	
133m	B16	1	2	2	5850	99	1105	1535	500	1270	890	
133n	B16	1	2	2	6000	99	1105	1615	500	1340	940	
133p	B16	1	2	2	6050	99	1105	1635	500	1350	950	
133q	B16	1	2	2	5800	99	1105	1515	500	1255	880	
133r	B16	1	2	2	5575	99	1105	1400	500	1165	810	
133s	B16	1	2	2	5325	99	1105	1280	500	1070	740	
133t	B16	1	2	2	5100	99	1105	1160	500	975	670	
133u	B16	1	2	2	4850	99	1105	1045	500	880	600	
133v	B16	1	2	2	4625	99	1105	925	500	785	530	
							A; C; D; B; E; A					
					Mks. 133, 134, 135, 136							
134a	B16	1	2	2	2550	99	590	555	210	485	310	
134b	B16	1	2	2	2675	99	590	610	210	530	345	
134c	B16	1	2	2	2775	99	590	665	210	575	380	
134d	B16	1	2	2	2900	99	590	730	210	625	415	
134e	B16	1	2	2	3050	99	590	805	210	685	460	
134f	B16	1	2	2	3225	99	590	890	210	755	510	
134g	B16	1	2	2	3400	99	590	980	210	825	565	
134h	B16	1	2	2	3600	99	590	1070	210	900	615	
134j	B16	1	2	2	3775	99	590	1160	210	970	670	
134k	B16	1	2	2	3950	99	590	1245	210	1040	720	
134l	B16	1	2	2	4100	99	590	1330	210	1110	775	
134m	B16	1	2	2	4275	99	590	1415	210	1180	825	
134n	B16	1	2	2	4400	99	590	1475	210	1225	855	
134p	B16	1	2	2	4150	99	590	1355	210	1130	785	
134q	B16	1	2	2	3925	99	590	1235	210	1035	715	
134r	B16	1	2	2	3700	99	590	1120	210	940	645	
134s	B16	1	2	2	3450	99	590	1000	210	845	575	
134t	B16	1	2	2	3225	99	590	885	210	750	505	
134u	B16	1	2	2	2975	99	590	765	210	655	435	
134v	B16	1	2	2	2750	99	590	650	210	560	365	
135a	B16	1	2	2	4150	99	1080	710	500	550	480	
135b	B16	1	4	4	3575	99	1080	425	500	350	480	
136	B16	1	6	6	2250	99	565	425	210	350	280	
137	B16	1	23	23	2225	21	1060	160	(1060)			
138a	B20	1	1	1	2550	13	1235	180	(1235)			
138b	B20	1	1	1	2550	13	1235	180	(1235)			
138c	B20	1	1	1	2550	13	1235	180	(1235)			
138d	B20	1	1	1	2550	13	1235	180	(1235)			
138e	B20	1	1	1	2575	13	1235	195	(1235)			
138f	B20	1	1	1	2575	13	1235	210	(1235)			
138g	B20	1	1	1	2600	13	1235	230	(1235)			
138h	B20	1	1	1	2625	13	1235	255	(1235)			
138j	B20	1	1	1	2650	21	1235	280	(1235)			
138k	B20	1	1	1	2675	21	1235	310	(1235)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

Bar mark	Type and size	No. of mbrs	No. of bars in each	Total no.	Length of each bar † mm	Shape code	A* mm	B* mm	C* mm	D* mm	E/R* mm	Rev letter
139a	B20	1	1	1	2700	29	1145	425	(1235)	410	215	
139b	B20	1	1	1	2750	29	1145	480	(1235)	455	250	
139c	B20	1	1	1	2825	29	1145	540	(1235)	505	285	
139d	B20	1	1	1	2875	29	1145	605	(1235)	555	325	
139e	B20	1	1	1	2950	29	1145	680	(1235)	620	365	
139f	B20	1	1	1	3050	29	1145	765	(1235)	685	420	
139g	B20	1	1	1	3150	29	1145	860	(1235)	760	470	
139h	B20	1	1	1	3225	29	1145	950	(1235)	830	525	
139j	B20	1	1	1	3325	29	1145	1035	(1235)	905	580	
139k	B20	1	1	1	3400	29	1145	1125	(1235)	975	630	
139l	B20	1	1	1	3500	29	1145	1210	(1235)	1045	680	
139m	B20	1	1	1	3575	29	1145	1295	(1235)	1110	730	
139n	B20	1	1	1	3625	29	1145	1350	(1235)	1155	765	
139p	B20	1	1	1	3525	29	1145	1235	(1235)	1060	695	
139q	B20	1	1	1	3400	29	1145	1115	(1235)	965	625	
139r	B20	1	1	1	3275	29	1145	1000	(1235)	870	555	
139s	B20	1	1	1	3150	29	1145	880	(1235)	775	485	
139t	B20	1	1	1	3050	29	1145	760	(1235)	680	415	
139u	B20	1	1	1	2925	29	1145	645	(1235)	590	345	
139v	B20	1	1	1	2800	29	1145	525	(1235)	495	275	
140	B20	1	3	3	2525	29	1110	270	(1235)	280	155	
									A; D; B; E; (C)			
					Mks. 139, 140							
141	B20	1	48	48	2550	13	1235	180	(1235)			
142	B16	1	16	16	1250	21	300	705	(300)			
143	B12	1	8	8	1475	21	400	705	(400)			
144	B12	1	4	4	2075	11	780	(1300)				
146a	B12	1	4	4	3000	21	280	2470	(280)			
146b	B12	1	4	4	2625	21	280	2110	(280)			
146c	B12	1	4	4	2275	21	280	1750	(280)			
146d	B12	1	4	4	1900	21	280	1380	(280)			
146e	B12	1	4	4	1525	21	280	1005	(280)			
146f	B12	1	4	4	1150	21	280	625	(280)			
147	B20	1	14	14	3400	29	1485	1165	(850)	1160	200	
									A; D; B; E; (C)			
					Mk. 147,151,153							
148	B20	1	14	14	2275	21	290	1160	(935)			
149	B20	1	14	14	3250	21	1500	455	(1400)			
150	B12	1	14	14	3650	99	250	1135	(965)	840	840	
							C; D; B; E; B; D; A					
					Mk. 150							
151	B12	1	16	16	3875	29	1720	425	(1770)	340	290	
153	B12	1	4	4	3875	29	1720	425	(1770)	340	290	
154	B20	1	12	12	3225	11	1770	(1500)				
155	B20	1	16	16	2750	21	940	975	(940)			

This schedule conforms to BS 8666: 2005

* Specified in multiples of 5 mm. † Specified in multiples of 25 mm.

DRAWING No. NR/CIV/SD/2167-2

NOTES

1. FOR GENERAL NOTES REFER TO DRAWING No. NR/CIV/SD/2001.

Rev	Date	Description of revision	Designed	C'kd
B	27.04.12	SECOND ISSUE	SzT	SWF
A	12.10.10	FIRST ISSUE	SzT	SWF

Network Rail

Network Rail Infrastructure Ltd. Registered Office: Kings Place, 90 York Way, London, N1 9AG

Approved	P. Clark	Head of Engineering IP Central	PC	Apr 2013
	Name	Position	Signature	Date

Master copy with original signatures held by Network Rail HQ CIVIL ENGINEERING STANDARD DESIGN

© COPYRIGHT NETWORK RAIL 2013

STANDARD CONARCH OVERBRIDGE

REINFORCEMENT DETAILS 9.4m EXTERNAL UNIT RIGHT SKEW 45°

SHEET 2

Scale	AS SHOWN	
Drawing Number	NR/CIV/SD/2167-2	B

Full document details: NR NR-CIV-SD-2167-2 ISSUE B 2012

Documents Document Sharing Hub

Copyright Network Rail
Provided by IHS under licence with Network Rail
No reproduction or networking permitted without licence from IHS

Licensee=Atkins Limited/5944001, User=sian, single
Not for Resale, 12/03/2014 07:00:59MDT