

Ref:	NR/L2/ELP/27009/MOD C38
Issue:	1
Date:	03/12/2011
Compliance date:	03/03/2012
Page	1 of 2

OVERHEAD LINE CAMPAIGN CHANGES – DATA SHEET	
38	SKIDDED NEUTRAL SECTIONS AND SKIDLESS CERAMIC BEADS FOR CLASS 373 PANTOGRAPHS
COMPONENT	<p>Skidded neutral sections and 1090 mm long ceramic bead insulators in skidless neutral sections, in areas where Class 373 pantographs run (with 400 mm wide pantograph head).</p> <p>This campaign change is specific to the class 373 pantograph. Introduction of other rolling stock will be subject to a compatibility assessment and issue of a new campaign change if needed.</p>
PROBLEM	<p>The pantograph head of the class 373 pantograph is wider than the standard Brecknell Willis pantographs (400mm wide). This will short out more of the in line insulator, leading to increased risk of flashover.</p> <p><i>Note: This campaign change was previously reported as completed.</i></p>

Reference Information	
Ellipse standard job number	13038
Ellipse standard job description	Replace BICC skidded / skidless NS
Category	Neutral section
Priority	No
Types of OLE affected	Mk1; Mk3a; Mk3b.
Original equipment dates	Before 1998

Ref:	NR/L2/ELP/27009/MOD C38
Issue:	1
Date:	03/12/2011
Compliance date:	03/03/2012
Page	2 of 2

OVERHEAD LINE CAMPAIGN CHANGES – DATA SHEET

38

SKIDDED NEUTRAL SECTIONS AND SKIDLESS CERAMIC BEADS FOR CLASS 373 PANTOGRAPHS

ACTION REQUIRED

1. Replace with Arthur Flury skidless neutral section or fit extended length ceramic bead skidless neutral section.
2. Alternatively, implement speed restrictions.

