

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 Dec 2008
Compliance date:	01 March 2009

Level 2

Design and Installation of Underfloor Wheel Lathes

Endorsement and Authorisation

Endorsed by:



Malcolm Miles, Senior Rail Plant Engineer

Authorised by:



Allan Jones, Head of Rail Vehicle Engineering

Accepted for issue by:



Mick McManus National Standards Manager

This document is the property of Network Rail. It shall not be reproduced in whole or part nor disclosed to a third party without the written permission of Network Rail.
© Copyright 2008 Network Rail.

Uncontrolled copy once printed from its electronic source.

Published and Issued by Network Rail, Kings Place, 90 York Way, London. N1 9AG.

Network Rail



Documents

Document Sharing Hub

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 December 2008
Compliance date:	01 March 2009

Issue record

Issue	Date	Comments
1	Dec 2008	First Issue

Compliance

This Network Rail standard is mandatory and shall be complied with by Network Rail and its contractors if applicable from 1st March 2009.

When this standard is implemented, it is permissible for all projects that have formally completed GRIP Stage 4 to continue to comply with the Issue of any relevant Network Rail Standards current when GRIP Stage 4 was reached and not to comply with requirements contained herein, unless the designated Standard Owner has stipulated otherwise in the accompanying Briefing Note.

Reference documentation

GI/RT7007	Low Voltage Electrical Installations
GI/GN7607	Guidance on Low Voltage Electrical Installations
GM/RT2466	Railway Wheelsets
GM/RC2566	Recommendations for Railway Wheelsets
NR/L2/RVE/0134	Shunting Vehicles for use with Underfloor Wheel Re-profiling Machines
BS 1134-1	Assessment of Surface Texture Methods and Instrumentation
BS 5378	Safety Signs and Colours
BS 5892-6	Railway Rolling Stock Materials. Specification for Wheelsets for Traction and Rolling Stock
BS EN 953	Safety of Machinery. Guards. General Requirements for the Design and Construction of Fixed and Moveable Guards
BS EN 982	Safety of Machinery. Safety Requirements for Fluid Power Systems and their Components. Hydraulics.
BS EN 13788	Machine tools. Safety. Multi spindle Automatic Turning Machines
BS EN 60204 - 1	Safety of machinery. Electrical Equipment of Machines.
BS EN 60529	Specification for Degrees of Protection Provided by Enclosures (IP Rating)
BS EN ISO 12100 - 1	Safety of Machinery. Basic concepts, General Principles for Design, Basic Terminology, Methodology.
BS EN ISO 12100 - 2	Safety of Machinery. Basic concepts, General Principles for Design, Technical Principles
BS EN ISO/IEC 17050	Conformity Assessment. Suppliers Declaration of Conformity
89/336/EEC	Electro-Magnetic Compatibility Directive

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 December 2008
Compliance date:	01 March 2009

Disclaimer

In issuing this document for its stated purpose, Network Rail makes no warranties, express or implied, that compliance with all or any documents it issues is sufficient on its own to ensure safe systems of work or operation. Users are reminded of their own duties under health and safety legislation.

Supply

Copies of documents are available electronically, within Network Rail's organisation. Hard copies of this document may be available to Network Rail people on request to the relevant controlled publication distributor. Other organisations may obtain copies of this document from IHS (Technical Indexes Ltd) tel: 01344 328039.

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 December 2008
Compliance date:	01 March 2009

Contents

1 Purpose	5
2 Scope	5
3 Definitions	5
4 Requirements	8
4.1 General	8
4.2 Machine Details	8
4.3 Electrical Requirements	12
4.4 Hydraulic Systems	13
4.5 Machine Safety	13
4.6 Machine Interfaces	13
5 Performance Requirements	13
6 Machine Accessories	14
7 Acceptance	14
8 Design Interfaces	14
9 Documentation	15
Appendix A – Machining Parameters and Accuracies	17
Appendix B – Rolling Stock Parameters	18

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 December 2008
Compliance date:	01 March 2009

1 Purpose

This specification defines the requirements for the design, manufacture, installation, testing, commissioning and handback of new underfloor wheel re-profiling facilities procured by, or on behalf of Network Rail for use within their Light Maintenance depots (LMD's).

2 Scope

This specification applies to any new re-profiling facility that Network Rail owns outright, or has a management or engineering responsibility for, under various finance lease or hire agreements. These facilities are either operated by Network Rail or, under contractual or lease agreement, by a third party Train Operator.

3 Definitions

Depth of Cut

The amount by which the radius of a wheel is reduced in a single cutting pass.

Diameter Parity

The maximum permissible variation on diameter between one wheel and another on the same axle when measured at the specified gauging plane.

Flange Height

The difference between the radius of the wheel at the tip of the flange, and the radius of the wheel at the tread datum position.

Flange Thickness

The thickness of the flange at a point 13mm above the tread datum position.

Minimum Metal

The least amount of metal which would be required to be taken off the smallest wheel set in order to re-profile that wheel leaving a witness mark of maximum width 10mm.

Radial Run Out

The variation of position of the considered feature with respect to a fixed point during one complete revolution about the datum axis without axial movement.

Re-profile

To machine a wheel or wheels on a wheelset to restore the wheel rim to its original profile or if so desired, a new profile.

Section of Cut

The area of metal being removed at the point of cut (sq. mm.) derived from the depth of cut (mm) x feed rate (mm/rev).

Surface Finish

The specified limit of surface roughness in accordance with BS 1134.

Wheel Rim

The whole of the wheel periphery from and including the chamfer at the outer edge of the wheel up to the point of blending of the flange crown radius with the inside face of the wheel.

Ref:	NR/L2/RVE/0133
Issue:	1
Date:	01 December 2008
Compliance date:	01 March 2009

Wheelset

A complete unit comprising an axle and two complete wheels together with any gear wheels, brake discs, etc, but without axle bearings and their end caps, spacers seals and other associated fittings.

Wheelset Back-to-Back Dimension

The dimension between the wheelset flange-back faces, measured parallel to the axle centreline with the wheelset in the free (unloaded) condition.

Wheel Wobble

The total axial displacement of the wheel tread when the wheelset is rotated, measured at the flange back.

Witness Mark

An area of unmachined material which can remain after re-profiling a previously worn tread to demonstrate that the minimum of material has been removed.

NOTE No witness mark will be acceptable if thermal damage is present.

All other terms used within this document shall have their meaning as described in the relevant Railway Group Standards or other applicable Network Rail document.




Figure 1 – Definition of Profile