

Ref:	NR/L2/SIG/30097/AppD1
Issue:	2
Date:	2 June 2012
Compliance date:	2 June 2012

Level 2 module

Appendix D1: Ergonomics requirements

Endorsement and Authorisation

For endorsement, authorisation and acceptance for use, please refer to NR/L2/SIG/30097, *Modular Signalling*.

NR/L2/SIG/30097/AppD1

This document is the property of Network Rail. It shall not be reproduced in whole or part nor disclosed to a third party without the written permission of Network Rail.

© Copyright 2012 Network Rail.

Uncontrolled copy once printed from its electronic source.

Published and Issued by Network Rail, Kings Place, 90 York Way, London. N1 9AG.



Ref:	NR/L2/SIG/30097/AppD1
Issue:	2
Date:	2 June 2012
Compliance date:	2 June 2012

User information

This Network Rail standard contains colour-coding according to the following Red–Amber–Green classification.

Red requirements – *No deviations, could stop the railway*

- **Red requirements shall** always be complied with and achieved.
- Red requirements shall be presented in a red box **with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of red requirements lies with the Professional Head/Standard Owner.
- Red requirements are monitored for compliance.
- Corrective actions shall be enforced if deviations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

Amber requirements – *Controlled deviations, approved risk analysis and mitigation*

- **Amber requirements shall** be complied with unless deviation has been approved in advance.
- Amber requirements shall be presented with an amber sidebar **and with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of these requirements lies with the Professional Head/Standard Owner, or their nominated Delegated Authority.
- Amber requirements are monitored for compliance.
- Deviations **may** be permitted. Deviations are approved by the Standard Owner or through existing Delegated Authority arrangements.
- Corrective actions shall be enforced if **non-approved** deviations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

Green – *Guidance*

- Guidance is based on good practice. Guidance represents supporting information to help achieve **Red** and **Amber** requirements.
- Guidance shall be presented with a dotted green sidebar **and with the word “should” (usually in notes) or as a direct instruction**.
- Guidance is **not mandatory** and is not monitored for compliance.
- Alternative solutions may be used. Alternative solutions do not need to be formally approved.
- Decisions made by a competent person to use alternative solutions should be backed up by appropriate evidence or documentation.

Ref:	NR/L2/SIG/30097/AppD1
Issue:	2
Compliance date:	2 June 2012

Electronic File Location

This document is located within Network Rail's Corporate Content Management System (CCMS), and has the unique reference no.:

Version History

Issue	Date	Comments
1.0	31/05/10	First issue for guidance
2.0	20/02/12	Second issue

Disclaimer

In issuing this document for its stated purpose, Network Rail makes no warranties, express or implied, that compliance with all or any documents it issues is sufficient on it's own to ensure safe systems of work or operation. Users are reminded of their own duties under health and safety legislation.

Ref:	NR/L2/SIG/30097/AppD1
Issue:	2
Compliance date:	2 June 2012

1.	INTRODUCTION	4
1.1	Background	4
1.2	Purpose	4
1.3	Scope	4
1.4	Definitions	4
2.	ERGONOMICS REQUIREMENTS FOR MODULAR SCHEMES.....	6
2.1	Engineering Assurance	6
2.2	Signaller workload demand prediction.	7
2.2.1	General Background.....	7
2.2.2	Pre-GRIP – Baseline workload assessments.....	7
2.2.3	GRIP 3/4 –Validation of initial workload predictions.....	8
2.3	Validation of Standard Workstation Design.	8
2.4	Control Centre.....	9
2.5	Alarm Management Strategy	10