

The following information is associated with Network Rail Standard:
NR/L3/CIV/140/025N Issue 1

Additional Content Access

Click the links below to access non PDF related content associated with this standard.

Word Document

- [NR/L3/CIV/140/025N](#)

If you have any questions, or need assistance, please contact [IHS Support](#)

Information accessed via the links above is the property of the Copyright holder

IHS Additional Content Page

RAILTRACK PLC

**MODEL CLAUSES FOR SPECIFYING
CIVIL ENGINEERING WORKS**

SECTION 25

**Presentation of Survey Data and
Information**

ISSUE NO. 1 REVISION A

RT/CE/C/008/025N

Page 1 of 16

Date: 30 September 1996

Submitted by: Keith Ross
Structures Standards Engineer
Civil Engineering Directorate
King's Cross

Approved by: Model Clauses (Civil Engineering)
Committee on 8 October 1996

Signature:
for Director, Civil Engineering

John Horsler
Civil Engineer, Structures Compliance
Chairman Model Clauses (Civil Engineering)
Committee

Amendments

Amendments and additions since the previous issue are marked by a vertical line in the right hand margin.

© Railtrack PLC 1997

This document is the property of Railtrack PLC. It shall not be reproduced in whole or in part without the written permission of the publisher for use external to Railtrack.

Published by

Director Civil Engineering,
Railtrack PLC,
Eastside Offices
King's Cross Station
London N1 9AP

Controlled document

No:.....

SECTION 25	PRESENTATION OF SURVEY DATA AND INFORMATION	
	SECTION CONTENTS	Page
	This table of contents does not form part of the Specification	
NOTES TO SPECIFIER	25.1 Scope of the survey and summary of requirements	3
	SPECIFICATION CLAUSES	
SECTION 25	PRESENTATION OF SURVEY DATA AND INFORMATION	
	25.001 Delivery of results	4
	25.002 Technical report on horizontal and vertical control	4
	25.003 Digital mapping for site verification	5
	25.004 Digital data drawings	5
	25.005 Presentation of detail	7
	25.006 Particular requirements for drawings	8
	25.007 String identification	8
	25.008 Macros	8
	25.009 Presentation and format of drawings	9
	25.010 Survey grid and orientation	9
	25.011 Lines, lettering and colours to be used on the drawings	10
	25.012 Project control information to be shown on drawing	11
	25.013 Notes to be shown on drawings	11
	25.014 Symbols and abbreviations	11
	25.015 Technical report	12
	25.016 Proofs, samples, reports, final information and materials to be supplied	12
	25.017 Approval of final drawings	13
APPENDIX	25A String Labels	14
REFERENCES	British Standards	16
	Railtrack Line Standards	16

SECTION 25

PRESENTATION OF SURVEY DATA AND INFORMATION

NOTES TO SPECIFIER:

These notes do not form part of the Specification.

**Scope of the
Section**

25.1

This Section specifies the requirements for the presentation of data arising from either an aerial or ground survey, and defines the requirements for digital mapping, drawings and technical reports. It should be read in conjunction with the corresponding survey Section.

All survey data and mapping should be related to Ordnance Survey National Grid but plotted to a true scale and to Newlyn height datum.

SECTION 25

PRESENTATION OF SURVEY DATA AND INFORMATION

Delivery of results	25.001	<p>The original records of observations, computations and adjustment, shall be supplied bound and indexed.</p> <p>Two sets of final results shall be supplied in robust ring binders containing:</p> <ul style="list-style-type: none"> (i) Horizontal and vertical control net diagrams, (ii) Abstracts of unadjusted and adjusted observations (eg height differences between bench marks), (iii) Lists of P.G.M.s, photopoints, Ordnance Survey control stations and bench marks used, with final National Grid and true grid co-ordinates and heights based on Ordnance Survey Newlyn datum together with the transformation factor, to allow transformation of true grid to Ordnance Survey co-ordinates, (iv) Designations of all P.G.M.s with location map, description, type of mark, photograph and instructions for gaining access if not on public access.
<i>Aerial survey only</i>		<ul style="list-style-type: none"> (v) Photo control results including diapositives, control prints and lists and descriptions of plan and height control points with run/exposure number of pricked aerial photograph.
<i>Moss surveys</i>	<i>!C!</i>	<ul style="list-style-type: none"> (vi) An ASCII Moss Genio Data file on a 1/4" magnetic tape!<i>CHECK!</i> containing true co-ordinates and height of all control stations, traverse stations and Ordnance Survey control stations. <p style="text-align: right;">(25.001)</p>
Technical report on horizontal and vertical control	25.002	<p>A concise technical report shall be provided as part of the final delivery of control results containing the following:</p> <ul style="list-style-type: none"> (i) A copy of the Contract Specification with any variations or agreed amendments, (ii) Horizontal and vertical control net diagrams (A3 size) showing connections to existing stations and bench marks and summaries of closures and residuals after adjustment, (iii) A description of the methods, equipment and staff employed on the project, (iv) Confirmation of the survey accuracy required and achieved, (v) A summary of the planned and actual programme of work and delivery schedule, (vi) Abstracts of unadjusted and adjusted observations (eg height differences between bench marks),

- (vii) Description of the method of adjustment of the horizontal and vertical net with rejected values, residuals etc,
- (viii) A quality management report describing the procedures used to test the accuracy, completeness and reliability of data and the results of tests,
- (ix) Comments on the specification and results and recommendations for future work.

A draft of the report shall be submitted for comment and amendment by the Employer's Representative and two copies of the final report shall be provided, one bound and one unbound.

(25.002)

**Digital mapping
for site verification**

25.003

Interpretative skills shall be used to complete detail features which are partly obscured or fully obscured for short distances, using the unreliable feature codes and dashed lines.

Features such as running rails, cess lines and railway boundaries which are required for mapping shall be continued through the Site as continuous strings.

The plans shall be plotted at 1:500 for site verification by Railtrack.

A paper plot from the actual data shall be provided with all survey files for comment or acceptance.

(25.003)

**Digital data
drawings**

25.004

All topographic mapping data shall be supplied to Railtrack as three dimensional strings. Each string within the system will have a unique label associated with it as a means of identification.

!C! The standard string identification as specified in Clause 25.008*!CHECK!* shall be used.

!C! The digital data shall be supplied as an AutoCAD 12 drawing file or in compatible DXF data transfer format and as three dimensional strings in Moss Genio format suitable for entry to Railtrack's Moss system in accordance with Table 25/1.*!CHECK!*

*Amend as applicable
to system in use*

Table 25/1 System Information	
System name	Moss
Data Interchange Format	Genio
Make of Computer	IBM RS6000
Exchange Data	Magnetic tape ¼" cartridge or 3½" diskette
Code	ASCII

The data will be considered as delivered once the information contained on the cartridge or diskette has been successfully loaded on to the Railtrack system and verified correct.