

GAUGING

User information

This Network Rail standard contains colour-coding according to the following Red–Amber–Green classification.

Red requirements – no variations permitted

- Red requirements are to be complied with and achieved at all times.
- Red requirements are presented in a red box.
- Red requirements are monitored for compliance.
- Non-compliances will be investigated and corrective actions enforced.

Amber requirements – variations permitted subject to approved risk analysis and mitigation

- Amber requirements are to be complied with unless an approved variation is in place.
- Amber requirements are presented with an amber sidebar.
- Amber requirements are monitored for compliance.
- Variations can only be approved through the national non-compliance process.
- Non-approved variations will be investigated and corrective actions enforced.

Green guidance – to be used unless alternative solutions are followed

- Guidance should be followed unless an alternative solution produces a better result.
- Guidance is presented with a dotted green sidebar.
- Guidance is not monitored for compliance.
- Alternative solutions should be documented to demonstrate effective control.

Amendment marks

- First document amendments are presented with a single black line to the right of the affected text.
- Second document amendments are presented with a double black line to the right of the affected text.

Contents

G.1.1a: Standard Structure Gauge	4
G.1.1b: Temporary Works Structure Gauge	7
Table 1 - Minimum Wire Heights for Standard Structure Gauge	5
Table 2 - Minimum Wire Heights for Temporary Works	8