

Ref:	SSI8505A
Issue:	6
Date:	05/09/2015
Compliance date:	06/12/2015

Module

Chapter A: Table of Contents

Endorsement and Authorisation

For endorsement, authorisation and issue record of this document, please refer to the SSI Applications Manual Contents, NR/L2/SIG/17002

This document is the property of Network Rail. It shall not be reproduced in whole or part nor disclosed to a third party without the written permission of Network Rail.

© Copyright 2015 Network Rail.

Uncontrolled copy once printed from its electronic source.

Published and Issued by Network Rail, 2nd Floor, One Eversholt Street, London. NW1 2DN.



Ref:	SSI8505A
Issue:	6
Date:	05/09/2015
Compliance date:	06/12/2015

User information

This Network Rail standard contains colour-coding according to the following Red–Amber–Green classification.

Red requirements – *No variations, could stop the railway*

- **Red requirements shall** always be complied with and achieved.
- Red requirements shall be presented in a red box **with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of red requirements lies with the Professional Head/Standard Owner.
- Red requirements are monitored for compliance.
- Corrective actions shall be enforced if deviations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

Amber requirements – *Controlled variations, approved risk analysis and mitigation*

- **Amber requirements shall** be complied with unless variation has been approved in advance.
- Amber requirements shall be presented with an amber sidebar **and with the word “shall” or expressed as a direct instruction**.
- Accountability for the efficacy of these requirements lies with the Professional Head/Standard Owner, or their nominated Delegated Authority.
- Amber requirements are monitored for compliance.
- Variations **may** be permitted. Variations are approved by the Standard Owner or through existing Delegated Authority arrangements.
- Corrective actions shall be enforced if **non-approved** variations are discovered through functional checks (e.g. engineering verification visits, audit or Operations Self-Assurance).

Green – *Guidance*

- Guidance is based on good practice. Guidance represents supporting information to help achieve **Red** and **Amber** requirements.
- Guidance shall be presented with a dotted green sidebar **and with the word “should” (usually in notes) or as a direct instruction**.
- Guidance is **not mandatory** and is not monitored for compliance.
- Alternative solutions may be used. Alternative solutions do not need to be formally approved.
- Decisions made by a competent person to use alternative solutions should be backed up by appropriate evidence or documentation.

Ref:	SSI8505A
Issue:	6
Date:	05/09/2015
Compliance date:	06/12/2015

Contents

1 Chapter A	4
2 Chapter B: General Information	4
3 Chapter C: Data Production	4
4 Chapter D: Installation, Testing and Commissioning	4
5 Chapter E: Maintenance	5
6 Chapter F: Record Keeping	5
7 Chapter G: EPROM and Memory Module Programming	6