



*NSF International Standard /
American National Standard*

NSF/ANSI 62 - 2015

Drinking Water Distillation Systems



Document Sharing Hub

NSF International, an independent, not-for-profit, non-governmental organization, is dedicated to being the leading global supplier of public health and safety-based risk management services serving the interests of all stakeholders.

This Standard is subject to revision.
Contact NSF to confirm this revision is current.

Users of this Standard may request clarifications and interpretations, or propose revisions by contacting:

Chair, Joint Committee on Drinking Water Treatment Units
c/o NSF International
789 North Dixboro Road, P. O. Box 130140
Ann Arbor, Michigan 48113-0140 USA
Phone: (734) 769-8010 Telex: 753215 NSF INTL
FAX: (734) 769-0109 E-mail: info@nsf.org
Web: <http://www.nsf.org>

NSF International Standard/
American National Standard
for Drinking Water Treatment Units –

Drinking water distillation systems

Standard Developer

NSF International

NSF International Board of Directors

Designated as an ANSI Standard

April 26, 2015

Designated as an American National Standard

Prepared by
The NSF Joint Committee on Drinking Water Treatment Units

Recommended for Adoption by
The NSF Council of Public Health Consultants

Adopted by
The NSF Board of Directors
May 1989

Revised November 1992
Revised September 1997
Revised September 1999
Addendum, June 2002
Revised February 2004
Revised October 2007
Revised August 2009
Revised February 2012
Revised December 2013
Revised January 2015
Revised October 2015

Published by

NSF International
P. O. Box 130140, Ann Arbor, Michigan 48113-0140, USA

For ordering copies or for making inquiries with regard to this Standard, please refer to the designation “NSF/ANSI 62 – 2015.”

Copyright 2015 NSF International
Previous edition © 2014, 2013, 2012, 2009, 2007, 2004, 1999, 1997, 1992, 1989

Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from NSF International.

Printed in the United States of America.

Disclaimers¹

NSF, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. The opinions and findings of NSF represent its professional judgment. NSF shall not be responsible to anyone for the use of or reliance upon this Standard by anyone. NSF shall not incur any obligation or liability for damages, including consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Standard.

NSF Standards provide basic criteria to promote sanitation and protection of the public health. Provisions for mechanical and electrical safety have not been included in this Standard because governmental agencies or other national standards-setting organizations provide safety requirements.

Participation in NSF Standards development activities by regulatory agency representatives (federal, local, state) shall not constitute their agency's endorsement of NSF or any of its Standards.

Preference is given to the use of performance criteria measurable by examination or testing in NSF Standards development when such performance criteria may reasonably be used in lieu of design, materials, or construction criteria.

The illustrations, if provided, are intended to assist in understanding their adjacent standard requirements. However, the illustrations may not include **all** requirements for a specific product or unit, nor do they show the only method of fabricating such arrangements. Such partial drawings shall not be used to justify improper or incomplete design and construction.

Unless otherwise referenced, the annexes are not considered an integral part of NSF Standards. The annexes are provided as general guidelines to the manufacturer, regulatory agency, user, or certifying organization.

¹ The information contained in this Disclaimer is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. Therefore, this Disclaimer may contain material that has not been subjected to public review of a consensus process. In addition, it does not contain requirements necessary for conformance to the Standard.

This page is intentionally left blank.

Contents

1	General	1
1.1	Scope	1
1.2	Minimum requirements.....	1
1.3	Chemical and microbiological reduction performance claims	1
1.4	Treatment train.....	1
1.5	Reviews and revisions.....	1
2	Normative references	2
3	Definitions	2
4	Materials	2
4.1	Materials in contact with drinking water	2
4.2	Materials evaluation	3
4.3	Gas chromatography/mass spectroscopy (GC/MS) analysis.....	5
5	Structural performance	14
5.1	Structural integrity.....	14
6	Minimum performance requirements.....	19
6.1	Total dissolved solids (TDS) reduction.....	19
6.2	Performance indication.....	23
6.3	Flow control	27
6.4	Storage tanks.....	27
6.5	Evaporator chamber.....	27
6.6	Openings and rims (product water zone)	27
6.7	Entry ports	27
6.8	Waste connections.....	28
6.9	Product water dispensing outlets.....	28
6.10	Active agents and additives	28
7	Elective performance claims – test methods	29
7.1	Inorganic chemical reduction claims qualified by TDS surrogate testing.....	29
7.2	Inorganic chemical reduction.....	29
7.3	In-place sanitization of the product water zone	33
7.4	Microbiological reduction.....	35
8	Instruction and information	39
8.1	Installation, operation, and maintenance instructions.....	39
8.2	Data plate	40
8.3	Replacement components.....	41
8.4	Performance data sheet	41
Annex A		A1
Annex B		B1
Annex C		C1
Annex D		D1

This page is intentionally left blank.

Foreword²

The purpose of this Standard is to establish minimum requirements for the materials, design and construction, and performance of point-of-use and point-of-entry drinking water distillation systems that are designed to reduce specific chemical and microbiological contaminants in public or private water supplies. NSF/ANSI 62 also specifies minimum product literature requirements that manufacturers must provide to authorized representatives and consumers.

Water contact materials in drinking water treatment units listed under NSF/ANSI 42, 44, 53, 55, 58, and 62 are tested and evaluated under a separate protocol from NSF/ANSI 61, with criteria that were developed specifically for the intended end-use. NSF/ANSI 61 listing should not be additionally required for acceptance of these listed units for water contact application.

This edition of the Standard contains the following revisions:

Issue 26

This revision added clarification regarding the maximum number of samples exposed in the Materials evaluation under section 4.

Issue 27

This revision added criteria for utilizing a treatment train approach for the evaluation of a system containing multiple, sequential treatment technologies.

Suggestions for improvement of this Standard are welcome. This Standard is maintained on a Continuous Maintenance schedule and can be opened for comment at any time. Comments should be sent to Chair, Joint Committee on Drinking Water Treatment Units at standards@nsf.org, c/o NSF International, Standards Department, P.O. Box 130140, Ann Arbor, Michigan 48113-0140, USA.

² The information contained in this Foreword is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. Therefore, this Foreword may contain material that has not been subjected to public review of a consensus process. In addition, it does not contain requirements necessary for conformance to the Standard.

This page is intentionally left blank.

NSF/ANSI Standard for Drinking Water Treatment Units –

Drinking water distillation systems

1 General

1.1 Scope

This standard establishes minimum materials, design and construction, and performance requirements for point-of-use and point-of-entry drinking water distillation systems and the components used in these systems. Distillation systems covered by this standard are designed to reduce specific chemical contaminants from potable drinking water supplies. Systems covered under this standard may also be designed to reduce microbiological contaminants, including bacteria, viruses, and cysts, from potable drinking water supplies. It is recognized that a system may be effective in controlling one or more of these contaminants, but systems are not required to control all.

Systems covered by this standard are not intended for the treatment of water that is visually contaminated (turbid) or has an obvious contamination source, such as raw sewage, nor are systems covered by this standard intended to convert wastewater to microbiologically potable water.

1.2 Minimum requirements

A system as defined in this standard shall meet the applicable requirements of Sections 4, 5, 6, and 8.

A component as defined in this standard shall meet the requirements of 4 and 8. If the component is pressure bearing, it shall also meet the applicable requirements of 5.

1.3 Chemical and microbiological reduction performance claims

1.3.1 All NSF/ANSI 62 performance claims shall be verified and substantiated by test data generated under the requirements of NSF/ANSI 62.

1.3.2 When performance claims are made for substances not specifically addressed in the scope of this Standard or for those substances not specifically addressed but falling under the scope of NSF/ANSI 62, those claims not specifically addressed in the Standard shall be so identified.

1.4 Treatment train

A system that contains multiple, sequential treatment technologies for a performance claim under this Standard shall meet the applicable requirements as described in Annex D.

1.5 Reviews and revisions

This Standard shall be reviewed at least every five years. The review is to be conducted by the NSF Joint Committee on Drinking Water Treatment Units.

2 Normative references

The following documents contain requirements which, by reference in this text, constitute requirements of this standard. At the time of publication, the indicated editions were valid. All standards are subject to revision and parties are encouraged to investigate the possibility of applying the recent editions of the standards indicated below. The most recent published edition of the document shall be used for undated references.

NSF/ANSI 61 – *Drinking water system components – Health effects*

APHA, Standard Methods for the Examination of Water and Wastewater, twentieth edition, 1998³

USEPA–600/4-79-020, Methods for the Chemical Analysis of Water and Wastes, March 1983⁴

USEPA-600-4-84-053, Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater, June 1984⁴

USEPA–600/4-88/039, Methods for the Determination of Organic Compounds in Drinking Water, December 1988⁴

USEPA-600/4-90/020, Methods for the Determination of Organic Compounds in Drinking Water - Supplement 1, July 1990⁴

USEPA–600/4-91/010, Methods for the Determination of Metals in Environmental Samples, June 1991⁴

USEPA *National Primary Drinking Water Regulations*, 40 CFR Part 141⁵ US EPA *National Secondary Drinking Water Regulations*, 40 CFR Part 143⁴

USEPA *National Secondary Drinking Water Regulations*, 56 CFR Part 3573⁴

US FDA Code of Federal Regulations, Title 21, (*Food and Drugs*) *Direct Food Additive Substances Parts 170 through 199*, April 1, 1992⁶

3 Definitions

Terms used in this Standard that have a specific technical meaning are defined in NSF/ANSI 330.

4 Materials

4.1 Materials in contact with drinking water

4.1.1 POE drinking water treatment units shall conform to the protocol and criteria in NSF/ANSI 61.

4.1.2 POU drinking water treatment units shall conform to the protocol and criteria in this section.

³ American Public Health Association (APHA), 1015 Fifteenth Street, NW, Washington, DC 20005 <www.apha.org>.

⁴ US Environmental Protection Agency (USEPA), Environmental Monitoring and Support Laboratory, Cincinnati, OH 45268 <www.epa.gov>.

⁵ Superintendent of Documents, US Government Printing Office, Washington, DC 20402 <www.gpo.gov>.

⁶ US Food and Drug Administration (US FDA), 5600 Fishers Lane, Rockville, MD 20857 <www.fda.gov>.

4.1.3 Acceptance criteria

4.1.3.1 Materials in contact with drinking water shall not impart levels of target compounds or Tentatively Identified Compounds (TICs) that exceed the Total Allowable Concentration (TAC), Maximum Contaminant Levels (MCL), or Maximum Acceptable Concentration (MAC) criteria specified in tables 1, 2 and 3 or specified in NSF/ANSI 61 Annex D and E. Any extractable contaminants not listed in the referenced tables shall be reviewed and shall not exceed criteria developed in accordance with NSF/ANSI 61 Annex A.

4.1.3.2 TIC identification and quantitation shall be conducted in accordance with section 4.3.1.2. Additional TIC identification and quantitation should be verified using a standard of the compound in question or an alternate approved analytical method. Additional TIC identification and quantitation is recommended when the contaminant is a health risk or when the “Probability Based Matching” process in section 4.3.1.2 is inconclusive. When possible, the product manufacturer should assist and support the testing laboratory in the identification of a standard for the compound and an appropriate analytical method, if applicable, so that confirmatory identification and quantification can be performed. If a standard and an adequate alternative analytical method are not available to verify the identification and quantitation of the compound, the TIC shall be evaluated according to section 4.3.1.2.

NOTE – Manufacturers may not be privy to formulation information, so they may not be able to assist a testing laboratory to identify a standard for the compound that extracted. Refer to Section 4.3.1.2 when the manufacturer does not have material formulation information.

4.1.3.3 Unknown contaminants detected by GC/MS analysis for which identification is unable to be made after performing the steps in 4.3.1 shall be reported in accordance to 4.1.4.2.

4.1.3.4 The concentration of active agents or additives used in the drinking water treatment process shall be evaluated in the product water as specified in 6.11. The concentration of active agents or additives used in the drinking water treatment process shall not be evaluated during extraction testing.

4.1.3.5 Whole-system or component assembly extraction testing may be waived if components, when separately tested, meet the requirements of this Standard and are assembled in a manner that does not introduce any new components or materials, increase the surface area-to-volume ratio of previously evaluated components, or present potential concern based on cumulative factors. The reported extractable concentrations for components shall be arithmetically added to ensure that the whole-system or component assembly meets the allowable levels in accordance with tables 1, 2, and 3 and Annex A, D, and E of NSF/ANSI 61.

4.1.4 Data reporting

4.1.4.1 All contaminants identified and detected at or above the reporting limit shall be reported with the identification of the contaminant, the concentration, and whether it exceeds the acceptance criteria as required in Section 4.1.3. Contaminants detected below the reporting limit shall be reported to the manufacturer as less than the reporting limit's value.

Example: If the lab's reporting limit is 1.0 mg/L for analyte “X” and the concentration was detected at 0.5 mg/L, the lab shall report less than 1.0 mg/L or <1.0 mg/L.

4.1.4.2 If the extractable contaminant cannot be identified following the procedures in 4.3.1 the laboratory shall supply the manufacturer with the approximate molecular weight along with any additional information about the compound.

4.2 Materials evaluation

Complete formulation information on any material not certified as specifically compliant with the sections of the U. S. Code of Federal Regulations, Title 21, listed in table 4, shall be reviewed to determine

whether the material presents a health effects concern in contact with drinking water and to assess the material's potential for contributing contaminants to the drinking water. As a minimum level of information for those materials requiring submission of formulation information, the complete chemical identity and proportion by weight (in some cases approximate weights or proportions may suffice) and ingredient sources of supply shall be provided.

The following additional information is required when available:

- a list of the known or suspected impurities within the product or material and the maximum percent or parts by weight of each impurity;
- the water solubility, hydrolysis products, and extraction rates of chemicals within the product or material; and
- a list of toxicological studies relevant to the chemicals and impurities present in the product, component, or material.

4.2.1 Analytical methods

All analyses shall be conducted in accordance with the applicable method(s) referenced in 2.

4.2.1.1 The laboratory shall validate the analytical method to the reporting limit (RL) concentration following the procedures established in the referenced method. The laboratory shall evaluate its method detection limit (MDL) in reference to the RL. In all cases, the RL shall be equal or greater than the MDL. When preparing its calibration standards, the lowest calibration point shall be at or less than the RL.

4.2.1.2 For extracted techniques (e.g., USEPA Method 625), regarding the concentration of the lowest calibration point, the laboratory shall apply the concentration factor due to sample preparation. For example, a sample one liter extracted, and the extract concentrated to 1.0 milliliter, for a factor of 1000, if the RL is set to 0.2 ug/L, then the lowest calibration point would be at or less than 0.2 mg/L.

NOTE – See Annex C for additional information on GC/MS and other alternative methods.

4.2.2 Exposure water

Systems and components shall be exposed to locally available tap water that has been adjusted to contain 50 ± 5 mg/L total dissolved solids, 0.5 ± 0.05 mg/L free available chlorine, and have a pH of 6.75 ± 0.25 . Exposure water used to evaluate systems or components shall be 23 ± 2 °C (73 ± 3 °F). Any existing concentrations of extraction testing parameters listed in Tables 1, 2, and 3 found to be present in the exposure water shall be subtracted from the values obtained in the analysis of the extractant water.

4.2.3 Exposure

4.2.3.1 The system or component(s) of a system shall be installed, flushed, and conditioned in accordance with the manufacturer's instructions using the exposure water specified in 4.2.2 at an initial inlet static pressure of 340 kPa (50 psig).

4.2.3.2 The system or component(s) shall be refilled with exposure water specified in 4.2.2 and operated according to manufacturer's instructions (if the system does not include a product water reservoir, the unit shall not be operated until immediately prior to sample collection). The system or component(s) shall be maintained for 24 h at an ambient temperature of 23 ± 2 °C (73 ± 3 °F). A 2-L water sample shall then be collected in accordance with 4.2.3.3. This procedure (4.2.3.2) shall be repeated two times for a total of three water sample collections.

4.2.3.3 A minimum sample volume of 2 L shall be collected at each sample point. If the water holding volume of the product is greater than 2 L, the entire volume shall be collected in a suitable collection

vessel, and a 2-L subsample obtained from this volume. If the water holding volume of the product is less than 2 L, sufficient samples shall be exposed to provide the required 2-L volume of extractant water. The maximum number of samples exposed shall not exceed 16 with 125 mL of extractant water drawn from each sample. If the components with a water-holding volume that is less than 250 mL and is able to be identified as one that will only occur once in the flow path of dispensed treated water (such as diverters, faucets, RO shutoff valves, or specialty components) then a volume of 250 mL shall be drawn from each sample using a maximum number of 8 samples.

4.2.3.4 All samples collected shall be composited and analyzed in accordance with 4.2.1.

4.2.3.5 Systems with adsorptive or absorptive media shall be tested with and without the media. Testing without media shall include removal of any granular adsorptive or absorptive media, and removal of any carbon block replacement elements.

4.3 Gas chromatography/mass spectroscopy (GC/MS) analysis

4.3.1 General requirements for GC/MS analysis

When determined to be required following a product-specific formulation review, USEPA Analytical Methods for semi-volatiles and volatiles that include mass spectral libraries shall be performed on products or components, and shall include full-range mass spectral libraries to monitor for non-target compounds.

Testing for semi-volatiles (e.g. USEPA Method 625 or 528 or 525.2) and volatiles (e.g. USEPA Method 524.2 or 524.3) shall be conducted using the required target compounds in Tables 2 and 3 and the laboratory's RL shall be no greater than the RL's listed in Tables 2 and 3.

4.3.1.1 Target compounds shall be validated in accordance with the requirements of the referenced method. USEPA Methods 524.2 and 625 have specific validation requirements including precision and accuracy requirements as well as demonstration of sensitivity (Method Detection Limit Study or MDL).

For USEPA Method 625, the minimum instrument operation requirements for GC/MS analysis shall be in accordance with those protocols as defined by the method with the following modifications:

- To guard against significant drift from an initial instrument calibration to subsequent instrument batches, the average chromatographic peak area of each internal standard in the calibration curve shall be determined. The chromatographic peak area of each internal standard in the continuing calibration shall be greater than 50% and not more than 200% of that average;
- Due to the number of characteristics of the analytes associated with method 625, while performing a continuing calibration check (CCC), concentrations of 10% of the target compounds for each analysis (e.g. base/neutral, base/neutral/acid, acid) shall be allowed to fall outside of the range of 70% to 130% (outlier) of the true value. None of the concentrations shall be allowed to fall below 50% or above 200% of the true value. If a positive sample analyte result is identified for any outlier, a second CCC shall be performed. If the second CCC determines the sample analyte result to no longer be an outlier, the sample shall be reanalyzed. However, if the second CCC also determines the analyte to be an outlier, a new calibration curve shall be determined and the sample shall be reanalyzed;

NOTE - At the laboratory's discretion, a calibration may be performed specifically for the compound in question, with the reporting of its data from this second calibration. It should be understood, that if the laboratory utilizes this approach (calibrating for the specific analyte) all method requirements as specified by 625 shall be achieved.

4.3.1.2 TICs are identified by comparison of the spectrum of the unknown to the mass-spectral reference library utilizing "Probability Based Matching" (as available from instrument manufacturers) as well as

interpretation by the analyst. The laboratory shall report the TIC with the best match factor (the match factor shall not be reported) except in the following circumstances:

- a) Due to the complex nature of GCMS interpretation and identification, when reviewing the list of possible matches for any particular TIC peak, the laboratory has the authority to assign the identification to a compound "hit" with a lower numeric match factor from the library search algorithm.
- b) The laboratory may determine that none of the returned compounds by the automated search algorithm is a good match for the unknown peak. In this case the compound is reported as a "Unknown."
- c) The laboratory may utilize manual spectral interpretation to identify the peak in question.
- d) All TICs detected at a concentration greater than or equal to 3.0 ppb shall be reported.

The library used during the analysis shall be NIST 2007 or most current version. Additional spectra libraries may be used to assist in the identification of unknown compounds. For TICs, the concentration is estimated by comparison of its total ion area response to the total ion area response of the nearest internal standard. For TICs, a response factor of "1" (one) shall be utilized for the purposes of calculating the TICs estimated concentration.

NOTE – It should be understood that when utilizing mass-spectrometer library searches to identify unknown chromatographic peaks (sometimes called "TICs") that the concentration is estimated assuming that the response of the TIC is the same as the internal standard. However, for example, when analyzing for traditional semi volatile compounds by USEPA method 625, the range of response factors is typically 0.1 to 2. Because the response factor is used as a reciprocal, and assuming that the response for the TIC falls within the range of the compounds for which the system is typically calibrated, the true concentration for this TIC would range up to 10 times greater to one half the reported TIC concentration.

4.3.1.3 Unknown Compounds - contaminants detected by GC/MS analysis but are not identified and quantified against a known mass spectrum or standard shall be evaluated as follows:

- a) The molecular weight shall be reported or, if no molecular ion is identifiable, a minimum value for the molecular weight (for example, if the highest mass ion for the TIC has a m/z of 143, then report $MW \geq 143$).
- b) The chemical class information shall be reported if this determination is possible.
- c) The laboratory shall report the presence of the common halogens chlorine and bromine utilizing their characteristic "M+2" patterns.
- d) The product material formulation(s) shall be reviewed for potential identification of the unknown contaminant(s) as an ingredient or byproduct;
- e) The manufacturer shall be notified and requested to provide supporting information that enables identification of the unknown contaminant(s);
- f) Structure activity relationships (SAR) shall be utilized when sufficient structural identification of the unknown contaminant(s) can be made; and
- g) Alternative methods of analysis that may identify the unknown contaminant(s) shall be considered, such as classifying the unknown into a chemical class.

Contaminants that are identified after performing one or more of the above steps shall be evaluated in accordance with 4.1.3.2 and 4.1.3.3. The product manufacturer, laboratory toxicologist and laboratory chemist shall assist the testing laboratory in the identification of a standard for the compound and an appropriate analytical method, if applicable, so that confirmatory identification and quantification can be

performed when needed. Standard validation is needed when the identified compound is not reported in the formulation review conducted in 4.2.

NOTE – Items “b” and “c” above may be automated utilizing software available from NIST with their mass-spectral database

4.3.1.4 Contaminants detected by GC/MS analysis for which no identification can be made after performing the above steps shall not be considered in the determination of product compliance to this Standard. When unknown contaminants are detected in the extractant water, the testing laboratory shall report the analytical results.

Table 1 – Extraction testing parameters

Parameter	Total Allowable Concentration (TAC) mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	USEPA method(s)
aluminum	0.5		0.1	200.7, 200.8
antimony		0.006	0.001	200.8, 200.9
arsenic		0.010	0.001	200.8, 200.9
barium		2	0.2	200.7, 200.8
beryllium		0.004	0.001	200.7, 200.8, 200.9
cadmium		0.005	0.001	200.8, 200.9
chromium		0.1	0.01	200.7, 200.8, 200.9
copper		1.3	0.1	200.7, 200.8
lead		0.010	0.001	200.8, 200.9
manganese	0.3		0.01	200.7, 200.8
mercury		0.002	0.001	200.8, 245.1
nickel	0.1		0.01	200.7, 200.8
selenium		0.05	0.005	200.8, 200.9
thallium		0.002	0.001	200.8, 200.9

– concluded –

Table 2 – Extraction testing parameters (Semi-Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
2,4,6-Trichlorophenol	88-06-2	0.005		0.001	525.2, 528, 625
2,4-Dichlorophenol	120-83-2	0.003		0.001	525.2, 528, 625
2,4-Dimethylphenol	105-67-9	0.1		0.01	525.2, 528, 625
2,6-Di-tert-butyl-4-methoxyphenol	489-01-0	0.003		0.003	525.2, 528, 625

Table 2 – Extraction testing parameters (Semi-Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
2-Methylnaphthalene	91-57-6	0.03		0.003	525.2, 528, 625
2-Nitrophenol	88-75-5	0.003*		0.001	525.2, 528, 625
2-Phenyl-2-propanol	617-94-7	0.05		0.005	525.2, 528, 625
3,3-Dichlorobenzidine	91-94-1	0.0008		0.001	525.2, 528, 625
3-and 4-Methylphenol, m&p-cresol	106-44-5 108-39-4	0.003*		0.001	525.2, 528, 625
4-Chloro-3-methylphenol	59-50-7	0.7		0.07	525.2, 528, 625
4-tert-Butylphenol or p-tert-Butylphenol	98-54-4	0.5		0.05	525.2, 528, 625
Acenaphthene	83-32-9	0.003*		0.004	525.2, 528, 625
Acenaphthylene	208-96-8	0.003		0.0004	525.2, 528, 625
Acetophenone	98-86-2	0.2		0.02	525.2, 528, 625
Anthracene	120-12-7	0.003*		0.0003	525.2, 528, 625
Benzo(a)pyrene	50-32-8		0.002	0.0002	525.2, 528, 625
Benzothiazole	95-16-9	0.003		0.003	525.2, 528, 625
Bis(2-ethylhexyl)adipate	103-23-1		0.4	0.04	525.2, 528, 625
Bis(2-ethylhexyl)phthalate	117-81-7		0.006	0.001	525.2, 528, 625
Butyl benzyl phthalate	85-68-7	1*		0.1	525.2, 528, 625
Chrysene	218-01-9	0.003*		0.003	525.2, 528, 625
Diethyl phthalate	84-66-2	6		0.6	525.2, 528, 625
Dimethyl phthalate	131-11-3	0.003		0.001	525.2, 528, 625
Di-n-butyl phthalate	84-74-2	0.7		0.07	525.2, 528, 625
Fluoranthene	206-44-0	0.003		0.0003	525.2, 528, 625
Isophorone	78-59-1	0.4		0.04	525.2, 528, 625
Naphthalene	91-20-3	0.4		0.04	525.2, 528, 625
N-Nitroso-di-n-butylamine	924-16-3	0.00006		0.0006	525.2, 528, 625
N-Nitroso-di-n-propylamine	621-64-7	0.00005		0.0005	525.2, 528, 625
N-Nitrosodiphenylamine	86-30-6	0.07		0.007	525.2, 528, 625
o-Cresol or 2-methylphenol	95-48-7	0.003*		0.001	525.2, 528, 625
Pentachlorophenol	87-86-5		0.001	0.0005	525.2, 528, 625

Table 2 – Extraction testing parameters (Semi-Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
Phenanthrene	85-01-8	0.003		0.0003	525.2, 528, 625
Phenol	108-95-2	2		0.2	525.2, 528, 625
Phenyl sulfone	127-63-9	0.003*		0.002	525.2, 528, 625
Pyrene	129-00-0	0.003		0.0006	525.2, 528, 625
¹ TAC values have been evaluated using qualitative or quantitative risk assessment methods. If contaminants extract above these levels, an evaluation in accordance of with Annex A of NSF/ANSI 61 may be used to determine a higher allowable level.					

– concluded –

Table 3 – Extraction testing parameters (Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
1,1,1,2-Tetrachloroethane	630-20-6	0.01		0.001	524.2, 524.3
1,1,1-Trichloroethane	71-55-6		0.2	0.02	524.2, 524.3
1,1,2,2-Tetrachloroethane	79-34-5	0.002		0.0005	524.2, 524.3
1,1,2-Trichloroethane	79-00-5		0.005	0.0005	524.2, 524.3
1,1-Dichloroethene	75-35-4		0.007*	0.0007	524.2, 524.3
1,1-Dichloropropene	563-58-6	0.003*		0.0005	524.2, 524.3
1,2,3-Trichlorobenzene	87-61-6	0.003		0.0005	524.2, 524.3
1,2,3-Trichloropropane	96-18-4	0.04		0.004	524.2, 524.3
1,2,4-Trichlorobenzene	120-82-1		0.07	0.007	524.2, 524.3
1,2-Dibromo-3-chloropropane	96-12-8		0.0002	0.0002	524.2, 524.3
1,2-Dibromoethane	106-93-4	0.0002		0.0002	524.2, 524.3

Table 3 – Extraction testing parameters (Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
1,2-Dichlorobenzene	95-50-1		0.6	0.06	524.2, 524.3
1,2-Dichloroethane	107-06-2		0.005	0.0005	524.2, 524.3
1,2-Dichloropropane	78-87-5		0.005	0.0005	524.2, 524.3
1,3,5-Trimethylbenzene	108-67-8	0.003*		0.0005	524.2, 524.3
1,3-Dichlorobenzene	541-73-1		0.6	0.06	524.2, 524.3
1,4-Dichlorobenzene	106-46-7		0.075	0.007	524.2, 524.3
2-Butanone	78-93-3	4		0.4	524.2, 524.3
2-Chlorotoluene	95-49-8	0.1*		0.01	524.2, 524.3
2-ethyl-1-hexanol	104-76-7	0.05		0.005	524.2, 524.3
4-Chlorotoluene	106-43-4	0.003		0.0005	524.2, 524.3
4-Isopropyltoluene	99-87-6	0.003		0.0005	524.2, 524.3
4-Methyl-2-pentanone	108-10-1	7		0.7	524.2, 524.3
Acetone	67-64-1	6		0.6	524.2, 524.3
Acetophenone	98-86-2	0.2		0.02	524.2, 524.3
Acrylonitrile	107-13-1	0.0006*		0.0006	524.2 SIM
Benzene	71-43-2		0.005	0.0005	524.2, 524.3
bis(2-Chloroethyl)ether or Di-(2-chloroethyl) ether	111-44-4	0.0003		0.0003	524.2, 524.3
Bromobenzene	108-86-1	0.003		0.0005	524.2, 524.3
Bromochloromethane	74-97-5		0.09	0.009	524.2, 524.3
Bromodichloromethane	75-27-4		See TTHMs	0.001	524.2, 524.3
Bromoform	75-25-2		See TTHMs	0.001	524.2, 524.3
Bromomethane	74-83-9	0.01		0.001	524.2, 524.3
Carbon disulfide	75-15-0	0.7		0.7	524.2, 524.3
Carbon tetrachloride	56-23-5		0.005	0.0005	524.2, 524.3
Chlorobenzene	108-90-7		0.1	0.01	524.2, 524.3
Chloroform	67-66-3		See TTHMs	0.001	524.2, 524.3
Chloromethane	74-87-3	0.03*		0.003	524.2, 524.3
cis-1,2-Dichloroethene	156-59-2		0.07	0.007	524.2, 524.3
Cyclohexanone	108-94-1	30		1.0	524.2, 524.3

Table 3 – Extraction testing parameters (Volatiles)

Analyte	CAS Number	TAC ¹ mg/L	Drinking water regulatory level (MCL/MAC) mg/L	Maximum Reporting Limit (RL) mg/L	Reference Method(s)
Dibromochloromethane	124-48-1		See TTHMs	0.001	524.2, 524.3
Dichlorodifluoromethane	75-71-8		0.003	0.0005	524.2, 524.3
Ethyl acrylate	140-88-5	0.01		0.001	524.2, 524.3
Ethylbenzene	100-41-4		0.7	0.07	524.2, 524.3
Methyl acrylate	96-33-3	0.003		0.001	524.2, 524.3
Methyl methacrylate	80-62-6	10		0.1	524.2, 524.3
Methyl tert-butyl ether	1634-04-4	0.002		0.0005	524.2, 524.3
Methylene chloride	75-09-2		0.005	0.0005	524.2, 524.3
n-Butyl acrylate	141-32-2	0.01		1	524.2, 524.3
n-Butylbenzene	104-51-8	0.003		0.0005	524.2, 524.3
sec-Butylbenzene	135-98-8	0.003		0.0005	524.2, 524.3
Styrene	100-42-5		0.1	0.01	524.2, 524.3
t-Butyl alcohol or t-butanol or tert-butanol	75-65-0	9		0.1	524.2, 524.3
Tetrachloroethene	127-18-4		0.005	0.0005	524.2, 524.3
Tetrahydrofuran	109-99-9	0.05		5	524.2, 524.3
Toluene	108-88-3		1	0.1	524.2, 524.3
Xylenes (Total) o-Xylene ² or 1,2-Xylene, m-xylene, p-xylene	95-47-6 106-42-3 108-38-3		10	0.1	524.2, 524.3
trans-1,2-Dichloroethene	156-60-5		0.1	0.01	524.2, 524.3
Dichloropropene (Total) Cis-1,3- Trans-1,3	542-75-6 10061-01-5 10061-02-6	0.004		0.0005	524.2, 524.3
Trichloroethene or Trichloroethylene	79-01-6		0.005	0.0005	524.2, 524.3
Trichlorofluoromethane	75-69-4	2		0.2	524.2, 524.3
Total Trihalomethanes (TTHMs)				0.001	524.2, 524.3
Bromodichloromethane			0.080		