PD IEC TR 62039:2021

BSI Standards Publication

Selection guidelines for polymeric materials for outdoor use under HV stress

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

National foreword

This Published Document is the UK implementation of IEC TR 62039:2021. It supersedes PD IEC/TR 62039:2007, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/112, Evaluation and qualification of electrical insulating materials and systems.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 580 99212 4

ICS 29.035.20; 29.080.10

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 November 2021.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

IEC TR 62039

Edition 2.0 2021-08

TECHNICAL REPORT

colour inside

Selection guidelines for polymeric materials for outdoor use under HV stress

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.035.20; 29.080.10

ISBN 978-2-8322-1012-8

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 8
4 Important material properties 9
4.1 General 9
4.2 Resistance to tracking and erosion 9
4.3 Arc resistance 9
4.4 Water diffusion test (resistance of material to chemical and physical degradation by water) 10
4.4.1 General 10
4.4.2 Test specimens 10
4.4.3 Test procedure 10
4.4.4 Minimum requirements 12
4.5 Tear strength 13
4.6 Volume resistivity 13
4.7 Breakdown field strength 13
4.8 Stress corrosion test (resistance to chemical attack) 13
4.8.1 General 13
4.8.2 Test specimens 14
4.8.3 Procedure 14
4.8.4 Acceptance criteria 14
4.9 Resistance to weathering and UV procedure 14
4.10 Resistance to flammability procedure 15
4.11 Glass transition temperature 15
4.12 Hydrophobicity 17
4.12.1 General 17
4.12.2 Transfer of hydrophobicity 17
4.12.3 Retention and recovery of hydrophobicity 21
5 Important properties and minimum requirements of polymeric insulation materials for outdoor use under HV stress 22
Annex A (informative) Additional measuring methods 25
A.1 General 25
A.2 Resistance to corona and ozone 25
A.3 Resistance to acid attack generated by partial discharge under wet, contaminated, and energization condition 25
Annex B (informative) Water immersion test 26
B.1 General 26
B.2 Test procedure 26
Bibliography 28

Figure 1 – Example of boiling container for water diffusion test 11
Figure 2 – Electrodes for voltage test 12
Figure 3 – Voltage test circuit 12
Figure 4 – Example of permanent load application for stress corrosion test 14

AVA Documents
Document Sharing Hub
Full document details: PD IEC TR 62039:2021

Figure 5 – Definition of glass transition temperature T_g 16
Figure 6 – Specimen with adhesive foil 18
Figure 7 – Specimen with pollution layer 19
Figure 8 – Area for the drop application for measurement according to IEC TS 62073 (example for Method A) 21
Figure B.1 – Example of water uptake of two different kinds of materials (MFRP and UFRP) 27

Table 1 – Important properties and minimum requirements of polymeric insulation materials for outdoor use under HV stress 22
Table B.1 – Example of dielectric properties in dry conditions and after water immersion for 100 days 27

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SELECTION GUIDELINES FOR POLYMERIC MATERIALS FOR OUTDOOR USE UNDER HV STRESS

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 62039 has been prepared by IEC technical committee 112: Evaluation and qualification of electrical insulating materials and systems. It is a Technical Report.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) addition of hydrophobicity definitions and hydrophobicity transfer test;
b) addition of stress corrosion test.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

The text of this Technical Report is based on the following documents:

Draft	Report on voting
112/526/DTR	112/535/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

INTRODUCTION

There is a need within utilities and industry for material standards that define the physical properties of the polymers applied for outdoor insulation. This requirement was identified during discussions in IEC TC 36 and IEC TC 112. As a consequence, in 2001, CIGRE formed the working group D1.14 and later on working groups D1.27, C4.303 and D1.58 with the specific task of defining the physical parameters which are important for the polymeric materials applied in outdoor insulation and developing the relevant test methods, where necessary. As a first step, a state-of-the-art report was issued by CIGRE in Technical Brochure 255. Thirteen properties were identified; standardized test methods and minimum requirements were available for eleven of them. For the remaining property of hydrophobicity retention and recovery, test methods and minimum requirements still need to be defined. This will be the future task of SC D1. This document presents, as a conclusion of the CIGRE report, the important material properties for polymeric materials used in outdoor insulation, where they are applicable, and lists standardized test methods including minimum requirements. If no standardized tests are available, then test methods reported in literature (references in the bibliography) are summarized.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

SELECTION GUIDELINES FOR POLYMERIC MATERIALS FOR OUTDOOR USE UNDER HV STRESS

1 Scope

This document presents the important material properties of polymeric materials used in outdoor insulation and, where applicable, lists standardized test methods including minimum requirements. If no standardized tests are available, the test methods reported in literature are summarized.

This document is valid for insulating materials having polymeric insulation, which are used in outdoor high voltage electrical applications with a system voltage greater than 1 000 V AC and 1 500 V DC (several tests are only defined for alternating current, which are not applicable for direct current). Such applications are relevant where the housing is an integral part of the device, for example in surge arresters and cable terminations. The scope of this document is limited to the insulation materials only and is not generally intended for coating materials (coating materials are, for example, thin layers applied on toughened glass and ceramic). Some tests mentioned in this document are applicable for coating and are under consideration by CIGRE. The performance of insulators in service depends on several factors such as the type of material, the design and environmental conditions. Consequently, the choice of materials that fulfil the requirements listed in Table 1 is a necessary condition but does not guarantee satisfactory performance when used in outdoor insulation.

In Annex A and Annex B different test methods for testing additional properties are given, which are not standardized.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60243-1, *Electric strength of insulating materials – Test methods – Part 1: Tests at power frequencies*

IEC 60243-2, *Electric strength of insulating materials – Test methods – Part 2: Additional requirements for tests using direct voltage*

IEC 60455-2, *Resin based reactive compounds used for electrical insulation – Part 2: Methods of test*

IEC 60587, *Electrical insulating materials used under severe ambient conditions – Test methods for evaluating resistance to tracking and erosion*

IEC 60695-11-10, *Fire hazard testing – Part 11-10: Test flames – 50 W horizontal and vertical flame test methods*

IEC 61621, *Dry, solid insulating materials – Resistance test to high-voltage, low-current arc discharges*

IEC TS 62073, *Guidance on the measurement of hydrophobicity of insulator surfaces*

AVA Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

IEC 62631-3-1, *Dielectric and resistive properties of solid insulating materials – Part 3-1: Determination of resistive properties (DC methods) – Volume resistance and volume resistivity – General method*

ISO 34-1, *Rubber, vulcanized or thermoplastic – Determination of tear strength – Part 1: Trouser, angle and crescent test pieces*

ISO 483, *Plastics – Small enclosures for conditioning and testing using aqueous solutions to maintain the humidity at a constant value*

ISO 4892-2, *Plastics – Methods of exposure to laboratory light sources – Part 2: Xenon-arc lamps*

ISO 6721-11, *Plastics – Determination of dynamic mechanical properties – Part 11: Glass transition temperature*

ISO 11357-2, *Plastics – Differential scanning calorimetry (DSC) – Part 2: Determination of glass transition temperature and step height*

ISO 11359-2, *Plastics – Thermomechanical analysis (TMA) – Part 2: Determination of coefficient of linear thermal expansion and glass transition temperature*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1
hydrophobicity
surface of a solid insulating material characterized by its capacity to repel water or aqueous electrolyte solutions

Note 1 to entry: Hydrophobicity of a polymeric insulating material is, in general, a volume property by means of the chemical composition of a material at its surface.

Note 2 to entry: Nonetheless, hydrophobicity is strongly affected by surface effects such as:

- surface structure (i.e. roughness);
- chemical interaction between water and the solid surface (adsorption, absorption, swelling of the solid material in contact with water);
- an accumulated pollution layer.

Note 3 to entry: Furthermore, the conditions during an evaluation of hydrophobicity (climatic (temperature, pressure, humidity), and the method for cleaning or electrostatic charges can affect the measured degree of hydrophobicity.

3.2
hydrophobicity class
HC
specific level of the scale used in the spray method (Method C)

Note 1 to entry: Seven classes, HC1 to HC7, have been defined. HC1 corresponds to the most hydrophobic surface and HC7 to the most hydrophilic surface.

[SOURCE: IEC TS 62073:2016, 2.6]

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021

3.3
hydrophobicity transfer
phenomenon of a transfer of hydrophobicity from the bulk of the housing material onto the pollution layer on its surface

[SOURCE: CIGRE TB 442:2010, Clause 4]

3.4
hydrophobicity transfer material
HTM
polymeric material which exhibits hydrophobicity and the capability to transfer hydrophobicity onto the layer of pollution, which is a combined dynamic behaviour of retention and transfer of hydrophobicity specific to different insulator materials

[SOURCE: IEC TS 60815-4:2016, 3.1.4. modified – The text after "pollution" has been added and the Note to entry has been deleted.]

4 Important material properties

4.1 General

This document defines the important properties that need to be tested on the material itself in order to ensure the functioning of the material under normal operating service conditions. Physical, mechanical, electrical and chemical properties of the materials have been considered.

According to their function in the insulation, three categories of insulating materials are considered:

- housing materials (in general a silicone rubber, EPDM, EVA, etc.);
- core materials (FRP, etc.);
- structural materials (epoxy, etc.).

The minimum requirements are, as far as possible, based on the performance of polymeric insulators in service.

4.2 Resistance to tracking and erosion

The inclined-plane-test according to IEC 60587 is easily applicable, shows a good reproducibility and allows a good differentiation between insulating materials with respect to the resistance of electrical insulating materials against erosion and tracking. The thickness of the test specimens should be 6 mm ± 0,5 mm.

The minimum requirements are given in Table 1.

NOTE IEC 60587 covers only alternating current. A tracking and erosion test for direct current is still under consideration by CIGRE (see also CIGRE TB 611).

4.3 Arc resistance

The test for the arc resistance capability of housing and structural materials is carried out according to IEC 61621.

The minimum requirements are given in Table 1.

NOTE IEC 61621 covers only alternating current. An arc resistance test for direct current is still under consideration by CIGRE.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62039:2021