PD IEC TR 62500:2024

BSI Standards Publication

Process management for avionics — Highly severe stress tests for operating margins identification and robustness improvement of avionics equipment — Application guidelines

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

National foreword

This Published Document is the UK implementation of IEC TR 62500:2024. It supersedes DD IEC/TS 62500:2008, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GEL/107, Process management for avionics.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 12810 9

ICS 03.100.50; 31.020; 49.060

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2024.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

IEC TR 62500

Edition 1.0 2024-05

TECHNICAL REPORT

colour inside

Process management for avionics – Highly severe stress tests for operating margins identification and robustness improvement of avionics equipment – Application guidelines

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-8322-8566-4

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 9
4 Highly severe stress tests for margins research and robustness improvement – Approach 10
4.1 General 10
4.2 Objectives 10
4.3 Considerations 11
4.4 General principles 11
4.5 Example of the limitations of highly severe stress tests 13
5 Industrial domains covered by highly severe stress tests 14
6 Highly severe stress tests in the equipment lifecycle and associated stages 14
6.1 General 14
6.2 Design and development 14
6.3 Qualification 15
6.4 Production 15
6.5 Operation and maintenance 15
7 Planning and management of highly severe stress tests 15
7.1 General 15
7.2 Planning of highly severe stress tests and budget consideration 16
7.3 Management of highly severe stress tests 16
8 Typical methodology for implementing highly severe stress tests 16
8.1 Basis for an effective approach 16
8.2 Identification of equipment potential built-in deficiencies/weak points 17
8.2.1 General 17
8.2.2 Sources of information and data for identification of potential built-in deficiencies or weak points 17
8.2.3 Specific consideration of parameters related to intrinsic limits 18
8.3 Selection of applicable stresses 18
8.3.1 General 18
8.3.2 Stress types 19
8.4 Test plan and preparation of the tests implementation 19
8.4.1 General 19
8.4.2 Test plan contents 19
8.4.3 Specific considerations 22
8.5 Tests implementation 23
8.5.1 General 23
8.5.2 Checks before tests 23
8.5.3 Stresses application 23
8.5.4 Root cause analysis, corrective actions 24
8.5.5 Test report 25
9 Taking advantage and using experience gained with highly severe tests 26

AVA Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

9.1 General ... 26
9.2 Creating or enhancing a database ... 26
9.3 Enhancing procedures and quality system ... 27
9.4 Contribution to environmental stress screening (ESS) definition ... 27
9.4.1 Reminder of ESS purpose ... 27
9.4.2 Contribution of highly severe stress tests ... 27
9.5 Checking the effectiveness of the highly severe stress tests with regard to the experience and the equipment maturity by correlation with feedbacks ... 27
9.6 Moving OEM's culture forward ... 28
10 Responsibilities and relationships ... 28
10.1 Customer/OEM relationship ... 28
10.1.1 Responsibilities ... 28
10.1.2 Contractual requirements ... 29
10.2 OEM and external test laboratories relationship ... 29
11 Costs and savings ... 30
11.1 General ... 30
11.2 "Non-maturity" costs ... 30
11.2.1 Cost due to delayed time to market (TTM) or poor entry into service (EIS) ... 30
11.2.2 Cost of an in-service built-in deficiencies processing ... 32
11.2.3 Cost of a in-service recovery operation and products retrofit ... 32
11.2.4 Impact on brand image ... 32
11.3 Expenses generated by the highly severe stress tests ... 33
11.3.1 Engineering for highly severe stress tests preparation ... 33
11.3.2 Highly severe stress tests implementation ... 33
11.3.3 Weakened, damaged or destroyed equipment ... 33
Annex A (informative) Highly severe tests approach ... 34
A.1 Approach for highly severe stress tests ... 34
A.2 Typical flowchart related to implementation of highly severe stress tests ... 34
Annex B (informative) Examples of potential effectiveness of stresses with regard to the nature of the equipment weak points ... 36
Bibliography ... 37

Figure 1 – Typical exploration of margins using a highly severe stress tests approach ... 13
Figure 2 – Typical marketing stages of a product with time ... 31
Figure A.1 – Typical flowchart related to planning of the highly severe tests ... 34
Figure A.2 – Typical flowchart related to highly severe stress tests implementation ... 35

Table B.1 – Examples of potential effectiveness of stresses with regard to the nature of the equipment weak points ... 36

Documents
Document Sharing Hub
Full document details: PD IEC TR 62500:2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROCESS MANAGEMENT FOR AVIONICS – HIGHLY SEVERE STRESS TESTS FOR OPERATING MARGINS IDENTIFICATION AND ROBUSTNESS IMPROVEMENT OF AVIONICS EQUIPMENT – APPLICATION GUIDELINES

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 62500 has been prepared by IEC technical committee 107: Process management for avionics. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
107/411/DTR	107/415/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

INTRODUCTION

In an increasingly harsh economic context (higher performance requirements, shorter development cycles, reduced cost of ownership, etc.), consideration is given to rapid equipment maturity, preferably from its entry into service (EIS).

It is with a view to remedying shortcomings that "highly severe stress" tests for margins research and robustness improvement are considered in equipment design and development methods. The main underlying principle behind this type of test strategy is as follows: rather than reasoning in terms of conformity with a specification and applying tests in line with the specification requirements, it is on the contrary attempted to push the equipment to its operating limits by applying environmental stresses or stimuli, whose levels are higher than the specification requirements.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

PROCESS MANAGEMENT FOR AVIONICS – HIGHLY SEVERE STRESS TESTS FOR OPERATING MARGINS IDENTIFICATION AND ROBUSTNESS IMPROVEMENT OF AVIONICS EQUIPMENT – APPLICATION GUIDELINES

1 Scope

This technical report considers the targets assigned to highly severe stress tests for operating margins research and robustness improvement of avionics equipment, their basic principles, their scope of application and their implementation process. It is primarily intended for avionics programme managers, electronic equipment project managers, designers, test managers, and dependability team.

This document provides guidance which can apply to all avionics programmes and is of primary interest to the original equipment manufacturers (OEMs) in charge of designing, developing and producing equipment built for these programmes, for obtaining early equipment maturity.

NOTE 1 Highly severe stress tests approach is often an industrial will in a global lifecycle cost effective approach (see the Introduction) and it is not required at certification level. Moreover, customers can potentially define, in contract clauses, in-service availability requirements, for example, from the entry into service (EIS) or in operation.

This highly severe stress tests approach is part of the avionics equipment design and development stage, and it can address stresses in mechanical, climatic, electrical, etc., domains.

NOTE 2 The principles and objectives described in this document can apply to all types of equipment used in systems developed in avionics programmes, whatever their nature (electronic, electromechanical, mechanical, electrohydraulic, electro-pneumatic, etc.) and whatever their size, from "low-level" subassemblies (circuit card assemblies (CCAs), mechanical assemblies, connectors, etc.) up to system level groups of equipment.

This document can be used in conjunction with IEC 62429, IEC 62506, or both, with regard to dependability aspects related to equipment consisting of hardware with embedded software.

NOTE 3 This document can provide an aid in an equipment definition justification process (see CEN-CENELEC prEN 9215) which can address:

- the development of a definition justification dossier (DJD) by bringing data related to equipment margins and to decisions; or
- the justification of potential future changes made at equipment definition, for example when processing cases of electronic component obsolescence.

For the purpose of this document, if the term "deficiency" is used alone afterwards, it is stated as "built-in deficiency" or "weak point" and encompasses the concept of "deficiency and associated potential malfunction or failure" (see 3.1.1).

Although developed for the avionics industry, this document can be used by other industrial sectors at their discretion.

2 Normative references

There are no normative references in this document.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1.1 built-in deficiency

fault, flaw, imperfection, shortcoming or abnormality, often called weak point, in the design or in the manufacturing processes of an item, which can potentially lead to a malfunction or a failure and cause the item not to operate or function correctly

Note 1 to entry: Deviation from state-of-the-art design rules or inaccurate manufacturing process control can constitute risks and be, for example, at the origin of equipment built-in deficiencies. These built-in deficiencies are usually considered as weak points.

Note 2 to entry: The correction of a built-in deficiency goes in the direction of improving operating margin and robustness of an item, and so in the direction of improving its early maturity.

Note 3 to entry: A built-in deficiency is usually latent (present or potential but not obvious or not explicit or dormant) and manifests itself in operating time or certain conditions.

3.1.2
destruct limit

point from which an item breaks and suffers permanent and irreversible damage

Note 1 to entry: The destruct limit is above (beyond) the operating limit. The stress level leading to the destruct and the permanent and irreversible damage is in excess of the one characterizing the operating limit of an item. The item no longer functions, even the stress level is reduced and returned to below the one characterizing the operating limit.

3.1.3
highly severe stress test

test during which the equipment or some of its parts are submitted to environmental or operating condition or stress that is increased progressively to values far in excess of the specified values, up to the operating limit of the equipment

3.1.4
intermitent

occasional or irregular

Note 1 to entry: An intermittent malfunction or failure occurs occasionally or at irregular intervals.

Note 2 to entry: Intermittent malfunction or failure can occur at stress level in excess of the specified operating limit of an item where the item functions with nominal load. The purpose of highly severe stress tests approach is to precipitate the potential built-in deficiencies (at design or manufacturing processes level for example) into intermittent or permanent malfunctions or failures to investigate them and seek corrective actions.

Note 3 to entry: Intermittent malfunction or failure origin can sometimes be detected by applying an additional specific low stress level (vibrations for example) during a function test.

Documents
Document Sharing Hub

Full document details: PD IEC TR 62500:2024

3.1.5
intrinsic limit
point below which an item, a material or a technology keeps its intrinsic properties or characteristics, with respect to given condition(s) (for example, temperature, vibration, electrical voltage, etc.)

Note 1 to entry: For example, melting temperature of a plastic, maximum junction temperature of a semiconductor, yield strength of an alloy, etc., are intrinsic properties or characteristics of these materials or technologies.

Note 2 to entry: This limit, whether or not destructive, is an absolute barrier.

3.1.6
maturity
state of an item whose functional and operational performance can be considered stabilized with respect to the specification

Note 1 to entry: Maturity is usually the result of a gradual process of eliminating built-in deficiencies still present at the item level and its associated processes (manufacturing processes for example).

3.1.7
operating limit
point at the boundary of the operation area of an item where it still operates or functions correctly and beyond which it no longer operates or functions correctly

Note 1 to entry: The operating limit defines the maximum range of correct operation area of an item, and it is usually characterized by stress level above which the item no longer operates or functions correctly. Usually, for determining this stress level, the stress level at which the item no longer operates or functions correctly is reduced to verify if the function of the item resumes; if the functionality resumes at the reduced stress level, then this stress level characterizes the operating limit.

Note 2 to entry: The operating limit can correspond to the intrinsic limit of a technology. In this case, this is the maximum range of operation which can be reached by the equipment.

3.1.8
operating margin
difference between the operating limit and the nominal operating level under specified stress levels

3.1.9
robustness
property of an item having reduced sensitivity of its performance under, for example, the environmental conditions, to components variations, or to drifts in its manufacturing processes

Note 1 to entry: Robustness is usually the result of actions taken to obtain sufficient operating margins while at the same time reducing all forms of variability.

3.2 Abbreviated terms

CCA	circuit card assembly
CDR	critical design review
EIS	entry into service
EMC	electromagnetic compatibility
ESD	electrostatic discharge
ESS	environmental stress screening
LCD	liquid crystal display
MTBF	mean operating time between failures
OEM	original equipment manufacturer
PCB	printed circuit board
PDR	preliminary design review

Documents
Document Sharing Hub
Full document details: PD IEC TR 62500:2024

RTV rapid temperature variation

TTM time to market

4 Highly severe stress tests for margins research and robustness improvement – Approach

4.1 General

With regard to the initiative for obtaining early equipment maturity, the approach based on highly severe stress tests for operating margins research and robustness improvement consists in submitting an equipment or some of its component parts to environmental or operating stresses, or both, which are gradually raised to values in excess of the specified values until the equipment operating or destruct limits are reached.

Instead of reasoning in terms of conformity with the specification (which is representative of the equipment real lifecycle or mission profile), the highly severe stress tests approach aims, indeed, on the contrary with a view to obtaining robust and mature equipment, to push the equipment to its operating limits or potentially to its destruct limits in order to:

- detect potential intermittent or permanent malfunctions or failures that were not foreseen before the tests;
- reveal, identify and then, depending on margins targets if defined, correct built-in deficiencies which can lead to intermittent or permanent malfunctions or failures; and
- explore available margins and improve, if needed, these margins through appropriate actions, for example, on the equipment design itself or the manufacturing processes.

Equipment operating margin targets are often defined to orientate the highly severe stress approach.

NOTE For example, if not specified by the customer, an operating margin target of 5 °C can be defined with regard to the specified low operating temperature, $T_{\text{op-low}}$, of an equipment; so, in this case, the highest level of stress is limited to $T_{\text{op-low}}$-5 °C. The equipment operating margin target can also be defined according to the industrial usage or application domain or by experience feedback.

Usually, the highly severe stress tests activity is part of a global lifecycle cost effective approach and is formalized with its general objectives and principles in quality system procedures or other specific summary documents, allowing effective coordination and OEM executive officers' support.

Annex A, Figure A.1, provides a typical flowchart related to the highly severe stress tests approach.

4.2 Objectives

The main objectives of the approach include:

a) achieving, in a relatively short time, an early equipment maturity by improving its robustness toward the specification;

b) taking, from the first prototypes, full advantage of technologies and manufacturing processes, by:
   - eliminating, for example, design and manufacturing processes built-in deficiencies;
   - researching operational limits or destruct limits in operating and environmental conditions more severe than the specified ones;
   - considering operational margins allowing to:
     - satisfy, for example, potential technologies or manufacturing processes variations (which can lead later to potential malfunctions, failures or specification non-conformities);

AVA Documents Document Sharing Hub