PD IEC/TR 62778:2014

Incorporating corrigendum July 2014

BSI Standards Publication

Application of IEC 62471 for the assessment of blue light hazard to light sources and luminaires

bsi.

...making excellence a habit.™

Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

National foreword

This Published Document is the UK implementation of IEC/TR 62778:2014, incorporating corrigendum July 2014. It supersedes PD IEC/TR 62778:2012, which is withdrawn.

The UK participation in its preparation was entrusted by Technical Committee CPL/34, Lamps and Related Equipment, to Subcommittee CPL/34/1, Electric lamps.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 87760 5
ICS 29.140.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2014.

Amendments/corrigenda issued since publication

Date	Text affected
31 August 2014	Implementation of IEC corrigendum July 2014: Formulas D.1 and D.2 amended

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

IEC TR 62778

Edition 2.0 2014-06

TECHNICAL REPORT

colour inside

Application of IEC 62471 for the assessment of blue light hazard to light sources and luminaires

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE W

ICS 29.140

ISBN 978-2-8322-1615-6

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

CONTENTS

FOREWORD 4
1 Scope 6
2 Normative references 6
3 Terms and definitions 6
4 General 11
5 Spectrum, colour temperature, and blue light hazard 12
5.1 Calculation of blue light hazard quantities and photometric quantities from emission spectra 12
5.2 Luminance and illuminance regimes that give rise to t_{max} values below 100 s 15
6 LED packages, LED modules, lamps and luminaires 17
7 Measurement information flow 18
7.1 Basic flow 18
7.2 Conditions for the radiance measurement 20
7.3 Special cases (I): Replacement by a lamp or LED module of another type 22
7.4 Special cases (II): Arrays and clusters of primary light sources 22
8 Risk group classification 22
Annex A (informative) Geometrical relations between radiance, irradiance and radiant intensity 23
Annex B (informative) Distance dependence of t_{max} for a certain light source 25
Annex C (informative) Summary of recommendations to assist the consistent application of IEC 62471 for the assessment of blue light hazard to light sources and luminaires 27
C.1 General 27
C.2 Situation of RG0 or RG1 classification not requiring radiance or irradiance measurement 27
C.2.1 Boundary conditions 27
C.2.2 True luminance values giving risk group not greater than RG1 27
C.2.3 Illuminance values giving risk group not greater than RG1 28
C.3 Situation for the classification of light sources larger than 2,2 mm and luminaires using these light sources 29
C.4 Situation for the classification of light sources smaller than 2,2 mm and luminaires using these light sources 30
C.5 Situation for the classification of light sources that pose practical difficulties in measurements at 200 mm 30
Annex D (informative) Detailed assessment of arrays and clusters of primary light sources, comprised of LED packages 31
D.1 General 31
D.2 Approach 31
D.2.1 Step by step assessment 31
D.2.2 Type of arrays and additional steps 32
D.2.3 Complete flowchart 34
D.3 Derivation of the formula for average radiance of the full array 35
Bibliography 37

Figure 1 – Blue light hazard efficacy of luminous radiation, $K_{B,v}$, for a range of light sources from different technologies, and for a few typical daylight spectra 13

AVA Documents
Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

Figure 2 – Comparison between the curves involved in calculating $K_{B,V}$ (the photopic eye sensitivity curve and the blue light spectral weighting function) and the CIE 1931 *Y* and *Z* curves involved in calculating the CIE 1931 *x*, *y* colour coordinates 14

Figure 3 – Correlation plot between the quantity (1 – *x* – *y*)/*y*, calculated from the CIE 1931 *x*, *y* colour coordinates, and the value of $K_{B,V}$, for all the spectra analysed to generate Figure 1 15

Figure 4 – Estimate of the luminance level where L_B = 10 000 W/(m^2·sr), border between RG1 (t_{max} > 100 s) and RG2 (t_{max} < 100 s) in the large source regime, as a function of CCT 16

Figure 5 – Estimate of the illuminance level where E_B = 1 W/m^2, border between RG1 (t_{max} > 100 s) and RG2 (t_{max} < 100 s) in the small source regime, as a function of CCT 16

Figure 6 – Relation of illuminance *E*, distance *d* and intensity *I* 20

Figure 7 – Flow chart from the primary light source (in blue) to the luminaire based on this light source (in amber) 21

Figure A.1 – Schematic image of the situation considered in Annex A 23

Figure B.1 – General appearance of t_{max} as a function of viewing distance *d*, for any light source with homogeneous luminance *L* and diameter *D* 26

Figure C.1 – Luminance values from Table C.1 in relation to the RG1/RG2 border as function of correlated colour temperature 28

Figure C.2 – Illuminance values from Table C.2 in relation to the RG1/RG2 border as function of correlated colour temperature 29

Figure D.1 – Examples of secondary lenses with identical light distribution and alignment 32

Figure D.2 – Examples of LED arrays with bare LED packages 33

Figure D.3 – Evaluation whether one or more LED elements fall in 11 mrad field of view at distance d_1 33

Figure D.4 – Complete flowchart of the detailed assessment of arrays and clusters of primary light sources 35

Table 1 – Correlation between exposure time and risk group 10

Table C.1 – Luminance values giving risk group not greater than RG1 28

Table C.2 – Illuminance values giving risk group not greater than RG1 29

Table D.1 – Applicability of steps 1 to 6 31

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

INTERNATIONAL ELECTROTECHNICAL COMMISSION

APPLICATION OF IEC 62471 FOR THE ASSESSMENT OF BLUE LIGHT HAZARD TO LIGHT SOURCES AND LUMINAIRES

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 62778, which is a technical report, has been prepared by subcommittee 34A: Lamps, of IEC technical committee 34: Lamps and related equipment.

This second edition cancels and replaces the first edition published in 2012. This edition constitutes a technical revision.

This edition includes the following significant technical change with respect to the previous edition: inclusion of the photobiological assessment of LED arrays (Annex D).

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
34A/1737/DTR	34A/1758/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62778:2014

APPLICATION OF IEC 62471 FOR THE ASSESSMENT OF BLUE LIGHT HAZARD TO LIGHT SOURCES AND LUMINAIRES

1 Scope

This Technical Report brings clarification and guidance concerning the assessment of blue light hazard of all lighting products which have the main emission in the visible spectrum (380 nm to 780 nm). By optical and spectral calculations, it is shown what the photobiological safety measurements as described in IEC 62471 tell us about the product and, if this product is intended to be a component in a higher level lighting product, how this information can be transferred from the component product (e.g. the LED package, the LED module, or the lamp) to the higher level lighting product (e.g. the luminaire).

A summary of recommendations to assist the consistent application of IEC 62471 to light sources and luminaires for the assessment of blue light hazard is given in Annex C.

NOTE It is expected that HID and LED product safety standards will make reference to this Technical Report.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), *International Electrotechnical Vocabulary* (available at <http://www.electropedia.org>).

IEC 62471:2006, *Photobiological safety of lamps and lamp systems*

CIE S 017/E:2011, *ILV: International Lighting Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62471:2006, CIE S 017/E:2011 and IEC 60050-845 as well as the following apply.

3.1
blue light hazard efficacy of luminous radiation
$K_{B,v}$
quotient of blue light hazard quantity to the corresponding photometric quantity

Note 1 to entry: Blue light hazard efficacy of luminous radiation is expressed in W/lm.

Note 2 to entry: The quantity $\Phi_\lambda(\lambda)$ in the formula below can be replaced by $L_\lambda(\lambda)$ or $E_\lambda(\lambda)$.

$$K_{B,v} = \frac{\int \Phi_\lambda(\lambda) \cdot B(\lambda) \cdot d\lambda}{K_m \cdot \int \Phi_\lambda(\lambda) \cdot V(\lambda) \cdot d\lambda}$$

where K_m = 683 lm/W.

Note 3 to entry: $K_{B,v} = L_B/L = E_B/E$.

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

3.2
blue light hazard efficiency of radiation
η_B
ratio of blue light hazard quantity to the corresponding radiometric quantity

Note 1 to entry: The quantity $\Phi_\lambda(\lambda)$ in the formula below can be replaced by $L_\lambda(\lambda)$ or $E_\lambda(\lambda)$.

$$\eta_B = \frac{\int \Phi_\lambda(\lambda) \cdot B(\lambda) \cdot \mathrm{d}\lambda}{\int \Phi_\lambda(\lambda) \cdot \mathrm{d}\lambda}$$

3.3
correlated colour temperature
CCT
temperature of the Planckian radiator having the chromaticity nearest the chromaticity associated with the given spectral distribution on a diagram where the (CIE 1931 standard observer based) *u*', 2/3 *v*' coordinates of the Planckian locus and the test stimulus are depicted

Note 1 to entry: Correlated colour temperature is expressed in kelvin (K).

Note 2 to entry: The concept of correlated colour temperature should not be used if the chromaticity of the test source differs more than $\Delta C = [(u'_t - u'_p)^2 + \frac{4}{9}(v'_t - v'_p)^2]^{1/2} = 5 \times 10^{-2}$ from the Planckian radiator, where

u'_t, v'_t refer to the test source, u'_p, v'_p to the Planckian radiator.

Note 3 to entry: Correlated colour temperature can be calculated by a simple minimum search computer program that searches for that Planckian temperature that provides the smallest chromaticity difference between the test chromaticity and the Planckian locus, or e.g. by a method recommended by Robertson, A. R. "Computation of correlated color temperature and distribution temperature", J. Opt. Soc. Am. 58, 1528-1535, 1968. (Note that the values in some of the tables in this reference are not up-to-date).

[SOURCE: CIE S 017/E:2011, 17-258, modified — T_{cp} is not referenced.]

3.4
illuminance <at a point of a surface>
E
quotient of the luminous flux dΦ incident on an element of the surface containing the point, by the area d*A* of that element

Note 1 to entry: Illuminance is expressed in lm/m^2 or lx.

[SOURCE: IEC 60050-845:1987, 845.01.38, modified — The second half of the definition is omitted.]

3.5
blue light weighted irradiance
E_B
irradiance spectrally weighted with the blue light spectral weighting function as defined in IEC 62471

Note 1 to entry: Blue light weighted irradiance is expressed in W/m^2.

3.6
threshold illuminance
E_{thr}
threshold illuminance value, below which the light source can never give rise to an exposure time t_{max} < 100 s, regardless of the light source's L_B value

Note 1 to entry: The threshold illuminance can be calculated by taking the E_B value for t_{max} = 100 s, which is E_B = 1 W/m^2, and dividing E_B by the $K_{B,v}$ value corresponding to the spectrum of the light source.

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

Note 2 to entry: Threshold illuminance is expressed in lm/m^2 or lx.

3.7
etendue
geometrical property of a collection of light rays in an optical system, given by the integral over all positions in a plane that these light rays pass through and over all directions into which they travel

Note 1 to entry: It takes the form of a product of area and solid angle. It can be seen as a volume in phase space. Basic physical conservation laws, related to the 'second law of thermodynamics', dictate that optical components that change only the direction of light (lenses, reflectors, all beam shaping optics) can never decrease the etendue for a given packet of flux.

Note 2 to entry: Etendue is expressed in m^{2}sr.

3.8
irradiance <at a point of a surface>
$\boldsymbol{E_e}$
quotient of the radiant flux dΦ_e incident on an element of the surface containing the point, by the area dA of that element

Note 1 to entry: Irradiance (at a point of a surface) is expressed in W/m^2.

Note 2 to entry: The spectral power distribution of the irradiance, as a function of wavelength, is denoted by $E_\lambda(\lambda)$.

Note 3 to entry: For the purposes of this Technical Report, it is important to mention that when $E_\lambda(\lambda)$ is known, it can be converted to illuminance (E) when weighted with the CIE 1924 photopic eye sensitivity spectrum $V(\lambda)$, and to blue light weighted irradiance (E_B) when weighted with the blue light spectral weighting function as defined in IEC 62471.

[SOURCE: IEC 60050-845:1987, 845.01.37, modified — Notes 2 and 3 to entry are introduced.]

3.9
luminance <in a given direction, at a given point of a real or imaginary surface>
$\boldsymbol{L}$
quantity defined by the formula

$$L = \frac{\mathrm{d}\,\Phi}{\mathrm{d}A \cdot \cos\theta \cdot \mathrm{d}\Omega}$$

where dΦ is the luminous flux transmitted by an elementary beam passing through the given point and propagating in the solid angle dΩ containing the given direction; dA is the area of a section of that beam containing the given point; θ is the angle between the normal to that section and the direction of the beam

Note 1 to entry: Luminance (in a given direction, at a given point of a real or imaginary surface) is expressed in cd/m^2.

[SOURCE: IEC 60050-845:1987, 845.01.35, modified — "L" instead of "L_V" is used. The note is deleted.]

3.10
blue light weighted radiance
$\boldsymbol{L_B}$
radiance spectrally weighted with the blue light spectral weighting function as defined in IEC 62471

Note 1 to entry: Blue light weighted radiance is expressed in W/(m^2·sr).

3.11
light source
any product that produces light

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

EXAMPLE LED package, LED module, lamp, luminaire

3.12
luminaire
apparatus which distributes, filters or transforms the light transmitted from one or more lamps and which includes, except the lamps themselves, all the parts necessary for fixing and protecting the lamps and, where necessary, circuit auxiliaries together with the means for connecting them to the electric supply

[SOURCE: IEC 60050-845:1987, 845.10.01, modified — Notes 1 and 2 are deleted.]

3.13
luminaire optics
all luminaire components that modify the spatial and directional characteristics of the radiation emitted by the primary light source inside the luminaire

3.14
primary light source
surface or object emitting light produced by a transformation of energy

Note 1 to entry: For the purpose of this Technical Report, it may refer to an LED package, an LED module, or a lamp.

[SOURCE: IEC 60050-845:1987, 845.07.01, modified — A new note to entry is added.]

3.15
radiance <in a given direction, at a given point of a real or imaginary surface>
L_e
quantity defined by the formula

$$L_e = \frac{d\Phi_e}{dA \cdot \cos\theta \cdot d\Omega}$$

where $d\Phi_e$ is the radiant flux transmitted by an elementary beam passing through the given point and propagating in the solid angle $d\Omega$ containing the given direction; dA is the area of a section of that beam containing the given point; θ is the angle between the normal to that section and the direction of the beam.

Note 1 to entry: Radiance (in a given direction, at a given point of real or imaginary surface) is expressed in $W/(m^2 \cdot sr)$.

Note 2 to entry: The spectral power distribution of the radiance, as a function of wavelength, is denoted by $L_\lambda(\lambda)$.

Note 3 to entry: For the purposes of this document, it is important to mention, that when $L_\lambda(\lambda)$ is known, it can be converted to luminance (L) when weighted with the CIE 1924 photopic eye sensitivity spectrum $V(\lambda)$, and to blue light weighted radiance (L_B) when weighted with the blue light spectral weighting function as defined in IEC 62471.

[SOURCE: IEC 60050-845:1987, 845.01.34, modified — Notes to entry 1 to 5 are deleted and new notes to entry are introduced.]

3.16
risk group
RG
risk classification when the product, at the relevant evaluation position, gives rise to a certain t_{max} value, according to Table 1, as defined in IEC 62471

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

Table 1 – Correlation between exposure time and risk group

Risk group number	Risk group name	Corresponding t_{max} range s
RG0	Exempt	> 10 000
RG1	Low risk	100 to10 000
RG2	Moderate risk	0,25 to100
RG3	High risk	< 0,25

3.17
maximum permissible exposure time
t_{max}
maximum permissible exposure time as calculated using the relevant formulae in 4.3.3 and 4.3.4 of IEC 62471:2006

3.18
true luminance
luminance value as obtained by integrating the equation as given in the definition of luminance, over a certain area of a light source, such that only the light emitting surface (or part of it) is included in the integration, and no dark surface area surrounding the light emitting part of the light source

Note 1 to entry: When a luminance measurement is performed over a certain field of view, it will only give a true luminance value when the field of view underfills the light emitting part of the light source.

3.19
true radiance
radiance value as obtained by integrating the equation as given in the definition of radiance , over a certain area of a light source, such that only the light emitting surface (or part of it) is included in the integration, and no dark surface area surrounding the light emitting part of the light source

Note 1 to entry: When a radiance measurement is performed over a certain field of view, it will only give a true radiance value when the field of view underfills the light emitting part of the light source.

3.20
LED package
one single electrical component encapsulating principally one or more LED dies, possibly with optical elements and thermal, mechanical, and electrical interfaces

Note 1 to entry: The component does not include the control unit of the controlgear, does not include a cap, and is not connected directly to the supply voltage.

Note 2 to entry: An LED package is a discrete component and part of the LED module. For a schematic build-up of an LED package, see Annex A of IEC 62504[1].

3.21
secondary optics
optics that are not part of the LED package itself

3.22
threshold distance
d_{thr}
distance from the light source at which the illuminance produced by that light source is equal to the E_{thr} value for that light source

[1] To be published.

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62778:2014

4 General

IEC 62471 is a comprehensive horizontal standard, describing all potential health hazards associated with artificial optical radiation, from the ultraviolet, visible, and infrared portions of the spectrum. This Technical Report deals exclusively with the hazard described in 4.3.3 and 4.3.4 of IEC 62471:2006. This hazard is called the retinal blue light hazard, as it is an effect mainly induced by the blue portion of the visible spectrum, which has its potentially damaging effects on the retina. The effects are described in Clause A.3 of the same standard.

Because the effect takes place on the retina, it is a function not only of the total amount of light that reaches the eye, but also of the size of the light source that produced this light. Larger light sources are imaged onto a larger portion of the retina, and therefore produce a lower irradiance on the retina than smaller light sources producing the same amount of light in the direction of the viewer's eye. Subclause 4.3.3 of IEC 62471:2006 takes this into account by relating the maximum permissible exposure time, t_{max}, to the radiance of the light source. Radiance (unit: $W/(m^2 \cdot sr)$) is a quantity describing the radiometric intensity, which is the radiation power emitted into a certain direction, divided by the apparent area of the light source when viewed from that same direction. In an imaging system, such as the eye, the local irradiance on the image plane (which for the eye is on the retina) is proportional to the radiance of the source.

Only when the light source is too small to be imaged sharply, or when it is so small that it will never be fixated on the same portion of the retina for so long that it can produce any damage, the radiance value is not the appropriate value. In this case, 4.3.4 of IEC 62471:2006 shall be applied, where the irradiance on the pupil is used as a value proportional to the effective irradiance on the retina.

The question whether a light source is "large", such that 4.3.3 shall be applied, or "small", such that 4.3.4 shall be applied, depends on the size of the light source as well as on the viewing distance. The subtended angle of the light source is used as discriminating quantity. When the time needed to produce damage is longer than 10 s, IEC 62471 states that the limiting subtended angle for a light source to be large or small is 0,011 rad. For light sources just on the edge between large and small, t_{max} can be calculated either way (using its radiance according to 4.3.3 and using the irradiance according to 4.3.4), which will produce the same result within about 5 %. The deviation of 5 % is caused by rounding of the conversion factors used to convert the radiometric quantity to t_{max}.

In the context of IEC 62471, "light source" means any product used to produce light. In real life, there is a hierarchy of lighting products, where light source is generally used to describe the constituent component of the lighting product that actually produces the light. Since some of the other components of the lighting product, most notably the luminaire optics, may change the radiation characteristics of the primary light source, it is important to know whether and how a photobiological assessment of the primary light source can be transferred to the product using this primary light source as light generating component.

Next to this, IEC 62471 makes a statement about risk classification of products. Because the t_{max} values as calculated in 4.3 of IEC 62471:2006 are determined both by the product itself and by the distance from which it is viewed, these cannot in themselves be used to determine a unique risk classification for a product. For this reason, IEC 62471:2006, Clause 6 states the standard conditions where photobiological safety shall be evaluated to determine risk classification of the products. For lamps intended for general lighting service (GLS), as defined in 3.11 of the same standard, the hazard values shall be reported at a distance which produces an illuminance of 500 lx, but not at a distance less than 200 mm. For all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm. Examples of these non-GLS light sources are given in the same 3.11 and include lamps for such uses as film projection, sun-tanning, and industrial processes. In some cases, the same lamp may be used in both GLS and special applications and in such cases should be evaluated and rated for the intended applications. At the evaluation distance, t_{max} is determined, and when it falls below 100 s, the product is classified as risk group 2 (RG2) and a cautionary labelling is required.

AVA Documents
Document Sharing Hub