PD IEC/TR 62795:2013

BSI Standards Publication

Interoperation guide for field device tool (FDT)/device type manager (DTM) and electronic device description language (EDDL)

bsi.

...making excellence a habit.™

Document Sharing Hub

National foreword

This Published Document is the UK implementation of IEC/TR 62795:2013.

The UK participation in its preparation was entrusted to Technical Committee AMT/7, Industrial communications: process measurement and control, including fieldbus.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013.
Published by BSI Standards Limited 2013

ISBN 978 0 580 78882 6
ICS 25.040.40; 35.240.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 October 2013.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62795:2013

IEC/TR 62795

Edition 1.0 2013-09

TECHNICAL REPORT

colour inside

Interoperation guide for field device tool (FDT) / device type manager (DTM) and electronic device description language (EDDL)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE U

ICS 25.040.40; 35.240.50

ISBN 978-2-8322-1116-8

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62795:2013

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions, and abbreviations 7
3.1 Terms and definitions 7
3.2 Abbreviations 8
4 Typical methods to convert EDD to FDT/DTM 8
4.1 Overview 8
4.2 Using a universal DTM to integrate the EDD document 9
4.2.1 General 9
4.2.2 Basic contents of the transformation from EDD to DTM 9
4.2.3 Procedure 10
4.3 Using a converting tool to integrate EDD documents 11
4.3.1 General 11
4.3.2 Basic contents 12
4.3.3 Procedure 12
4.4 Generate an FDT/DTM based on EDD documents 13
5 General requirements for the conversion from EDD to FDT 13
5.1 Overview 13
5.2 Requirements for the agent interpreter 13
5.2.1 General 13
5.2.2 Standardized requirements of the basic parameters description 16
5.2.3 Standardized requirements of the fieldbus communication protocol mapping 17
5.2.4 Standardized requirements of the device parameters visual description 17
5.2.5 Standardized requirements of error handling 18
5.3 The requirements of EDD document format 19
5.4 Requirements for EDD storage management 19
5.5 The user interface style requirements of FDT/DTM converted from EDDL 20
5.5.1 Overview 20
5.5.2 Basic requirements of the FDT/DTM interface design 20
5.5.3 FDT/DTM user interface 20
5.5.4 FDT/DTM user interface areas 21
5.5.5 Parameter handling 24
Annex A (informative) Standard user interface of FDT/DTM 26
Bibliography 27

Figure 1 – EDD to DTM conversion flowchart 11
Figure 2 – EDD to DTM general process of conversion flowchart 12
Figure 3 – Basic parameter description mapping 17
Figure 4 – Communication mapping 17
Figure 5 – User interface mapping 18
Figure A.1 – Specific example of FDT/DTM's standard user interface 26

AVA Documents
Document Sharing Hub

Table 1 – EDD basic elements 14
Table 2 – The related interfaces of DTM 15
Table 3 – Standard user interface of FDT/DTM 21
Table 4 – Contents of Identification Area 21
Table 5 – Contents of Action Area 22
Table 6 – Elements of the Status Bar 23
Table 7 – Connection states of DTM 23
Table 8 – Data source states 24
Table 9 – States of the instance data set 24
Table 10 – Device diagnostic states 24

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62795:2013

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INTEROPERATION GUIDE FOR FIELD DEVICE TOOL (FDT) / DEVICE TYPE MANAGER (DTM) AND ELECTRONIC DEVICE DESCRIPTION LANGUAGE (EDDL)

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62795, which is a technical report, has been prepared by subcommittee 65E: Devices and integration in enterprise systems, of IEC technical committee 65: Industrial-process measurement, control and automation.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
65E/240/DTR	65E/330/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

AVA Documents
Document Sharing Hub

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC/TR 62795:2013

INTRODUCTION

At present, there are two International Standards for device integration that describe the properties of automation system components to be used in host systems. They are IEC 61804 for electronic device description language (EDDL) and IEC 62453 for field device tools (FDT), with both standards having their own characteristics. The number of manufacturers and users using EDDL or FDT technologies is increasing, and investment in both of them is therefore increasing too.

EDDL technology enables the integration of real product details using the tools of the engineering life cycle and specifies EDDL as a generic language for describing the properties of automation system components. EDDL technology allows to transfer the properties of a device to a data set, called electronic device description (EDD), that can be interpreted by configuration tools in a host system. EDD files, representing the behavior and attributes of a device, can be stored in the field device or control system. The interaction between a field device and a control system uses various communication protocols such as specified in IEC 61784-1, CP 1-1 (FF) or IEC 61784-1, CP 9-1 (HART®[1]).

FDT is an open and independent software interface specification. An FDT specification describes software interface and relationships within the framework of the project (FDT container, FDT frame applications) and device software components in a Device Type Manager (DTM). An FDT framework is independent from the devices and fieldbus system, while the DTM depends on specific device and fieldbuses.

Both technologies are supported by automation vendors and users, so that there is a need to generate a DTM based on an EDD as long as the field device integration (FDI) technology is not published as an International Standard.

FDI (IEC 62769) covers device integration and device management technology, combining base concepts and technology aspects of the EDDL (IEC 61804), FDT (IEC 62543) and OPC UA (IEC 62541-1). The combination of those different proven technologies ensures a secure life cycle and the ability to address all challenges of device integration and device management in a scalable manner.

EDDL and FDT are complimentary in a way that an EDDL can be converted into an FDT-DTM. As long as FDI is not available, converting EDD into a DTM helps to combine the two standards and use EDDs in an FDT frame environment in case there is no specific DTM available. The conversion criterion is based on EDDL and FDT technologies.

[1] HART® is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of this product.

AVA Documents
Document Sharing Hub
Full document details: PD IEC/TR 62795:2013

INTEROPERATION GUIDE FOR FIELD DEVICE TOOL (FDT) / DEVICE TYPE MANAGER (DTM) AND ELECTRONIC DEVICE DESCRIPTION LANGUAGE (EDDL)

1 Scope

This Technical Report provides the general requirements for converting an EDD into a DTM. Using this TR, an FDT/DTM developer can develop an EDD-DTM conversion tool that can be used to import, parse, and manage EDD to generate the corresponding DTM. A conversion tool versus a DTM written independent of an EDD helps the DTM generation to maintain consistency in function, data and presentation styles.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61804 (all parts), *Function blocks (FB) for process control*

IEC 61804-3:2010, *Function blocks (FB) for process control – Part 3 Electronic Device Description Language (EDDL)*

IEC 62453-1:2009, *Field device tool (FDT) interface specification – Part 1: Overview and guidance*

3 Terms, definitions, and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62453-1, IEC 61804-3, as well as the following apply.

3.1.1
agent interpreter
analytical software for parsing EDD

Note 1 to entry: An agent interpreter can parse out the elements in the EDD document and map to the DTM.

Note 2 to entry: An agent interpreter can realize the interaction between the DTM and the physical device.

3.1.2
application
software functional unit that is specific to the solution of a problem in industrial-process measurement and control

Note 1 to entry: An application may be distributed across multiple resources, and may communicate with other applications.

[SOURCE: IEC 61499-1:2005, 3.5]

Documents
Document Sharing Hub
Full document details: PD IEC/TR 62795:2013

3.1.3
device type manager
DTM
device-specific application software components

3.1.4
field device tool
FDT
interfaces for data exchange among the field devices and control systems, engineering tools, and resource management system tools

3.2 Abbreviations

BTM	Block type manager
COM	Component object model
CP	Communication profile
DCS	Distributed control system
DD	Device description
DLL	Dynamic link library
DTM	Device type manager
EDD	Electronic device description
EDDL	Electronic device description language
ERP	Enterprise resource planning
FA	Frame application
FB	Function block
FDI	Field device integration
FDT	Field device tool
FF	Fieldbus Foundation
GUI	Graphical user interface
I/O	Input/output
ID	Identifier
IT	Information technology
MES	Manufacturing execution systems
OLE	Object linking and embedding
OPC	Open connectivity via open standards
PLC	Programmable logic controller
SCADA	Supervisory, control and data acquisition
UML	Unified modeling language
UUID	Universal unique identifier
XML	Extensible markup language

4 Typical methods to convert EDD to FDT/DTM

4.1 Overview

There are three typical methods to integrate EDD documents into FDT:

- Using a universal DTM to integrate EDD documents.

Documents
Document Sharing Hub