PD IEC TR 63449:2023

BSI Standards Publication

Dynamic metadata high dynamic range impacts on TV power consumption

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

National foreword

This Published Document is the UK implementation of IEC TR 63449:2023.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio-visual equipment.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 22347 7

ICS 33.160.40

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 May 2023.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

IEC TR 63449

Edition 1.0 2023-05

TECHNICAL REPORT

colour inside

Dynamic metadata high dynamic range impacts on TV power consumption

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.40

ISBN 978-2-8322-6849-0

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 7
3.1 Terms and definitions 7
3.2 Abbreviated terms 11
4 Dynamic metadata high dynamic range video 12
4.1 Introduction to dynamic metadata HDR video 12
4.1.1 Overview 12
4.1.2 Dolby Vision® 13
4.1.3 HDR10+ 13
4.2 Market relevance of dynamic metadata HDR video 14
4.2.1 Dolby Vision® market snapshot 14
4.2.2 HDR10+ market snapshot 15
4.3 Consumer availability of dynamic metadata HDR video technologies in TVs 15
5 Dynamic metadata HDR TV power consumption research 16
5.1 Overview 16
5.2 Dynamic metadata test media 16
5.3 Dynamic metadata laboratory tests 21
5.3.1 General 21
5.3.2 General research method 21
5.3.3 Phase I testing: assessing the overall impact of dynamic metadata 22
5.3.4 Phase II testing: next level of detail 23
5.3.5 Phase III: in-depth testing with one TV 30
6 Summary 32
Annex A (informative) Test material workflows 34
Bibliography 36

Figure 1 – Occurrence of linear and non-linear signal encodings in context of a typical display processing pipeline and how they can be used to compute APL and APL' 8
Figure 2 – Power use with dynamic metadata 25
Figure 3 – Screen-average dynamic luminance with dynamic metadata vs static metadata 26
Figure 4 – Relative efficiency of TVs when playing different content formats 27
Figure 5 – Normalized comparison of LED TVs playing Table 1 UHD Dolby Vision® and HDR10+ 5 min test clips 29
Figure 6 – Phase III test results by content category 32

Table 1 – Static and dynamic metadata test media 17
Table 2 – HDR10+ test media metadata 18
Table 3 – Dolby Vision® test media metadata 19
Table 4 – Results of phase I testing 22
Table 5 – Summary of phase I testing 23
Table 6 – Characteristics of TV models used for the test media validation 23

AVA Documents
Document Sharing Hub

Table 7 – 4K real-world content used for tests 24
Table 8 – Phase II: real world content (streamed movies/series) 24
Table 9 – Phase III: HDR10+ and SDR using non-test clips 30
Table 10 – Phase III: test clips only 30
Table 11 – Phase III test results 31
Table A.1 – Workflow details 35

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DYNAMIC METADATA HIGH DYNAMIC RANGE IMPACTS ON TV POWER CONSUMPTION

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TR 63449 has been prepared by Technical Area 19: Environmental and energy aspects for multimedia systems and equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment. It is a Technical Report.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
100/3862/DTR	100/3886/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

AVA Documents
Document Sharing Hub

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

INTRODUCTION

HDR technologies affect the entire video ecosystem from production and processing, through to distribution and presentation. HDR-capable television sets typically have higher peak luminance and better low-luminance capabilities than non-HDR TVs and can take advantage of HDR video signals which typically represent scenes with much higher luminance and more detailed low-luminance levels than was possible in traditional analogue and digital non-HDR video systems.

As the luminance range of an HDR signal might not match the luminance range capabilities of the display device, the signal must be adjusted before being displayed. This luminance adjustment is called tone-mapping and is implemented as a processing step in the TV. The tone mapping process can be improved with metadata, which describes the properties of the content to be displayed.

Dynamic metadata based HDR tone-mapping approaches and behaviours are seeing an ever-increasing application in consumer televisions; however, representative standardized test content for measurement of the power consumption impact of those technologies on televisions is not available. To prepare objective test materials (video clips), a study of power and luminance behaviour was conducted, the results of which are described in Clauses 5 and 6.

This document assesses the impact of dynamic HDR on TV luminance and power consumption using two technologies currently in deployment.

A small sample of TVs that supported the two technologies were studied using "representative" content prepared by PT100-24 members. Test results show that dynamic metadata HDR content, delivered to a dynamic metadata capable TV, can provide pictures with even greater dynamic range (higher peak luminance and more detailed luminance levels with wider colour gamut) than static HDR at the same or lower TV power consumption versus static HDR or SDR content delivered to that same TV.

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

DYNAMIC METADATA HIGH DYNAMIC RANGE IMPACTS ON TV POWER CONSUMPTION

1 Scope

This document presents a study of the impact of high dynamic range (HDR) technologies with "dynamic metadata" on TV luminance and power consumption. It compares the power consumption of content with dynamic metadata to the same content without dynamic metadata. Non-dynamic "static metadata" HDR technologies such as HDR10 and non-metadata HDR such as HLG, were previously studied in IEC TR 63274:2021.

This document also reviews the current HDR TV market and analyses existing HDR TV power measurement methods and considerations for any changes to those power measurement standards.

While this document studies the results of content that include Dolby Vision® and HDR10+ dynamic metadata, any comparison of these two technologies is outside of the scope of this document.

2 Normative references

There are no normative references in this document.

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1 Terms and definitions

3.1.1
average picture level
APL
average level of all the pixels of a single video signal frame in the linear luminance domain

EXAMPLE Display equipment such as television sets or computer monitors that internally use linear encoding after undoing the non-linearity of the input signal.

[SOURCE: IEC TR 63274:2021, 3.1.10]

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

3.1.2
average picture level based on non-linear input signal
APL′
average level of all pixels of a single video signal frame in the non-linear luminance domain

EXAMPLE Display equipment such as television sets or computer monitor receive input signals that encode luminance in a non-linear way. Examples for such non-linear encoding are PQ or HLG EOTFs (ITU-R BT.2100).

Note 1 to entry: APL′ is defined as a percentage of the range between reference black and reference white level.

Note 2 to entry: This is not a measure of the linear signal that might be available inside of some display equipment and delivered to the display device. The external and internal video signals are shown in Figure 1.

[SOURCE: IEC TR 63274:2021, 3.1.11]



Figure 1 – Occurrence of linear and non-linear signal encodings in context of a typical display processing pipeline and how they can be used to compute APL and APL'

3.1.3
colour gamut
maximum area of chromaticity reproducible by a display

[SOURCE: IEC 62977-2-1:2021, 3.1.5, modified – "area" deleted from term]

3.1.4
colour volume
three-dimensional space of all colours and intensities that a device or signal can reproduce or convey

[SOURCE: ISO/IEC TR 23091-4:2021, 3.6, modified – "three-dimensional" added to definition]

3.1.5
content light level
CLL
integer static HDR metadata value defining the luminance of any single pixel within an encoded HDR video sequence

Note 1 to entry: The CLL is provided in candelas per square metre (cd/m^2).

3.1.6
maximum content light level
MaxCLL
integer static HDR metadata value defining the maximum luminance of any single pixel within an encoded HDR video sequence

Note 1 to entry: The MaxCLL is provided in candelas per square metre (cd/m^2).

Note 2 to entry: CTA-861 provides further explanation.

Documents
Document Sharing Hub
Full document details: PD IEC TR 63449:2023

3.1.7
dynamic metadata
metadata that can be different for different portions of the image essence

[SOURCE: SMPTE ST 2094-1:2016, 4.6]

3.1.8
electro-optical transfer function
EOTF
mathematical function for transferring an electrical signal into a desired optical signal

EXAMPLE EOTFs are typically non-linear and monotonic and aim to incorporate behaviour of the human visual system, e.g. on a display device. Some are absolute, addressing luminance values directly, while others are of relative nature.

[SOURCE: IEC TR 63274:2021, 3.1.1]

3.1.9
frame average light level
FALL
integer static HDR metadata value defining the average luminance for all pixels of any single frame within an encoded HDR video sequence

Note 1 to entry: The FALL is provided in candelas per square metre (cd/m^2).

3.1.10
maximum frame average light level
MaxFALL
integer static HDR metadata value defining the maximum average luminance for all pixels of any single frame within an encoded HDR video sequence

Note 1 to entry: The MaxFALL is provided in candelas per square metre (cd/m^2).

Note 2 to entry: CTA-861 provides further explanation.

3.1.11
high definition
HD
spatial video resolution ranging from 1 280 × 720 to 1 920 × 1 080

[SOURCE: IEC TR 63274:2021, 3.1.6]

3.1.12
high dynamic range video
HDR video
capability of components in a video pipeline to capture, process, transport or display luminance levels and tone gradations that exceed capabilities of conventional SDR imaging pipelines components

Note 1 to entry: An HDR video signal typically uses a greater bit depth, luminance and colour volume than standard dynamic range (SDR) video. It also typically utilizes different tone curves such as perceptual quantizer (PQ) as specified in SMPTE ST 2084 or hybrid log gamma (HLG) specified in ITU-R BT.2100 instead of gamma, as used with SDR. When the HDR video signal is rendered on an HDR display, it is possible to see greater luminance ranges and wider colour gamuts.

Note 2 to entry: HDR video can provide an enhanced viewer experience and can more accurately reproduce scenes that include, within the same image, dark areas and bright highlights, such as emissive light sources and reflections. The luminance range of an HDR image is typically constrained between 0,005 cd/m^2 to 4 000 cd/m^2.

[SOURCE: IEC TR 63274:2021, 3.1.2, modified – The last sentence of Note 2 to entry has been added.]

Documents
Document Sharing Hub

Full document details: PD IEC TR 63449:2023

3.1.13
hybrid log-gamma
HLG
one set of HDR transfer functions offering a degree of backwards compatibility to SDR by more closely matching the previously established television transfer curves

Note 1 to entry: Sets of transfer functions related to HDR signals are specified in Rec. ITU-R BT.2100-1.

Note 2 to entry: HLG is used both as a description of a dedicated transfer function and as a video format name.

[SOURCE: IEC 62087-2:2023, 3.1.9, modified – Added 'to SDR'.]

3.1.14
image-related metadata
identifiers describing intrinsic image properties in form of both static metadata valid throughout the content and dynamic metadata for frame-specific image parameters

EXAMPLE 1 Minimum and maximum luminance, average picture level, properties of the grading display.

EXAMPLE 2 HDR image related static metadata are MaxCLL and MaxFall as specified in CTA-861-G, section 6.9.1 and Appendix P, sections P.1 and P.2 for algorithms to calculate each.

EXAMPLE 3 Dynamic metadata is utilized by Dolby Vision® (SMPTE ST 2094-10) and HDR10+ (SMPTE ST 2094-40).

Note 1 to entry: They can be used as recommendations and guidance for image rendering and display.

[SOURCE: IEC TR 63274:2021, 3.1.9]

3.1.15
perceptual quantizer
PQ
one set of HDR transfer functions addressing a very wide range of absolute luminance levels for a given bit depth using a non-linear transfer function that is finely tuned to match the sensitivity of the human visual system

Note 1 to entry: Sets of transfer functions related to HDR signals are specified in Rec. ITU-R BT.2100-1.

[SOURCE: ISO/IEC TR 23008-15:2018, 3.8, modified – In the definition, "brightness" has been replaced with "luminance".]

3.1.16
signal identification metadata
identifiers describing the properties of an image stream

EXAMPLE Format, resolution, colour space, chroma subsampling, bit-depth, image compression, image transport.

[SOURCE: IEC TR 63274:2021, 3.1.8]

3.1.17
standard dynamic range video
SDR video
capability of components in a video pipeline to capture, process, transport or display luminance levels and tone gradations that can be characterized by the dynamic range, colour rendering and tone gradation capabilities essentially compatible with cathode ray tube (CRT) displays

EXAMPLE ITU-R BT.709 /BT.1886 and IEC 61966-2-1 (sRGB).

Note 1 to entry: The luminance range of an SDR image is typically constrained between 0,1 cd/m^2 to 100 cd/m^2.

[SOURCE: IEC TR 63274:2021, 3.1.3]

Documents
Document Sharing Hub
Full document details: PD IEC TR 63449:2023