



BSI Standards Publication

Fire hazard testing

Part 2-21: Glowing/hot-wire based test methods —
Fire containment test on finished units

National foreword

This Published Document is the UK implementation of IEC TS 60695-2-21:2023.

The UK participation in its preparation was entrusted to Technical Committee GEL/89, Fire hazard testing.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 05915 1

ICS 13.220.40

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2023.

Amendments/corrigenda issued since publication

Date	Text affected
<hr/>	

TECHNICAL SPECIFICATION



**Fire hazard testing –
Part 2-21: Glowing/hot-wire based test methods – Fire containment test on
finished units**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 13.22.40

ISBN 978-2-8322-7122-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Test specimen	9
4.1 General.....	9
4.2 Verification of potential ignition sources	9
4.3 Test conditions	10
5 Test apparatus	10
5.1 Nickel-Chromium wire (NiCr wire)	10
5.2 Test circuit.....	10
5.3 Connections.....	10
5.4 Cheesecloth.....	10
5.5 Test chamber.....	10
5.6 Timing device	11
6 Verification of the NiCr wire	11
7 Conditioning	11
7.1 Conditioning of the test specimen	11
7.2 Conditioning of the cheesecloth	11
7.3 Testing condition	11
8 Test procedure	11
8.1 Flow chart.....	11
8.2 Identification of potential ignition sources.....	13
8.3 Factors affecting test	14
8.4 Application of NiCr wire.....	14
8.5 Selection of NiCr wire application methodology.....	15
8.6 Potential ignition source verification.....	16
8.7 Test specimen fire containment verification.....	17
9 Observations and measurements.....	18
9.1 Initial observations.....	18
9.2 Test observations	18
10 Evaluation of test results	18
11 Test report.....	19
12 Information to be given in the relevant product standard	19
Annex A (normative) Interpretations of the location of the cylindrical volume	20
Annex B (normative) NiCr wire application methods – Internal coil winding method.....	21
B.1 General.....	21
B.2 Insulating material cavity preparation	21
B.3 NiCr wire coil preparation.....	21
Annex C (normative) NiCr wire application methods – External winding method.....	24
C.1 General.....	24
C.2 Insulated connections winding method	24
C.3 Non-insulated connections winding method.....	25
C.4 Examples of electrical connections applying the external winding method.....	26

C.4.1	General	26
C.4.2	Insulated terminals providing mechanical support function.....	26
C.4.3	Insulated terminals with one side not accessible	26
Annex D (informative)	Examples of supply wires fixation methodologies	28
D.1	General.....	28
D.2	Fixation over existing electrical connection supply harness	28
D.3	Fixation over surrounding parts.....	28
Bibliography.....		30
Figure 1 – Test procedure flow-chart.....		12
Figure 2 – Insulating material cavity cross sectional dimensions		16
Figure 3 – NiCr wire application methodology selection flow-chart		16
Figure A.1 – Examples of the location of the cylindrical volume		20
Figure B.1 – Winding tool.....		22
Figure B.2 – Example 1 of NiCr wire coil application		23
Figure B.3 – Example 2 of NiCr wire coil application		23
Figure B.4 – Example 3 of NiCr wire coil application		23
Figure C.1 – Single connection insulating material external winding – Side View		24
Figure C.2 – Single connection insulating material external winding – Front view.....		25
Figure C.3 – Example of non-insulated single terminal electrical connection		26
Figure C.4 – Example of insulated terminals providing mechanical support function.....		26
Figure C.5 – Example of insulated terminal with one side not accessible		27
Figure D.1 – Fixation over existing harness by stripe		28
Figure D.2 – Fixation over surrounding parts by adhesive tape – Side view		29
Figure D.3 – Fixation over surrounding parts by adhesive tape – Top view		29
Table B.1 – Drill bit and winding tool dimensions		22

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIRE HAZARD TESTING –

**Part 2-21: Glowing/hot-wire based test methods –
Fire containment test on finished units**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 60695-2-21 has been prepared by IEC technical committee 89: Fire hazard testing. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
89/1554/DTS	89/1561A/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This publication has the status of a Technical Specification in accordance with IEC Guide 104 and ISO/IEC Guide 51.

NOTE The following print types are used:

- terms defined in Clause 3: in **bold** type.

A list of all parts in the IEC 60695 series, published under the general title *Fire hazard testing*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Fires might create hazards to life and property as a result of the generation of heat (emission of heat on fire hazard), and also as a result of the production of toxic effluent, corrosive effluent and smoke (fire effluents on the fire hazard). Fires start with ignition and then can grow, leading in some cases to flash-over and a fully developed fire. Resistance to ignition is therefore one of the most important parameters of a material to be considered in the assessment of a fire hazard.

Most current fire hazard assessment techniques evaluate the resistance to ignition characteristics of a single material or component. These assessment techniques are able to drive the preselection and validation of materials and components but are not able to evaluate the possible interaction of materials or components in a complex environment such as in a finished unit, once a fire event is initiated.

In a fault condition, a finished unit might be subject to the overheating of electrical connections and contacts. Such overheating can be caused by corrosion, poor crimp connections, incorrect assembly, erosion of contact surfaces, or mechanical fatigue. Insulating materials that are overheated can ignite and cause fire.

It is difficult to simulate the actual conditions of potential faults in finished units; therefore all possible fire hazards should be taken into account at the design stage and subsequently during the preselection of materials and components.

This fire containment test has been developed to verify if a finished unit is able to contain an internal fire event, generated by combustible parts ignited by a simulated overheated electrical connection.

FIRE HAZARD TESTING –

Part 2-21: Glowing/hot-wire based test methods – Fire containment test on finished units

1 Scope

This part of IEC 60695, which is a Technical Specification, specifies a **fire** containment test method for **finished units**. It is intended to verify the capability of containing of a fire event generated by an **effective ignition source** inside a **finished unit**.

Unless otherwise specified by the relevant product standard, determination of the **fire** containment described in this document does not apply to any of the following:

- A single electrical component;
- A single electrical component when incorporated into a **finished unit**;
- Electrical installation products such as distribution boards, circuit protection devices, switchgear, controlgear, cable management system and electrical accessories (wiring devices).

The test method described in this document does not apply to the following electrical connections:

- Low-power electrical connections contained in **finished units**, where the maximum power through the connection does not exceed 15 W.
- Soldered and welded electrical connections are exempted from the evaluations of this document.

This document is intended to be used for evaluating the capability of **fire** containment of **finished units**, during the selection of **finished units** and in the design of **finished units**.

The requirements, test method or test conditions of this document will not apply unless specifically referred to or included in the relevant publications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62368-1:2018, *Audio/video, information and communication technology equipment – Part 1: Safety requirements*

ISO 13943:2017, *Fire safety – Vocabulary*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

cheesecloth

bleached cotton cloth of approximately 40 g/m²

[SOURCE: IEC 62368-1:2018, 3.3.6.2, modified – Deleted the Note to entry]

3.2

draught-free environment

space in which the results of experiments are not significantly affected by the local air speed

Note 1 to entry: A qualitative example is a space in which a wax candle **flame** remains essentially undisturbed. Quantitative examples are small-scale **fire** tests in which a maximum air speed of 0,1 m·s⁻¹ or 0,2 m·s⁻¹ is sometimes specified.

[SOURCE: ISO 13943:2017, 3.83]

3.3

effective ignition source

potential ignition source that has been proved to be able to initiate combustion of surrounding insulating material or combustible parts

Note 1 to entry: The proving methodology is defined by the test specified in 8.6.

3.4

enclosure

<electrotechnical> external casing protecting the electrical and mechanical parts of apparatus

Note 1 to entry: The term excludes cables.

[SOURCE: ISO 13943:2017, 3.93]

3.5

finished unit

complete unit which is designed to stand alone, usable by an end-user and having a direct function for the end-user

Note 1 to entry: It is intended to be placed on the market and/or taken into service as single unit.

Note 2 to entry: Electrical installation products such as distribution boards, circuit protection devices, switchgear, controlgear, cable management system and electrical accessories (wiring devices) are not considered to be finished units.

3.6

fire

process of combustion characterized by the emission of heat and fire effluent and usually accompanied by smoke, **flame** or glowing or a combination thereof

Note 1 to entry: In English language the term "**fire**" is used to designate three concepts, two of which relate to specific types of self-supporting combustion with different meanings. Of these three, two of them are designated using two different terms in both French and German.

[SOURCE: ISO 13943:2017, 3.114, modified – The domain <general> has been deleted.]

3.7

flame, noun

rapid, self-sustaining, sub-sonic propagation of combustion in a gaseous medium, usually with emission of light

[SOURCE: ISO 13943:2017, 3.159]

3.8

ignition

DEPRECATED: sustained **ignition**

initiation of sustained **flame**

[SOURCE: ISO 13943:2017, 3.218]

3.9

low-power point

electrical connection where the power dissipated at the connection does not exceed 15 W

Note 1 to entry: To dissipate more than 15 W at an electrical connection, the power delivered to a resistive load via the electrical connection must exceed 60 W. This is based on the maximum power transfer theorem that shows that an electrical connection can only dissipate one-fourth of the power delivered to a resistive load when the resistance of the connection is equal to the resistance of the load.

3.10

non-combustible material

not capable of undergoing combustion (see ISO 13943:2017, 3.55) under specified test conditions

EXAMPLE According to the test method described in this document, steel, glass, ceramic and concrete are considered examples of non-combustible materials.

[SOURCE: ISO 13943:2017, 3.282, modified – Added "test"]

3.11

potential ignition source

electrical connection where electrical energy can cause **ignition**

[SOURCE: IEC 62368-1:2018, 3.3.9.1, modified – Deleted "PIS" and "location"]

4 Test specimen

4.1 General

The test specimen is a **finished unit**.

4.2 Verification of potential ignition sources

Before carrying out any tests on the test specimen, it is necessary to identify electrical connections and verify if these are **potential ignition sources** as described in 3.2 to 3.6.