



BSI Standards Publication

Shunt capacitors for AC power systems having a rated voltage above 1 000 V

Part 3: Protection of shunt capacitors and shunt capacitor banks

National foreword

This Published Document is the UK implementation of IEC TS 60871-3:2015+A1:2023. It supersedes PD IEC/TS 60871-3:2015, which is withdrawn.

The start and finish of text introduced or altered by amendment is indicated in the text by tags. Tags indicating changes to IEC text carry the number of the IEC amendment. For example, text altered by IEC amendment 1 is indicated by **A1** **A1**.

The UK participation in its preparation was entrusted to Technical Committee W/-, Consumer Products and Services Sector Policy and Strategy Committee.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 28477 5

ICS 29.240.99; 31.060.70

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2015.

Amendments/corrigenda issued since publication

Date	Text affected
30 September 2023	Implementation of IEC amendment 1:2023

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Internal fuses	7
4.1 General	7
4.2 Fuse characteristics	8
4.2.1 Rated current.....	8
4.2.2 Rated discharge capability	8
4.2.3 Disconnecting capability	8
4.2.4 Voltage withstand capability after operation.....	8
4.3 Influence of capacitor element configuration on capacitor life.....	8
4.3.1 Capacitor with all elements connected in parallel.....	8
4.3.2 Capacitor with elements connected in series and parallel	8
5 External fuses	8
5.1 General	8
5.2 Fuse characteristics	9
5.2.1 Rated current.....	9
5.2.2 Rated voltage	9
5.2.3 Time-current characteristics	9
5.2.4 Discharge capability.....	10
5.3 Fuse types	10
5.3.1 General	10
5.3.2 Expulsion fuses	10
5.3.3 Current-limiting fuses.....	11
5.3.4 Combination current-limiting/expulsion fuses.....	11
5.4 Influence of capacitor bank configuration on fuse selection.....	11
5.4.1 Single series section grounded star and delta banks	11
5.4.2 Single series section ungrounded star banks.....	11
5.4.3 Multiple series section banks	11
5.5 Coordination with case rupture curves.....	11
6 Unbalance detection.....	12
6.1 Operation.....	12
6.2 Types of unbalance protection.....	12
6.2.1 Neutral current (Figure 3).....	12
6.2.2 Neutral voltage (Figure 4)	12
6.2.3 Current unbalance between neutrals (Figure 5)	13
6.2.4 Phase voltage unbalance (Figure 6)	13
6.2.5 Voltage difference (Figure 7).....	13
6.2.6 Current unbalance in bridge connection (Figure 8)	13
6.3 Current and voltage transformers	13
6.3.1 Current transformers.....	13
6.3.2 Voltage transformers.....	14
6.4 Relays and protection settings	14
6.5 Sensitivity	14
6.6 Initial unbalance.....	15

7	Overload current	15
7.1	Operation.....	15
7.2	Protective arrangement.....	15
7.3	Current transformers	15
7.4	Relays	15
7.5	Protective settings	16
8	Over and undervoltage	16
8.1	Operation.....	16
8.2	Overvoltage protection	16
8.3	Undervoltage protection	16
8.4	Reclosing.....	16
9	Other protection	17
9.1	Surge arresters.....	17
9.1.1	General	17
9.1.2	Operation	17
9.1.3	Lightning transients.....	17
9.1.4	Switching transients.....	17
9.1.5	Temporary overvoltages.....	17
9.1.6	Rated voltage	17
9.1.7	Energy absorption.....	18
9.2	Damping devices	18
9.2.1	Capacitor switching.....	18
9.2.2	Inrush currents	18
9.2.3	Voltage transients.....	19
9.2.4	Ratings.....	19
9.3	Synchronized switching.....	19
9.3.1	Operation	19
9.3.2	Breaker contacts delay.....	19
10	Safety	19
10.1	Discharging devices.....	19
10.1.1	General	19
10.1.2	Internal resistors.....	20
10.1.3	External discharge devices	20
10.1.4	Discharging after disconnection	20
10.2	Dead metallic parts	20
	Bibliography	25
	Figure 1 – Fuse types	10
	Figure 2 – Typical case rupture curves for approximately 30 000 cm ³ case volume	21
	Figure 3 – Star connection with the neutral grounded through a current transformer	21
	Figure 4 – Star connection with voltage transformer between neutral and ground	21
	Figure 5 – Star connection with ungrounded neutral and voltage transformers connected in an open delta	22
	Figure 6 – Double-star connection with ungrounded neutral	22
	Figure 7 – Star connection with grounded neutral and voltage transformers connected in differential measurement.....	22
	Figure 8 – Bridge connection	22

Figure 9 – Line overcurrent relays for capacitor bank, grounded.....	22
Figure 10 – Line overcurrent relays for capacitor bank, ungrounded.....	23
Table 1 – Melting currents for type-K (fast) fuse links, in amperes.....	23
Table 2 – Melting currents for type-T (slow) fuse links, in amperes.....	24

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SHUNT CAPACITORS FOR AC POWER SYSTEMS HAVING A RATED VOLTAGE ABOVE 1 000 V –

Part 3: Protection of shunt capacitors and shunt capacitor banks

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

International Standard IEC 60871-3, which is a technical specification, has been prepared by IEC technical committee 33: Power capacitors and their applications.

This second edition cancels and replaces the first edition published in 1996. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Clearer writing of formulas on energy limitation for expulsion fuses;
- b) Updated normative references and bibliography;
- c) A new clause for synchronized switching has been added.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
33/545/DTS	33/563/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60871, published under the general title *Shunt capacitors for a.c. power systems having a rated voltage above 1 000 V*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

SHUNT CAPACITORS FOR AC POWER SYSTEMS HAVING A RATED VOLTAGE ABOVE 1 000 V –

Part 3: Protection of shunt capacitors and shunt capacitor banks

1 Scope

This part of IEC 60871, which is a technical specification, gives guidance on the protection of shunt capacitors and shunt capacitor banks. It applies to capacitors according to IEC 60871-1.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60549, *High-voltage fuses for the external protection of shunt capacitors*

IEC 60871-1, *Shunt capacitors for a.c. power systems having a rated voltage above 1 000 V – Part 1: General*

IEC 60871-4, *Shunt capacitors for AC power systems having a rated voltage above 1 000 V – Part 4: Internal fuses*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60549, IEC 60871-1 and IEC 60871-4 apply.

4 Internal fuses

4.1 General

Internal fuses for shunt capacitors are selective current-limiting fuses arranged inside a capacitor. As defined in IEC 60871-4, they are designed to isolate faulted capacitor elements or capacitor unit, to allow operation of the remaining parts of that capacitor unit and the bank in which the capacitor unit is connected.

The operation of an internal fuse is initiated by the breakdown of a capacitor element. The affected element is instantaneously disconnected by the operation of the element fuse without interruption in the operation of the capacitor.

The number of externally parallel connected capacitors and the available short-circuit current of the supply system should not affect the current-limiting of internal fuses.

It should be noted that internal fuses do not provide protection against a short circuit between internal connections or a short circuit between active parts and casing, both of which may lead to case rupture.

4.2 Fuse characteristics

4.2.1 Rated current

There is no definition or test method existing for element fuses.

Element fuses are, in general, designed for much higher currents than the maximum permissible element current. They are meant to disconnect only faulty elements. The faulty elements and their fuses are not intended to be replaced.

4.2.2 Rated discharge capability

IEC 60871-4 and IEC 60871-1 specify that the capacitor be subject to five undamped discharges from a d.c. charge level of $2,5 U_N$. For special applications, where inrush currents and/or peak voltages are limited, lower discharge requirements are applicable.

4.2.3 Disconnecting capability

Requirements and test procedures are given in IEC 60871-4. These tests verify that the fuse has a current-limiting action.

4.2.4 Voltage withstand capability after operation

Requirements and test procedures are given in IEC 60871-4.

4.3 Influence of capacitor element configuration on capacitor life

4.3.1 Capacitor with all elements connected in parallel

After the breakdown of an element, the respective fuse will melt in less than a millisecond owing to the discharge current from the parallel connected elements and capacitors and the power frequency current from the supply. The capacitor may, however, continue operating with a correspondingly reduced output.

If the capacitor is operated at a fixed bus voltage, no variation in operating voltage on the remaining healthy elements will occur.

4.3.2 Capacitor with elements connected in series and parallel

After the breakdown of an element, all parallel connected elements discharge their stored energy or part of it into the faulty element. The power frequency current is limited by the remaining healthy elements connected in series.

After the disconnection of the faulty element, the capacitor continues operating with a correspondingly reduced output. The remaining healthy elements of the group are then stressed with a voltage approximately $m \times n / [m(n - 1) + 1]$ times the initial voltage, where n is the number of parallel connected elements per group and m the number of series-connected sections per unit. In certain cases the voltage may be higher, for example due to neutral shift with an ungrounded star configuration.

5 External fuses

5.1 General

External fuses for shunt capacitors are defined in IEC 60549 as intended to clear faults inside a capacitor unit and to permit continued operation of the remaining parts of the bank in which the unit is connected. They will also clear an external capacitor bushing flashover.