PD IEC/TS 62600-201:2015

BSI Standards Publication

Marine energy — Wave, tidal and other water current converters

Part 201: Tidal energy resource assessment and characterization

bsi.

...making excellence a habit.™

Document Sharing Hub

Full document details: PD IEC/TS 62600-201:2015

National foreword

This Published Document is the UK implementation of IEC/TS 62600-201: 2015.

The UK participation in its preparation was entrusted to Technical Committee PEL/114, Marine energy — Wave, tidal and other water current converters.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.
Published by BSI Standards Limited 2015

ISBN 978 0 580 79776 7
ICS 27.140

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 August 2015.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD IEC/TS 62600-201:2015

IEC TS 62600-201

Edition 1.0 2015-04

TECHNICAL SPECIFICATION

colour inside

Marine energy – Wave, tidal and other water current converters – Part 201: Tidal energy resource assessment and characterization

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.140

ISBN 978-2-8322-2591-2

Warning! Make sure that you obtained this publication from an authorized distributor.

® Registered trademark of the International Electrotechnical Commission

Documents
Document Sharing Hub

Full document details: PD IEC/TS 62600-201:2015

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Symbols, units and abbreviations 7
4.1 Symbols and units 7
4.2 Abbreviations 8
5 Methodology overview 8
5.1 Project definition 8
5.1.1 General 8
5.1.2 Stage 1: Feasibility study 9
5.1.3 Stage 2: Layout design study 9
5.2 Methodology 9
6 Data collection 12
6.1 Introduction 12
6.2 Bathymetry 12
6.3 Tidal characteristics 13
6.3.1 General 13
6.3.2 Assessment of data quality 13
6.3.3 Tidal height 14
6.3.4 Tidal current mobile survey 14
6.3.5 Tidal current stationary survey 16
6.4 Meteorological data 19
6.4.1 General 19
6.4.2 Wind data 19
6.4.3 Atmospheric pressure 20
6.5 Wave climate 20
6.6 Turbulence 20
6.6.1 General 20
6.6.2 Flow structure / Eddies 20
6.7 Stratification, seawater density and sediment measurement 21
7 Model development and outputs 21
7.1 General 21
7.2 Model coverage, resolution and boundary conditions 21
7.2.1 Bathymetric data 21
7.2.2 Model coverage 22
7.2.3 Model boundary conditions 22
7.2.4 Model resolution 23
7.3 Choice of model (including characteristics) 23
7.3.1 General considerations 23
7.3.2 Model selection 24
7.3.3 Model characteristics 25
7.4 Analysing data to provide model inputs, calibration and validation 25
7.4.1 Bathymetry interpolation 25

AVA Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

7.4.2 Currents ... 25
7.4.3 Meteorological analysis ... 25
7.4.4 Waves ... 26
7.4.5 Turbulence ... 26
7.4.6 Flow Structures / Eddies ... 27
7.4.7 Seawater density, salinity and temperature ... 28
7.4.8 Sediment ... 28
7.5 Model calibration / Validation ... 28
7.5.1 Model calibration ... 28
7.5.2 Model validation ... 29
7.6 Incorporating energy extraction ... 30
7.6.1 General ... 30
7.6.2 Methodology for incorporating energy extraction ... 31
7.6.3 Practical incorporation of energy extraction in modelling ... 32
8 Data analysis and results presentation ... 33
8.1 General model result presentation ... 33
8.2 Generation of annual velocity distribution ... 33
8.2.1 General ... 33
8.2.2 Potential methodologies for simulating “missing” tidal constituents ... 34
8.2.3 Long-term model current predictions (harmonic analysis) ... 34
8.2.4 Results presentation ... 36
8.3 Velocity distribution curves – Joint probability distribution ... 37
9 Reporting of results ... 39
9.1 Purpose of reporting ... 39
9.2 Contents of the report ... 39
Annex A (informative) Calculation of TEC Annual Energy Production ... 40
A.1 General ... 40
A.2 Individual TEC Annual Energy Production (AEP) ... 40
A.3 Array Annual Energy Production ... 41
Annex B (informative) Guidelines for current profiler measurements ... 42
B.1 General ... 42
B.2 Instrument configuration ... 42
B.3 Correcting for clock drift ... 42
B.4 Depth quality control ... 43
B.5 Velocity quality control ... 43
Bibliography ... 44

Figure 1 – The effect of predicting tides with various constituents from Cook Inlet, Alaska ... 36
Figure 2 – Joint velocity and direction probability distribution, a location in Cook Inlet, Alaska ... 38
Figure 3 – Example exceedance curve for velocity magnitude ... 39

Table 1 – Resource assessment stages ... 9
Table 2 – Model and field survey recommendations (Overview) ... 11

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARINE ENERGY – WAVE, TIDAL AND OTHER WATER CURRENT CONVERTERS –

Part 201: Tidal energy resource assessment and characterization

FOREWORD

1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
6) All users should ensure that they have the latest edition of this publication.
7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62600-201, which is a technical specification, has been prepared by IEC technical committee 114: Marine energy – Wave, tidal and other water current converters.

Documents
Document Sharing Hub

Full document details: PD IEC/TS 62600-201:2015

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
114/142/DTS	114/151A/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62600 series, published under the general title *Marine energy – Wave, tidal and other water current converters*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: PD IEC/TS 62600-201:2015

INTRODUCTION

This Technical Specification is for use by appropriately qualified and competent persons. The development of the tidal power industry is at an early stage and the significance of particular tidal energy resource characteristics is not well understood. This Technical Specification is intended to be updated as understanding of the resource and its response to power extraction becomes better understood. It is noted that it is presently particularly difficult to derive the uncertainty (within specified confidence limits) of the resource, given lack of field and model data for a statistically significant number of sites.

The purpose of this Technical Specification is to provide a uniform methodology that will ensure consistency and accuracy in the estimation, measurement, characterization and analysis of the theoretical tidal current resource at sites that could be suitable for the installation of an array of Tidal Energy Converters (TECs), together with defining a standardised methodology with which this resource can be described and reported. Application of the estimation, measurement and analysis techniques recommended in this Technical Specification will ensure that resource assessment is undertaken in a consistent and accurate manner. This Technical Specification presents techniques that are expected to provide fair and suitably accurate results that can be replicated by others.

The overall goal of the methodology is to enable calculation of the Annual Energy Production (AEP) for the proposed array of TECs at each TEC location in conjunction with IEC 62600-200.

In this Technical Specification, the theoretical tidal energy resource (undisturbed or disturbed by power extraction) is defined as the velocity probability distribution $f(U_i)$. For projects over c. 10 MW (circa 10 MW), the velocity probability distribution is calculated using hydrodynamic models that have been appropriately verified using measured data. The methodology for measuring the required data is also defined. For individual TECs within small projects of less than c. 10 MW, an alternative method which uses measured data at each TEC location may also be used to define the resource.

This Technical Specification describes only the aspects of the resource required to calculate AEP; e.g., it does not describe aspects of the resource required to evaluate design loads or to satisfy environmental regulations. Furthermore, this Technical Specification is not intended to cover every eventuality that may be relevant for any particular project. Therefore, this Technical Specification assumes that the user has access to, and reviews, other relevant IEC documentation before undertaking work (e.g., surveys and modelling) which could also satisfy other requirements.

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

MARINE ENERGY – WAVE, TIDAL AND OTHER WATER CURRENT CONVERTERS –

Part 201: Tidal energy resource assessment and characterization

1 Scope

This part of IEC 62600 establishes a system for analysing and reporting, through estimation or direct measurement, the theoretical tidal current energy resource in oceanic areas including estuaries (to the limit of tidal influence) that may be suitable for the installation of arrays of TECs.

It is intended to be applied at various stages of project lifecycle to provide suitably accurate estimates of the tidal resource to enable the arrays' projected annual energy production to be calculated at each TEC location in conjunction with IEC 62600-200.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61400-12-1, *Wind turbines – Part 12-1: Power performance measurements of electricity producing wind turbines*

IEC TS 62600-1, *Marine energy – Wave, tidal and other water current converters – Part 1: Terminology*

IEC TS 62600-200, *Marine energy – Wave, tidal and other water current converters – Part 200: Electricity producing tidal energy converters – Power performance assessment*

IHO (International Hydrographic Organisation), 2008, *Standards for Hydrographic Surveys. Special Publication No. 44. 5th Edition*

ICES, 2006, *Guidelines for Multibeam Echosounder Data*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC TS 62600-1 apply.

4 Symbols, units and abbreviations

4.1 Symbols and units

$f(U_i)$ Time occurrence likelihood of a velocity in each magnitude bin (%)

$f(U_i, \theta_k)$ Time occurrence likelihood of a velocity in each magnitude and direction bin (%)

I Turbulence intensity

i Index for velocity magnitude bin numbers

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

j Index for number of time intervals

k Index for direction bin numbers

K Turbulent kinetic energy (m^2/s^2)

N Number of time intervals

N_B Number of velocity bins

u' Root-mean-square of the turbulent velocity fluctuations (m/s)

$\overline{U}$ Mean velocity magnitude (m/s)

U_i Central value velocity magnitude in the ith bin (m/s)

U_j Central value velocity magnitude of time step j (m/s)

θ_k Direction for the kth bin (deg)

V_{rmc} Root Mean Cubed Velocity (m/s)

ρ Density of the water (kg/m^3)

4.2 Abbreviations

AEP Annual Energy Production

ADV Acoustic Doppler Velocimeter

APD Average Power Density (kW/m^2)

CTD Conductivity, Temperature, Depth

CFD Computational Fluid Dynamics

EEP Energy Extraction Plane

GPS Global Positioning System

IEC International Electrotechnical Commission

NOAA National Oceanic and Atmospheric Administration

PCA Projected Capture Area

RTK Real Time Kinematics

SAR Synthetic Aperture Radar

TEC Tidal Energy Converter

UTC Coordinated Universal Time

5 Methodology overview

5.1 Project definition

5.1.1 General

This Technical Specification should be applied at various stages of the resource assessment process to provide velocity probability distributions for computing Annual Energy Production (AEP) with increasing accuracy or lower levels of uncertainty. This specification assumes that a region of interest has already been identified. Aspects of the methodology to be followed

AVA Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

when undertaking a tidal resource assessment depend on the scope of the analysis and its objectives. Two distinct types of studies, feasibility and layout design, are defined as indicated in Table 1. The feasibility study generally has a focus on the whole estuary or channel with a medium level of uncertainty. The layout design study is expected to focus on the particular sites chosen through the feasibility studies.

Table 1 – Resource assessment stages

Stage	Aim	Area	Level of uncertainty
Stage 1	Feasibility	Whole estuary, channel, etc.	Medium
Stage 2	Layout design	Development site.	Low

The expected decrease in uncertainty as the resource assessment stages progress can result from:

- measurements and/or modelling over longer durations / periods;
- availability of additional, and/or higher quality measurements;
- use of more capable models, as outlined in 7.3;
- finer discretisation in space and time;
- use of improved boundary conditions;
- improvements in modelling techniques during the project's evolution.

5.1.2 Stage 1: Feasibility study

A Stage 1 study is focused on investigating the scale and attributes of the energy resource within a particular study area. The results of a Stage 1 resource assessment can be used to help assess the feasibility of constructing tidal energy arrays at sites within the study area by estimating the undisturbed site resource.

5.1.3 Stage 2: Layout design study

A Stage 2 study is focused on generating detailed and accurate information on the tidal energy resource in a specific area to determine AEP, through supporting the layout design of a tidal array, and may incorporate energy extraction impacts depending upon the project scale. The Stage 2 study should consider the technology to be installed and locations of TEC deployments in order to estimate AEP with lower uncertainty.

5.2 Methodology

The resource assessment requirements are defined depending on the scale of the project as well as the objective of the assessment (feasibility or design layout). The AEP (calculated using the method outlined in Annex A) may be assessed based on data from either direct measurements or from hydrodynamic modelling.

For projects where the total power output is expected to be less than c. 10 MW, or those where the proposed energy extraction is less than 2 % of the theoretical undisturbed tidal energy resource (see Note) and therefore there is expected to be little if any impact on the underlying hydrodynamics of the site, AEP may be estimated from direct resource measurements using static current profiler measurements and harmonic analysis as defined in 8.2.3. In order to use this method, measurements shall be made at each individual turbine location. Such projects may also use the hydrodynamic modelling required for larger projects. If the data collection indicates that the TECs should be deployed in different locations in

AVA Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

where static current profiler data has been collected, then either additional data gathering at the new location or the modelling approach is required.

NOTE Understanding of the potential impact of energy extraction from TEC arrays is evolving; existing useful references include: Black & Veatch/Carbon Trust (2011); Garrett et al. (2004); Garrett et al. (2005); Sutherland et al. (2007); Polagye et al. (2008); Karsten et al. (2008); Draper et al. (2009); Vennell (2010); Vennell (2011); Polagye et al. (2011), Defne et al. (2011), Walters et al (2013).

For projects larger than c. 10 MW or 2 % of the theoretical undisturbed resource, AEP shall be assessed by hydrodynamic modelling, with appropriate verification by measurements. The first step in this process is to define the required model inputs, as described in 7.2. Subclause 7.3 describes the choice of numerical model. The next step is to assemble the information required to implement the model. If sufficient data does not exist for the model inputs, additional data shall be collected as described in Clause 6. The accuracy of the model may then be assessed as per 7.4. For feasibility studies, the model output may be used to produce the velocity probability distribution for AEP calculation. For layout design studies, if the level of energy extraction is to be small relative to the existing resource (see 7.6), the model data may be used directly. Otherwise, the model should be run with energy extraction to accurately specify velocity probability distributions for AEP estimation.

Many of the external constraints that determine the assessment of the practical resource, such as acceptable environmental impacts, are beyond the scope of this Technical Specification. However, the modelling methodologies described within this Technical Specification may be used to assess some of the impacts of TEC deployments, including changes in tidal regime, tidal currents and bottom sediment movements, and may also provide data required for environmental studies. External constraints to be considered in determining the tidal resource should be determined in consultation with the appropriate regulators.

Table 2 should be used to help determine the appropriate model and survey requirements to estimate the tidal energy resource at any particular resource assessment Stage. Where appropriate, Table 2 references the relevant clause in this Technical Specification where the detailed information related to that activity is contained. These recommendations consider the practicalities of gathering the data to satisfy these requirements.

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

Table 2 – Model and field survey recommendations (Overview)

		Stage 1	Stage 2
Modelling	Minimum number of harmonic constituents for modelling driving boundary (tidal amplitude)	4-8	8-12
	Grid resolution at the area(s) of interest	< 500 m or	< 50 m
		> 10 grid cells across a channel section	
	Period of run	> 35 days	> 35 days
	Other model characteristics	7.2 and 7.3	Shall include energy extraction impacts as needed 7.6
Physical data requirement	Bathymetry	6.2	6.2
	Tidal height	6.3.3	6.3.3
	Wave characteristics	6.5	6.5
	Meteorological data	6.4	6.4
	Flow structure / Eddies / Turbulence	6.6	6.6
	Stratification, seawater density and sediment measurement	6.7	6.7
	Tidal currents – Mobile survey	6.3.4	6.3.4
	Tidal currents – Stationary survey	6.3.5	6.3.5
Data analysis	Harmonic analysis on available current data (minimum no. of constituents)	20	20

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

6 Data collection

6.1 Introduction

For projects using hydrodynamic models for providing velocity distributions to support AEP calculations, field measurements are required to calibrate and validate numerical models of the tidal currents. This includes measurements of harmonic tidal currents, as well as non-tidal low frequency processes that may impact tidal resource assessment such as storm surge, residual flows and stratification, and high frequency processes such as turbulence. For projects smaller than c. 10 MW, the field measurements may be used to provide the velocity distributions to directly calculate AEP for individual turbines. Guidelines for current profiler measurements are provided in Annex B.

6.2 Bathymetry

The required resolution of the bathymetry data to feed into a hydrodynamic model is described in 7.2.1.

The bathymetric data already available shall be reviewed, e.g. contact with the oceanographic centres responsible for the region concerned is recommended. If existing data is to be used, then the collection techniques for the original data and their appropriateness shall be reviewed, e.g. by comparison to modern techniques. Such data should be used with an element of caution. If a bathymetric survey is required to complement and expand the available existing data in the specific region of interest, the survey should be conducted in accordance with the IHO *Standards for Hydrographic Surveys:*2008. Reporting of bathymetric survey activities shall be completed to the standard of the ICES *Guidelines for Multibeam Echosounder Data:*2006.

A map should be provided for all undertaken surveys for which data is available. The following information should be provided on each survey:

- date of survey;
- survey methods used;
- uncertainty of data;
- coordinate system and transformation used to convert to/from another coordinate system, as appropriate, for later use;
- method for accounting for stage of tide throughout survey and tidal reference (measurement or prediction) used;
- chart/tidal datum applied;
- calibrations applied;
- availability of data in electronic form.

There is no accepted world standard definition of tidal datum or chart datum used for navigation charts and tidal height graphs. Many nations have developed their own definitions. It is particularly important for numerical modelling purposes to have bathymetric depths referenced to a fixed geodetically determined datum, which can be referenced to true local mean sea level. Tidal or chart datum used on all worldwide navigation charts is not a fixed datum but may change from chart to chart and should be defined.

If new survey data is used in conjunction with existing data, the new data should overlap the existing data to allow for validation between the two datasets.

Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015

6.3 Tidal characteristics

6.3.1 General

The tidal height and tidal current (both depth-averaged and depth varying) characteristics at the site shall be identified and reported. As a minimum this should include graphs of typical daily, monthly and annual tidal height, current speed and direction. These graphs may be generated directly from measured data or predictions may be calculated from tidal harmonic constituents derived from measured data using harmonic analysis software, according to the Stage of the investigation.

The usage of 'typical' is intended to convey the general conditions to be expected on site, for example a 'typical' daily cycle for a semi-diurnal or diurnal site will show the repetition in the expected pattern of high and low tides. A 'typical' daily cycle for a site with mixed tides may require several daily graphs to capture clearly the lower high water and higher low water cycles. A 'typical' monthly cycle should be selected for a 29 day period when solar semi-annual and annual constituents have minimal influence. A 'typical' annual cycle should be presented in the context of the longer term 18,6 year lunar-solar cycle.

Existing long-term data sets and tidal constituent data maintained by the national hydrographic office or oceanographic data centre responsible for the region should be accessed where available. Tidal characteristics from all tidal height stations and tidal current stations in the area of interest shall be determined. Further tidal height data including tidal constituents may also be obtained from appropriate satellite databases. If additional location specific tidal height data is required, an appropriate survey should be conducted (see 6.3.3). These approaches to obtaining data require use of appropriate methodologies, and an appropriate assessment of the uncertainty in the data should be reported.

NOTE 1 A standard text on the theory of tides and tidal currents, including what constitutes a typical spring tidal cycle, and tidal harmonic analyses and prediction may be consulted before any substantive work is completed on this tidal resource analysis. Several good references are freely available including the straightforward Forrester (1983), and the more mathematically complex Foreman (2004). The latter manual includes freely available tidal height and current prediction and analysis software. Alternative analysis and prediction software is available, e.g. T-Tide, (Pawlowicz et al., 2002)
(http://www.eos.ubc.ca/~rich/) or UTide (Codiga 2011).

NOTE 2 Tidal height and tidal current constituent data can be obtained from a number of sources. These are freely available in the USA and many other localities but some countries, including the UK, protect the raw constituent data and only make them available for a fee.

NOTE 3 Examples of appropriate satellite databases include TOPEX/POSEIDON, and ERS-1. For those unfamiliar with satellite imagery the following references may be useful: http://sealevel.jpl.nasa.gov, http://podaac.jpl.nasa.gov/OceanSurfaceTopography.

NOTE 4 Preliminary tidal characteristics such as the spatial structure of persistent tidal eddies may be evaluated for a project site through the use of surface drifters.

6.3.2 Assessment of data quality

Ideally, an overall assessment of tidal current data quality would be conducted according to the standardised approach presented in ISO/IEC Guide 98-3:2008. However, application of this method to current profiler non-steady (turbulent) flow data is itself subject to debate. Current profiler manufacturers can prescribe a given uncertainty in measurement for the selected instrument configuration, but this value is applicable only for homogeneous flow across layers of constant depth. Hence, this prescribed uncertainty value does not account for the error caused when separate beams detect spatially varying flow, yet transform the data into a velocity vector at a single point. The ISO/IEC Guide 98-3 provides a method for characterizing measurement uncertainty using the standard deviation of multiple measurements. However, this method relies upon the measurement of fluctuations from an observed steady mean value. At many sites, the approximately 12 h period of the tidal cycle, in combination with large-scale eddies with time scales of just a few minutes and small-scale turbulence with timescales of a few seconds, precludes an averaging period over which the underlying velocity can be considered a truly steady value. Thus it is generally not possible to rigorously conduct propagation of uncertainty for values dependent on the tidal velocities

AVA Documents
Document Sharing Hub
Full document details: PD IEC/TS 62600-201:2015