PD ISO/IEC TR 11801-9906:2020

BSI Standards Publication

Information technology — Generic cabling for customer premises

Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

National foreword

This Published Document is the UK implementation of ISO/IEC TR 11801-9906:2020.

The UK participation in its preparation was entrusted to Technical Committee TCT/7, Telecommunications - Installation requirements.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 539 13086 7

ICS 35.200

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 29 February 2020.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

ISO/IEC TR 11801-9906

Edition 1.0 2020-02

TECHNICAL REPORT

Information technology – Generic cabling for customer premises – Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-7843-7

Warning! Make sure that you obtained this publication from an authorized distributor.

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

CONTENTS

FOREWORD 6
INTRODUCTION 8
1 Scope 9
2 Normative references 9
3 Terms, definitions and symbols 9
3.1 Terms and definitions 9
3.2 Symbols 10
4 Balanced 1-pair cabling channels 10
4.1 General 10
4.2 Component specifications 11
4.3 Environmental classifications 11
4.4 Channel reference implementations 12
4.5 Balanced 1-pair cabling channel signal transmission specifications 12
4.5.1 Return loss (RL) 12
4.5.2 Insertion loss (IL) 12
4.5.3 Unbalance attenuation and coupling attenuation 13
4.5.4 Alien (exogenous) crosstalk 15
4.5.5 DC loop resistance 16
4.5.6 Propagation delay 16
Annex A (informative) Balanced 1-pair cable specifications 17
A.1 General 17
A.2 Cables using alternative conductor sizes 17
A.3 Balanced 1-pair cable specifications 17
A.3.1 Return loss (RL) 17
A.3.2 Insertion loss (IL) 18
A.3.3 Unbalance attenuation and coupling attenuation 18
A.3.4 Alien (exogenous) crosstalk 20
A.3.5 DC resistance 21
A.3.6 Propagation delay 21
Annex B (informative) Balanced 1-pair connector specifications 22
B.1 General 22
B.2 Balanced 1-pair connector specifications 22
B.2.1 Return loss (RL) 22
B.2.2 Insertion loss (IL) 22
B.2.3 Unbalance attenuation and coupling attenuation 23
B.2.4 Alien (exogenous) crosstalk 24
B.2.5 DC resistance (DCR) 25
B.2.6 Propagation delay (delay) 25
Annex C (informative) Link segment specifications 26
C.1 General 26
C.2 Return loss (RL) 26
C.2.1 1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4 26
C.2.2 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 26
C.2.3 10BASE-T1S, IEEE 802.3cg 26
C.2.4 10BASE-T1L, IEEE 802.3cg 27

Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020

C.3 Insertion loss (IL) ... 27
C.3.1 1000BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 27
C.3.2 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 ... 27
C.4 TCL - 10BASE-T1L, IEEE 802.3cg ... 28
C.5 ELTCTL - 10BASE-T1L, IEEE 802.3cg ... 29
C.6 PS ANEXT ... 29
C.6.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 29
C.6.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 29
C.6.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 ... 29
C.6.4 10BASE-T1S, IEEE 802.3cg ... 30
C.6.5 10BASE-T1L, IEEE 802.3cg ... 30
C.7 PS AACR-F ... 30
C.7.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 30
C.7.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 30
C.7.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 ... 31
C.7.4 10BASE-T1S, IEEE 802.3cg ... 31
C.7.5 10BASE-T1L, IEEE 802.3cg ... 31
C.8 Coupling attenuation ... 31
C.8.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 31
C.8.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 32
C.8.3 100BASE-T1, ISO/IEC/IEEE 8802-3:2017/AMD1 ... 32
C.8.4 10BASE-T1S, IEEE 802.3cg ... 32
C.8.5 10BASE-T1L, IEEE 802.3cg ... 32
C.9 Delay ... 33
C.9.1 1000BASE-T1, Type A, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 33
C.9.2 1000BASE-T1, Type B, ISO/IEC/IEEE 8802-3:2017/AMD4 ... 33
C.9.3 10BASE-T1L, IEEE 802.3cg ... 33
Annex D (informative) Considerations for balanced 1-pair channels bundled in a 4-pair cabling channel ... 34
Annex E (informative) Conductor size effects for reduced insertion loss ... 35
E.1 Channel parameters affected by conductor size and AWG ... 35
E.2 IL parameter variation due to conductor size variation ... 36
E.3 AWG ... 36
Bibliography ... 37

Table 1 – SPE signal transmission functional space ... 11
Table 2 – Balanced 1-pair cabling channel return loss (RL) ... 12
Table 3 – Balanced 1-pair cabling channel IL ... 13
Table 4 – Balanced 1-pair cabling channel TCL ... 14
Table 5 – Balanced 1-pair cabling channel ELTCTL ... 14
Table 6 – Balanced 1-pair cabling channel coupling attenuation ... 15
Table 7 – Balanced 1-pair cabling channel PS ANEXT ... 15
Table 8 – Balanced 1-pair cabling channel PS AACR-F ... 16
Table 9 – Balanced 1-pair cabling channel DC loop resistance ... 16
Table 10 – Balanced 1-pair cabling channel propagation delay ... 16
Table A.1 – Balanced 1-pair cable standards ... 17
Table A.2 – Balanced 1-pair cable RL ... 18
AVA Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020

Table A.3 – Balanced 1-pair cable IL 18
Table A.4 – Balanced 1-pair cable TCL 19
Table A.5 – Balanced 1-pair cable ELTCTL 19
Table A.6 – Balanced 1-pair cable coupling attenuation 20
Table A.7 – Balanced 1-pair cable PS ANEXT 20
Table A.8 – Balanced 1-pair cable PS AACR-F 21
Table A.9 – Balanced 1-pair cable DC resistance 21
Table A.10 – Balanced 1-pair cable propagation delay 21
Table B.1 – Balanced 1-pair connector standards 22
Table B.2 – Balanced 1-pair connector RL 22
Table B.3 – Balanced 1-pair connector IL 23
Table B.4 – Balanced 1-pair connector TCL 23
Table B.5 – Balanced 1-pair connector TCTL 23
Table B.6 – Balanced 1-pair connector coupling attenuation 24
Table B.7 – Balanced 1-pair connector PS ANEXT 24
Table B.8 – Balanced 1-pair connector PS AACR-F 24
Table B.9 – Balanced 1-pair connector DCR 25
Table B.10 – Balanced 1-pair connector delay 25
Table C.1 – Return loss limits for 15 m and 40 m link segment 26
Table C.2 – Return loss limits for 15 m link segment 26
Table C.3 – Return loss limits for 15 m link segment 26
Table C.4 – Return loss limits for 1 000 m link segment 27
Table C.5 – Insertion loss limits of a 15 m and 40 m link segment 27
Table C.6 – Insertion loss limits for a 15 m link segment 27
Table C.7 – Insertion loss limits for a 15 m link segment 28
Table C.8 – Insertion loss limits for a 1 000 m link segment 28
Table C.9 – TCL for a 1 000 m link segment 28
Table C.10 – ELTCTL for a 1 000 m link segment 29
Table C.11 – PS ANEXT for a 15 m link segment 29
Table C.12 – PS ANEXT for a 40 m link segment 29
Table C.13 – PS ANEXT for a 15 m link segment 29
Table C.14 – PS ANEXT for a 15 m link segment 30
Table C.15 – PS ANEXT for a 1 000 m link segment 30
Table C.16 – PS AACR-F for a 15 m link segment 30
Table C.17 – PS AACR-F for a 40 m link segment 30
Table C.18 – PS AACR-F for a 15 m link segment 31
Table C.19 – PS AACR-F for a 15 m link segment 31
Table C.20 – PS AACR-F for a 1 000 m link segment 31
Table C.21 – Coupling attenuation for a 15 m link segment 31
Table C.22 – Coupling attenuation for a 40 m link segment 32
Table C.23 – Coupling attenuation for a 15 m link segment 32
Table C.24 – Coupling attenuation for a 15 m link segment 32
Table C.25 – Coupling attenuation for a 1 000 m link segment 32
AVA Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020

Table C.26 – Delay for a 15 m link segment 33
Table C.27 – Delay for a 40 m link segment 33
Table C.28 – Delay for a 1 000 m link segment 33
Table E.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient 35

Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020

© ISO/IEC 2020

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906 – Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

FOREWORD

1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.

3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.

5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.

8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC and ISO technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 11801-9906, which is a Technical Report, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology – Generic cabling for customer premises*, can be found on the IEC and ISO websites.

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

© ISO/IEC 2020

The text of this Technical Report is based on the following documents:

Draft TR	Report on voting
JTC1-SC25/2888/DTR	JTC1-SC25/2913/RVDTR

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

INTRODUCTION

This document is a compendium of balanced 1-pair cabling channels specifications related to specific applications.

The balanced 1-pair cabling channels support single-pair Ethernet (SPE) applications, according to ISO/IEC/IEEE 8802-3:2017/AMD4, 1000BASE-T1; ISO/IEC/IEEE 8802-3:2017/AMD1, 100BASE-T1; and IEEE 802.3cg, 10BASE-T1.

While the original use case for SPE was automotive applications, this document describes balanced 1-pair cabling channels intended for use in non-automotive, SPE applications – for example:

- industrial automation applications, Industrial Internet of Things (IIoT), Industry 4.0;
- enterprise building applications, Internet of Things (IoT), smart lighting, energy management, and access control;
- other IoT applications, smart building and home automation applications.

SPE cabling channels support bidirectional signal transmission, using one balanced pair, for 1 000 Mbit/s (ISO/IEC/IEEE 8802-3:2017/AMD4) up to 40 m, 100 Mbit/s (ISO/IEC/IEEE 8802-3:2017/AMD1) up to 15 m, or 10 Mbit/s (IEEE 802.3cg) up to 1 000 m, where reach is influenced by cabling channel capacity limitations from signal loss and electromagnetic interference.

SPE channels optionally support power delivery together with the signal delivery over a single balanced pair. Remote powering over balanced 1-pair cabling is addressed in ISO/IEC TS 29125:2017/AMD1[1].

[1] To be published. Stage at the time of publication: ISO/IEC DTS 29125:2017/AMD1:2019.

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

© ISO/IEC 2020

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906 – Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

1 Scope

This document covers channel specifications, for channels constructed from balanced 1-pair cabling components, primarily intended for use in industrial automation and process control applications.

The channel specifications are consistent with corresponding IEEE 802.3 single-pair Ethernet (SPE) applications and are referenced from link segment specifications in the following IEEE SPE physical layer specifications:

- ISO/IEC/IEEE 8802-3:2017/AMD4, 1 000 Mb/s: 1000BASE-T1 Type A, ≤ 15 m, 1000BASE-T1 Type B, ≤ 40 m;
- ISO/IEC/IEEE 8802-3:2017/AMD1, 100 Mb/s: 100BASE-T1, ≤ 15 m;
- IEEE 802.3cg, 10 Mb/s: 10BASE-T1S, ≤ 15 m; 10BASE-T1L, ≤ 1 000 m.

The channel component specifications are referenced according to corresponding IEC balanced 1-pair cable and connector specifications.

Channel specifications include IL, RL, TCL, coupling attenuation, and alien crosstalk parameters specifications.

Channel EMC related specifications include electromagnetic isolation levels E_1, E_2 and E_3, which are defined according to the MICE standard environmental characterization system specified in ISO/IEC 11801-1.

2 Normative references

ISO/IEC 11801-1, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11801-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

Documents
Document Sharing Hub

Full document details: PD ISO/IEC TR 11801-9906:2020

3.1.1
balanced 1-pair cabling channel
cabling channel constructed from balanced 1-pair cables, balanced 1-pair connectors and balanced 1-pair cord to form a cabling channel intended for use in differential-mode signal transmission and power delivery applications

3.1.2
balanced 1-pair cable
cable consisting of a single pair of conductors, optional screen, and overall jacket, primarily intended for use in differential-mode signal transmission and power delivery applications

3.1.3
balanced 1-pair connector
connector intended for use with balanced 1-pair cable in differential-mode signal transmission and power delivery applications

3.1.4
balanced 1-pair cord
cable assembly constructed from a 1-pair cable and 1-pair connectors

3.2 Symbols

V_{pp} peak-to-peak voltage

4 Balanced 1-pair cabling channels

4.1 General

Channel signal transmission specifications for balanced 1-pair cabling are referenced from three physical layer specifications: ISO/IEC/IEEE 8802-3:2017/AMD1, ISO/IEC/IEEE 8802-3:2017/AMD4 and IEEE802.3cg. These cover five link segment specifications: 1000BASE-T1 Type A, 1000BASE-T1 Type B, 100BASE-T1, 10BASE-T1S, and 10BASE-T1L. IEEE SPE link segment specifications and physical layer standards are summarized in Annex C.

The SPE link segment specifications are identified by their corresponding upper frequency specification, i.e. 600 MHz, 66 MHz, and 20 MHz.

The SPE signal transmission functional space covered by the five link segment specifications is given in Table 1.

Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020

Table 1 – SPE signal transmission functional space

Upper frequency	Frequency range	Reach	Screen	Data rate	SPE link segment	IEEE physical layer
MHz	MHz	m	**Type**	Mb/s	**Specification**	**Standard**
600	$1 \leq f \leq 600$	15	Screened and unscreened	1 000	1000BASE-T1 Type A	ISO/IEC/IEEE 8802-3:2017/ AMD4
600	$1 \leq f \leq 600$	40	Screened	1 000	1000BASE-T1 Type B	ISO/IEC/IEEE 8802-3:2017/ AMD4
66	$0,3 \leq f \leq 66$	15	Unscreened	100	100BASE-T1	ISO/IEC/IEEE 8802-3:2017/ AMD1
20	$0,1 \leq f \leq 20$	15	Screened and unscreened	10	10BASE-T1S	802.3cg
20	$0,1 \leq f \leq 20$	1 000	Screened and unscreened	10	10BASE-T1L	802.3cg

NOTE Limits involving more than 1 pair within a channel; the following parameters are not applicable to balanced 1-pair cabling channels: NEXT, PS NEXT, ACR-F, PS ACR-F, ACR-N, PS ACR-N, delay skew and pair-to-pair resistance unbalance.

4.2 Component specifications

Balanced 1-pair cabling channel characteristics are specified using balanced 1-pair cabling component specifications. Balanced 1-pair cable and connector component specification references are given in Annex A and Annex B, respectively.

The characteristics of a channel are specified between connections to active equipment. The channel comprises only passive sections of cable, connecting hardware and cords. The connections at the hardware interface to active equipment are not taken into account.

Application support depends on channel performance, which in turn depends on cable length, number of connections, connector termination practices, workmanship and performance. It is possible to achieve equivalent channel performance over greater lengths by the use of fewer connections or by using components with higher performance.

Considerations for balanced 1-pair channels bundled in a 4-pair cabling channel are given in Annex D.

4.3 Environmental classifications

ISO/IEC 11801-1 classifies the environments for generic cabling according to three "MICE" levels.

The balanced 1-pair cabling specifications referenced in ISO/IEC/IEEE 8802-3:2017/AMD1, ISO/IEC/IEEE 8802-3:2017/AMD4 and IEEE 802.3cg include channel EMC related specifications for electromagnetic isolation levels E_1, E_2 and E_3, which are defined according to the MICE standard environmental characterization system specified in ISO/IEC 11801-1.

The channel EMC related specifications are unbalance attenuation, coupling attenuation, and alien (exogenous) crosstalk, which are specified for channels and components per E_1, E_2 and E_3.

Documents
Document Sharing Hub
Full document details: PD ISO/IEC TR 11801-9906:2020