



BSI Standards Publication

Information technology — Generic cabling for customer premises

Part 9906: Balanced single-pair cabling channels up to 600 MHz for single-pair Ethernet (SPE)

National foreword

This Published Document is the UK implementation of ISO/IEC TR 11801-9906:2025. It supersedes PD ISO/IEC TR 11801-9906:2020, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee TCT/7/2, Telecommunications; Installation requirements: Cabling installation and UK implementation.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2025
Published by BSI Standards Limited 2025

ISBN 978 0 539 35231 3

ICS 35.200

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 January 2025.

Amendments/corrigenda issued since publication

Date	Text affected
<hr/>	



TECHNICAL REPORT

**Information technology – Generic cabling for customer premises –
Part 9906: Balanced single-pair cabling channels up to 600 MHz for single-pair
Ethernet (SPE)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8327-0142-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and symbols.....	8
3.1 Terms and definitions.....	8
3.2 Symbols.....	8
4 Single-pair Ethernet (SPE) link segment specifications.....	8
4.1 General.....	8
4.2 Link segment specifications	8
4.3 Environmental classifications	9
4.4 SPE link segment signal transmission specifications.....	9
4.4.1 SPE link segment return loss (RL)	9
4.4.2 SPE link segment insertion loss (IL)	10
4.4.3 SPE link segment unbalance attenuation and coupling attenuation	11
4.4.4 SPE link segment alien (exogenous) crosstalk	14
4.4.5 SPE link segment DC loop resistance	16
4.4.6 SPE link segment propagation delay.....	16
5 Balanced single-pair cabling channels	16
5.1 General.....	16
5.2 Component specifications	17
5.3 Environmental classifications	17
5.4 Channel reference implementations	17
Annex A (informative) Balanced single-pair cable specifications	18
A.1 General.....	18
A.2 Cables using alternative conductor sizes	18
A.3 Balanced single-pair cable specifications.....	19
A.3.1 Return loss (RL)	19
A.3.2 Insertion loss (IL).....	19
A.3.3 Unbalance attenuation and coupling attenuation	20
A.3.4 Alien (exogenous) crosstalk.....	22
A.3.5 DC resistance.....	24
A.3.6 Propagation delay.....	24
Annex B (informative) Balanced single-pair connector specifications	25
Annex C (informative) Conductor size effects for reduced insertion loss	26
C.1 Channel parameters affected by conductor size and AWG	26
C.2 IL parameter variation due to conductor size variation	27
C.3 AWG.....	27
Bibliography.....	28
Table 1 – SPE link segment characteristics.....	9
Table 2 – SPE link segment return loss (RL).....	10
Table 3 – SPE link segment IL	11
Table 4 – SPE link segment TCL	12
Table 5 – SPE link segment ELTCTL	13

Table 6 – SPE link segment coupling attenuation.....	14
Table 7 – SPE link segment PS ANEXT	15
Table 8 – SPE link segment PS AACR-F.....	15
Table 9 – SPE link segment DC loop resistance.....	16
Table 10 – SPE link segment propagation delay	16
Table 11 – Balanced single-pair cabling channels	17
Table A.1 – Balanced single-pair cable standards	18
Table A.2 – Balanced single-pair cable RL.....	19
Table A.3 – Balanced single-pair cable IL	19
Table A.4 – Balanced single-pair cable TCL.....	20
Table A.5 – Balanced single-pair cable ELTCTL	21
Table A.6 – Balanced single-pair cable coupling attenuation and low-frequency coupling attenuation.....	22
Table A.7 – Balanced single-pair cable PS ANEXT	23
Table A.8 – Balanced single-pair cable PS AACR-F.....	23
Table A.9 – Balanced single-pair cable DC resistance	24
Table A.10 – Balanced single-pair cable propagation delay	24
Table B.1 – Balanced single-pair connector standards	25
Table C.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient	26

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906: Balanced single-pair cabling channels up to 600 MHz for single-pair Ethernet (SPE)

FOREWORD

- 1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO National bodies.
- 3) IEC and ISO documents have the form of recommendations for international use and are accepted by IEC and ISO National bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC and ISO documents is accurate, IEC and ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC and ISO National bodies undertake to apply IEC and ISO documents transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC and ISO document and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC and ISO do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC and ISO marks of conformity. IEC and ISO are not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this document.
- 7) No liability shall attach to IEC and ISO or their directors, employees, servants or agents including individual experts and members of its technical committees and IEC and ISO National bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this ISO/IEC document or any other IEC and ISO documents.
- 8) Attention is drawn to the Normative references cited in this document. Use of the referenced publications is indispensable for the correct application of this document.
- 9) IEC and ISO draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC and ISO take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC and ISO had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch> and www.iso.org/patents. IEC and ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TR 11801-9906 has been prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology. It is a Technical Report.

This second edition cancels and replaces the first edition published in 2020. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the addition of ISO/IEC/IEEE 8802-3, 100BASE T1L, long reach;
- b) complete rearrangement of the information contained in Clause 4, Clause 5, Annex A, Annex B, and Annex C.

The text of this Technical Report is based on the following documents:

Draft	Report on voting
JTC1-SC25/3279/DTR	JTC1-SC25/3293/RVDTR

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Report is English.

The list of all currently available parts of the ISO/IEC 11801 series, under the general title *Information technology – Generic cabling for customer premises*, can be found on the IEC and ISO websites.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1, and the ISO/IEC Directives, JTC 1 Supplement available at www.iec.ch/members_experts/refdocs and www.iso.org/directives.

INTRODUCTION

This document is a compendium of balanced single-pair cabling channel specifications, which support application-specific use in the link-segments specified in ISO/IEC/IEEE 8802-3 single-pair Ethernet (SPE) physical interface (PHY) standards.

The balanced single-pair cabling channels support SPE PHYs as specified in ISO/IEC/IEEE 8802-3, including 1000BASE-T1 Type B, 1000BASE-T1 Type A, 100BASE-T1L, 100BASE-T1, 10BASE-T1L, and 10BASE-T1S.

NOTE At the time of publication, 100BASE-T1L is unpublished.

While the original use case for SPE was automotive applications, this document describes balanced single-pair cabling channels intended for use in non-automotive, SPE applications, for example:

- 1) industrial automation applications, Industrial Internet of Things (IIoT), Industry 4.0;
- 2) enterprise building applications, Internet of Things (IoT), smart lighting, energy management, and access control;
- 3) other IoT applications, smart building, and home automation applications.

SPE cabling channels support bidirectional signal transmission, using one balanced pair, for 1 000 Mbit/s up to 40 m, 100 Mbit/s up to 500 m, or 10 Mbit/s up to 1 000 m, where reach is influenced by cabling channel capacity limitations from signal loss.

INFORMATION TECHNOLOGY – GENERIC CABLING FOR CUSTOMER PREMISES –

Part 9906: Balanced single-pair cabling channels up to 600 MHz for single-pair Ethernet (SPE)

1 Scope

This document covers cabling channel specifications, for cabling channels constructed from balanced single-pair cabling components, intended for use in:

- 1) industrial automation applications, Industrial Internet of Things (IIoT), Industry 4.0;
- 2) enterprise building applications, Internet of Things (IoT), smart lighting, energy management, and access control;
- 3) other IoT applications, smart building, and home automation applications.

The cabling channel specifications are intended to support ISO/IEC/IEEE 8802-3 single-pair Ethernet (SPE) link segment specifications in the following SPE physical layer specifications (PHYs):

- a) 1000BASE-T1 Type B, with reach up to 40 m;
- b) 1000BASE-T1 Type A, with reach up to 15 m;
- c) 100BASE-T1L, with reach up to 500 m;
- d) 100BASE-T1, with reach up to 15 m;
- e) 10BASE-T1L, with reach up to 1000 m;
- f) 10BASE-T1S, with reach up to 15 m.

NOTE At the time of publication, 100BASE-T1L is unpublished.

The channel component specifications are referenced according to corresponding IEC balanced single-pair cable and connector specifications.

Channel specifications include IL, RL, TCL, coupling attenuation, and alien crosstalk parameters specifications.

The channel EMC related specifications are referenced according to the MICE standard environmental characterization systems specified in ISO/IEC 11801-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 11801-1, *Information technology – Generic cabling for customer premises – Part 1: General requirements*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 11801-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

balanced single-pair cabling channel

cabling channel constructed from balanced single-pair cables, balanced single-pair connectors and balanced single-pair cords to form a cabling channel intended for use in differential-mode signal transmission and power delivery applications

3.1.2

balanced single-pair cable

cable consisting of a single pair of conductors, optional screen, and overall jacket, primarily intended for use in differential-mode signal transmission and power delivery applications

3.1.3

balanced single-pair connector

connector intended for use with balanced single-pair cable in differential-mode signal transmission and power delivery applications

3.1.4

balanced single-pair cord

cable assembly constructed from a single-pair cable and single-pair connectors

3.2 Symbols

V_{pp} peak-to-peak voltage

4 Single-pair Ethernet (SPE) link segment specifications

4.1 General

The cabling channel specifications are intended to support ISO/IEC/IEEE 8802-3 single-pair Ethernet (SPE) link segment specifications in the SPE physical layer specifications (PHYs) listed in Clause 1.

The information provided in this Clause 4 on single-pair cabling is from ISO/IEC/IEEE 8802-3, which gives additional information.

4.2 Link segment specifications

ISO/IEC/IEEE 8802-3 single-pair Ethernet (SPE) link segment characteristics are summarized in Table 1.