PD ISO/PAS 20065:2016

BSI Standards Publication

Acoustics — Objective method for assessing the audibility of tones in noise — Engineering method

Documents
Document Sharing Hub

Full document details: PD ISO/PAS 20065:2016

National foreword

This Published Document is the UK implementation of ISO/PAS 20065:2016.

The UK participation in its preparation was entrusted to Technical Committee EH/1, Acoustics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016. Published by BSI Standards Limited 2016

ISBN 978 0 580 93282 3

ICS 17.140.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 July 2016.

Amendments issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD ISO/PAS 20065:2016

PUBLICLY AVAILABLE SPECIFICATION

ISO/PAS 20065

First edition
2016-07-01

Acoustics — Objective method for assessing the audibility of tones in noise — Engineering method

Acoustique — Méthode objective pour évaluer l'audibilité des tons dans le bruit — Méthode d'expertise

Reference number
ISO/PAS 20065:2016(E)

Documents
Document Sharing Hub
© ISO 2016

Full document details: PD ISO/PAS 20065:2016

COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub

Full document details: PD ISO/PAS 20065:2016

Contents

Page

Foreword ... **iv**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Measurement procedure ... **5**
4.1 General ... 5
4.2 Measurement instruments ... 5
4.3 Merging the basic spectra ... 5

5 Evaluation ... **6**
5.1 General information ... 6
5.2 Width Δf_c of the critical band ... 7
5.3 Determination of prominent tones ... 7
5.3.1 General information ... 7
5.3.2 Determination of the mean narrow-band level L_S of the masking noise ... 7
5.3.3 Determination of the tone level L_T of a tone in a critical band ... 8
5.3.4 Distinctness of a tone ... 9
5.3.5 Determination of the critical band level, L_G, of the masking noise ... 10
5.3.6 Masking index ... 10
5.3.7 Determination of the audibility, ΔL ... ***10***
5.3.8 Determination of the decisive audibility, ΔL_j, of a narrow-band spectrum ... 10
5.3.9 Determination of the mean audibility ΔL of a number of spectra ... 12

6 Calculation of the uncertainty of the audibility ΔL ... **13**

7 Recommendations on the presentation of results ... **16**
7.1 Measurement ... 16
7.2 Acoustic environment ... 16
7.3 Instruments for measurement, recording and evaluation ... 16
7.4 Acoustic data ... 16

Annex A (informative) **Window effect and Picket fence effect** ... **17**

Annex B (informative) **Resolving power of the human ear at frequencies below 1 000 Hz and geometric position of the critical bands — corner frequencies** ... **20**

Annex C (informative) **Masking, masking threshold, masking index** ... **22**

Annex D (informative) **Iterative method for the determination of the audibility, ΔL** ... **23**

Annex E (informative) **Example for the determination of the tonal audibility** ... **27**

Bibliography ... **33**

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

Acoustics — Objective method for assessing the audibility of tones in noise — Engineering method

1 Scope

This Publicly Available Specification describes a method for the objective determination of the audibility of tones in environmental noise.

This Publicly Available Specification is intended to augment the usual method for evaluation on the basis of aural impression, in particular, in cases in which there is no agreement on the degree of the audibility of tones. The method described can be used if the frequency of the tone being evaluated is equal to, or greater than, 50 Hz. In other cases, if the tone frequency is below 50 Hz, or if other types of noise (such as screeching) are to be captured, then this method cannot replace subjective evaluation.

The method presented herein can be used in continuous measurement stations that work automatically.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1996-1, *Acoustics — Description, measurement and assessment of environmental noise — Part 1: Basic quantities and assessment procedures*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1996-1 and the following apply.

3.1
tonality
presence of a tone in a noise, the level of which is below that of the remaining noise components in the *critical band* (3.5) about the *tone frequency* (3.2) by less than the value of the *masking index* (3.16), a_V

3.2
tone frequency
f_T
frequency of the *spectral line* (3.23) (or mid-band frequency of the narrow-band filter), to the level of which the tone contributes most strongly

3.3
tone level
L_T
energy summation of the *narrow-band level* (3.22) with the *tone frequency* (3.2), f_T, and the lateral lines about f_T, assignable to this tone

Note 1 to entry: If the *critical band* (3.5) for the frequency, f_T, under consideration contains a number of tones, then the tone level, L_T, is the energy sum of these tones. This level, L_T, is then assigned to the frequency of the participating tone that has the maximal value of *audibility* (3.4), ΔL.

Note 2 to entry: The method for the determination of the tone level, L_T, of a tone in a critical band is described in 5.3.3.

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub

Full document details: PD ISO/PAS 20065:2016

3.4
audibility
ΔL
difference between the *tone level* (3.3), L_T, and the *masking threshold* (3.15), L'_T

Note 1 to entry: The method for the determination of the *decisive audibility* (3.24), ΔL_j, of a *narrow-band spectrum* (3.12) is described in 5.3.8.

3.5
critical band
frequency band with a *bandwidth* (3.17), Δf_c, within which the auditory system integrates the sound intensity in the formation of loudness and within which it integrates the sound intensity in the formation of the *masking threshold* (3.15)

Note 1 to entry: This characteristic of a critical band (see also References [3] and [4]) holds only for a restricted sound level range. This dependence is neglected here.

3.6
mean narrow-band level of the critical band
L_S
energy mean value of all *narrow-band levels* (3.22) in a *critical band* (3.5) that (as a rule) does not exceed this mean value by more than 6 dB

Note 1 to entry: The method for the determination of the mean narrow-band level L_S of the masking noise is described in 5.3.2 and Annex D (iterative method).

3.7
critical band level
L_G
level of noise that is assigned to the *critical band* (3.5) that describes the masking characteristic of the noise for one or more tones of the noise in this critical band

Note 1 to entry: See *narrow-band level* (3.22) and Annex C for masking.

Note 2 to entry: For the definition formula for L_G, see Formula (12).

3.8
sampling frequency
f_S
number of samples taken per second

Note 1 to entry: The analogue data provided continuously are converted into samples through sampling at discrete time intervals for digital processing.

Note 2 to entry: To ensure the reproducibility of a digitized signal, the Shannon theorem requires that the sampling frequency, f_S, is at least 2 times the highest frequency of the signal components used for evaluation in the time signal [$f_S \geq 2\ f_N$, see also *aliasing* (3.9), *antialiasing filter* (3.10) and *useable frequency* (3.20)]. The algorithm of a Fast Fourier Transform analysis (the variant of a discrete Fourier Transform used typically and optimized for calculation) only permits *block lengths* (3.11), N, that correspond to a power of two. FFT analyzers thus need a sampling frequency that is at least 2,56 times the maximum frequency to be analysed.

3.9
aliasing
reflection in the *line spectrum* (3.12) of frequency components from the range above the *sampling frequency* (3.8) divided by two ($f_S/2$) in the range below $f_S/2$

Note 1 to entry: *Antialiasing filters* (3.10) are used to avoid errors through such reflections.

Note 2 to entry: Half the sampling frequency ($f_S/2$) is also known as the Nyquist frequency.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

3.10
antialiasing filter
low-pass filter
ideal filter that allow frequencies below half the *sampling frequency* (3.8) to pass through completely (without influencing the signal), but completely block all higher frequencies

Note 1 to entry: To prevent *aliasing* (3.9), the noise under investigation shall be filtered using an antialiasing filter before analogue-to-digital conversion.

Note 2 to entry: Real aliasing filters have a final damping (generally 120 dB/octave) within the blocking range, i.e. signal components in this transition range are reflected (damped). For example, in the transformation of 2 048 (2 k) data points, 1 024 frequency lines are calculated and 800 lines shown. A component in the line number 1 248 is folded back into the line number 800. With a low-pass filter of 120 dB/octave the damping of these components is approximately 75 dB.

Note 3 to entry: The usual commercial FFT analyzers have an antialiasing filter, the limit frequency of which can be switched automatically with the selectable sampling frequency. The reflection of simulated *narrow-band levels* (3.22) is suppressed.

3.11
block length
N
block of sampling values that in discrete form represents a time-limited range of the time signal to be analysed

Note 1 to entry: In contrast to frequency analysis with analogue and digital filters, the noise with the Fast Fourier Transform is processed in data blocks. In general, these blocks embrace only a part of the noise recording. The block length, *N*, expresses the number of data points processed at the same time. Due to the nature of the Fast Fourier Transform, the value of *N* has the integer of power of 2. It has a value, for example, of $N = 2^{10} = 1\,024$ data points.

3.12
line spectrum
narrow-band spectrum
frequency spectrum
plot of the sound pressure level (*narrow-band level*) (3.22) as a function of the frequency in frequency bands of constant *bandwidth* (3.17) (*line spacing*, Δf) (3.13)

Note 1 to entry: A-weighting of the level is assumed in this Publicly Available Specification.

Note 2 to entry: Frequency analysis delivers a line spectrum, in which each line represents the output of a filter, the mid-frequency of which corresponds to the frequency of the *spectral line* (3.23).

3.13
line spacing
frequency resolution
distance between neighbouring *spectral lines* (3.23), where the line spacing in the FFT is given by

$$\Delta f = f_S / N$$

where

f_S is the *sampling frequency* (3.8);

N is the *block length* (3.11).

Note 1 to entry: In this Publicly Available Specification, the line spacing is $1{,}9\ \text{Hz} \leq \Delta f \leq 4{,}0\ \text{Hz}$.

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

3.14
time window
time data set of the signal segment (*block length*) (3.11) that is multiplied by a weighting function (window function)

Note 1 to entry: In accordance with the definition of the Fourier integral, a prerequisite of the FFT analysis is that the time data set is periodic. If this is not the case (as with stochastic signals), cut-off effects at the edges of the time window will lead to distortion of the spectrum. These distortions are avoided through weighting functions such as the Hanning Function.

Note 2 to entry: For more information on window and weighting functions, see, for example, Reference [5] and Annex A.

3.15
masking threshold
L'_{T}
audibility (3.4) threshold for a specific sound in the presence of a masking sound (masker)

Note 1 to entry: See Annex C for more information on the audibility threshold and the masking noise.

3.16
masking index
a_{v}
difference between the *masking threshold* (3.15), L'_{T}, and the *critical band level* (3.7), L_{G}, of the masking noise

Note 1 to entry: For frequency-dependent masking index, a_{v}, masking and masking noise, see Annex C.

3.17
bandwidth
frequency bandwidth
frequency range of a number of neighbouring *spectral lines* (3.23)

Note 1 to entry: If the width of a frequency band is calculated for which its beginning or end does not correspond to the boundary between two spectral lines, then only the spectral lines that lie in their full width within the calculated frequency range are assigned to the frequency band.

3.18
distinctness
clarity
ratio of the conspicuousness of a tone based on a bandpass noise to the conspicuousness of a sinusoidal tone of the same *tone frequency* (3.2), f_{T}, and same *tone level* (3.3), L_{T}

3.19
edge steepness
ratio of the level difference between the maximum *narrow-band level* (3.22) of a tone, L_{Tmax}, and the narrow-band levels of the first line below/above the tone to the corresponding frequency difference

3.20
useable frequency
f_N
upper limit frequency of the signal components used for evaluation

3.21
investigation range
range within which tones are investigated in the *line spectrum* (3.12)

3.22
narrow-band level
averaged level within a *spectral line* (3.23)

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

3.23
spectral line
frequency band of *bandwidth* (3.17), Δf (*line spacing*) (3.13), in a *line spectrum* (3.12)

3.24
decisive audibility
ΔL_j
maximum *audibility* (3.4), ΔL, in the individual spectrum, j

4 Measurement procedure

4.1 General

The measurement procedure will depend on the aims. The requirements for the measurement and assessment procedure in terms of the choice of measurement point, measurement time and duration of measurement, extraneous noise, etc. shall be satisfied.

The variable for determination of audibility of prominent tones is the sound pressure $p(t)$. For frequency analysis, the A-weighted equivalent continuous sound pressure level, L_{Aeq}, as given in ISO 1996-1, is to be established for the respective spectral lines. If the spectrum is unweighted (linear), then it shall be corrected to A-weighting in accordance with IEC 61672-1.

4.2 Measurement instruments

Sound level meters that meet, or exceed, the requirements of Class 1 in IEC 61672-1 shall be used. These have a frequency weighting “A”/“LIN” or “A”/“Z” with a lower limit frequency equal to, or below, 20 Hz.

Additional instruments such as recording instruments (digital or magnetic tape) may also be used. The measured values derived through recording instruments shall lie within the tolerance range given in IEC 61672-1.

Analysis of frequency components in the measurement signals is performed using a frequency analyzer. The constant line spacing, Δf, shall lie in the range 1,9 Hz to 4 Hz (inclusive). The use of the Hanning window is mandatory in this Publicly Available Specification. For further processing, it shall be ensured that the digitalization of the sound pressure signal across the entire dynamic range used has a resolution of at least 0,1 dB.

Before it is processed further, the analogue measurement signal shall be passed through a steep low-pass filter (antialiasing filter) to avoid errors in frequency analysis. The sampling frequency (see 3.8) shall be at least two times the maximum usable frequency present (see 3.20). The Hanning window is to be used as time window to reduce lateral bands (see 3.14).

4.3 Merging the basic spectra

The spectra for the prominent tone assessment shall have an averaging time of approximately 3 s. Due to the line spacing of 1,9 Hz to 4 Hz (see 4.2) and the typical frequency range, f, of a few kHz, the basic spectra given by the frequency analyzer will have an averaging time below 1 s. To get the averaging time of approximately 3 s, a number of basic spectra shall be merged. This shall be done line by line with Formula (1):

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

$$L_i = 10\lg\left(\frac{1}{N}\sum_{j=1}^{N} 10^{0,1L_{i,j}/\mathrm{dB}}\right)\mathrm{dB} \quad (1)$$

where

$L_{i,j}$ is the level of the ith spectral line for the jth spectrum;

N is the number of merged spectra.

5 Evaluation

5.1 General information

The aim of evaluation is to establish the audibility, ΔL. The procedure is the same for stationary and non-stationary noises. For tones that can only just be perceived, a quaver (eighth note) is to be adopted as a base time that is adequate for hearing. However, comprehensive studies have shown that the lower limit for use of the procedure is reached at averaging times of approximately 3 s. Lower averaging times lead to unjustified values of audibility, ΔL (too high, but also too low). Signals that have a very high level dynamic and/or frequency dynamic that no longer correspond with a 3-second averaging can, therefore, not be evaluated using this Publicly Available Specification. The following conditions shall be satisfied for the measurements.

— The extended uncertainty, U, of the audibility, ΔL, with a coverage probability of 90 % in a bilateral confidence interval (see Clause 6) shall not exceed ±1,5 dB. This is generally the case with evaluation of at least 12 time-staggered narrow-band averaged spectra. If there are less than 12 averaged spectra then the uncertainty shall be taken into consideration as given in Clause 6.

— Where there are alternating operating states, all of the operating states shall be covered by the averaging spectra used (see Annex E).

Tonal components in different critical bands are evaluated separately. To arrive at a decision on whether a tonal audibility has to be made, only the most pronounced tone is considered. If a number of tones are present within a critical band, then an energy summation of their tone levels, $L_{\mathrm{T}i}$, is carried out to yield a tone level, L_{T} (see 5.3.8).

A tonal audibility is performed for a tone only if its distinctness (see 3.18) is at least 70 %. This means a maximal bandwidth, Δf_{R}, dependent on the tone frequency [see Formula (9)] and necessitates edge steepness (see 3.19) of at least 24 dB/octave.

NOTE 1 For the distinctness of a tone, see 5.3.4.

NOTE 2 Harmonic multiples of a tone are evaluated, independently of that tone, similarly to all other components of the spectrum.

A sample program to determine audibility can be downloaded from http://standards.iso.org/iso/20065

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016

5.2 Width Δf_c of the critical band

The width Δf_c of the critical band about the tone frequency f_T is given by Formula (2):

$$\Delta f_c = 25{,}0\ \text{Hz} + 75{,}0\left[1{,}0 + 1{,}4\left(\frac{f_T/\text{Hz}}{1\,000}\right)^2\right]^{0{,}69}\ \text{Hz} \tag{2}$$

Assuming a geometric position of the corner frequencies of the critical band (see Annex B), these corner frequencies, f_1 and f_2, are derived as follows:

$$f_T = \sqrt{f_1 \times f_2} \tag{3}$$

$$f_1 = \frac{-\Delta f_c}{2} + \frac{\sqrt{(\Delta f_c)^2 + 4 f_T{}^2}}{2} \tag{4}$$

$$f_2 = f_1 + \Delta f_c \tag{5}$$

5.3 Determination of prominent tones

5.3.1 General information

The audibility of a tone is determined using the tone level, L_T, and the critical band level, L_G, of the masking noise in the critical band about the tone frequency, f_T. The frequency of all maxima of the spectrum is considered as the tone frequency.

The use of the Hanning window is recommended in Annex A. With window functions (except for rectangular windows), the effective analysis bandwidth, Δf_e, is greater than the bandwidth, Δf, of an ideal filter (see 3.13), i.e. the individual bands are thus superimposed. In the summation process, the energy components are counted a number of times (see Annex A for more information).

In a frequency analyzer, this influence of summation (number of lines >1) is taken into consideration through a correction value; if the level addition is simulated by the analyzer program, then this correction value has to be considered in the computing program, both in the formation of the tone level [see Formula (8)] and in the calculation of the masking noise [see Formula (12)].

5.3.2 Determination of the mean narrow-band level L_S of the masking noise

The mean narrow-band level, L_S, [see Formula (6)] is derived in an iterative procedure from the lines of the critical band about the line under investigation. The procedure commences with the energy averaging of all lines of the critical band with the exception of the line under investigation itself. In the subsequent steps, the levels of the lines of the critical band under consideration are no longer taken into consideration in the averaging procedure if their level exceeds the energy mean value determined beforehand by more than 6 dB. The iterative procedure is discontinued, if in an iteration step, the new energy mean value is equal within a tolerance of ±0,005 dB to that of the previous iteration step or if the number of lines contributing to the mean narrow-band level to the right or left of the line under investigation falls below a value of 5. In this case, the energy mean value from the last iteration step, at which the number of energy averaged levels on both sides of the line under investigation in each case was still at least 5 is used to form the mean narrow-band level.

For determination of the mean narrow-band level, the entire critical band about the line under investigation is used. Consequently, the range under investigation (see 3.21) is limited relative to the useable frequency f_N such that the upper limit of the uppermost critical band being considered does not exceed the useable frequency f_N. A corresponding condition also applies in principle for the lower limit of the lowest critical band considered. Since the use of this Publicly Available Specification is restricted

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/PAS 20065:2016