PD ISO/TR 22400-10:2018

BSI Standards Publication

Automation systems and integration — Key performance indicators (KPIs) for manufacturing operations management

Part 10: Operational sequence description of data acquisition

Documents
Document Sharing Hub

Full document details: PD ISO/TR 22400-10:2018

National foreword

This Published Document is the UK implementation of ISO/TR 22400-10:2018.

The UK participation in its preparation was entrusted to Technical Committee AMT/5, Industrial architectures and integration frameworks.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2018
Published by BSI Standards Limited 2018

ISBN 978 0 580 94946 3

ICS 25.040.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 October 2018.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD ISO/TR 22400-10:2018

TECHNICAL REPORT

ISO/TR 22400-10

First edition
2018-10

Automation systems and integration — Key performance indicators (KPIs) for manufacturing operations management —

Part 10: Operational sequence description of data acquisition

Systèmes d'automatisation et intégration — Indicateurs de la performance clé pour le management des opérations de fabrication —

Partie 10: Description de l'acquisition des données relatives aux séquences opérationnelles

Reference number
ISO/TR 22400-10:2018(E)

Documents
Document Sharing Hub
© ISO 2018

Full document details: PD ISO/TR 22400-10:2018

COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2018 – All rights reserved

Documents
Document Sharing Hub

Full document details: PD ISO/TR 22400-10:2018

Contents

Page

Foreword ..... **iv**
Introduction ..... **v**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 KPI calculation examples **2**
4.1 Example setup 2
4.2 KPIs for work unit 2
4.3 KPIs for production orders and production order sequences 7
4.4 KPIs for worker 15
Annex A (informative) **Example: Work unit data recording for KPI calculation** **19**

© ISO 2018 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 184, *Automation systems and integration*, Subcommittee SC 5, *Interoperability, integration, and architectures for enterprise systems and automation applications*.

A list of all parts in the ISO 22400 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2018 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Introduction

This document describes the procedure for the determination of key performance indicators (KPIs) by means of examples. The KPIs that are used are given in ISO 22400-2.

© ISO 2018 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Documents
Document Sharing Hub

Full document details: PD ISO/TR 22400-10:2018

Automation systems and integration — Key performance indicators (KPIs) for manufacturing operations management —

Part 10: Operational sequence description of data acquisition

1 Scope

This document contains descriptions for the practical use for applying formulae as specified in ISO 22400-2 for key performance indicators for production control and monitoring. This document is intended to be applied in conjunction with the content of ISO 22400-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 22400-2:2014, *Automation systems and integration — Key performance indicators (KPIs) for manufacturing operations management — Part 2: Definitions and descriptions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 22400-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
planned shut down time
PSDT
time in which the work unit is planned to be out of operation

Note 1 to entry: Corresponds to "no production" as defined in ISO 22400-2.

3.2
planned down time
PDOT
time, included in the planned operation time, in which the work unit is planned for no operations within the operation time period

Note 1 to entry: ISO 22400-2:2014, Figure 3, gives a detailed overview of the used time lines for work units as used for the ISO 22400 series.

3.3
work unit log
data recording of work unit events along with their time stamps

© ISO 2018 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

4 KPI calculation examples

4.1 Example setup

KPIs are calculated for different scopes including work unit and production orders. The KPIs are determined from the work unit log.

The example given in Tables 1 and 2 consists of two work units (W1 and W2) within a time period of one calendar day. Two production orders (PO1 and PO2) are executed in this production area within this calendar day. A work unit log for each work unit is produced. Based on the data in the work unit logs, KPIs can be calculated. The scope of the KPI can be the work unit, the production order, the worker etc.

Each Production Order (PO) is composed of two Production Order Sequences (POS):

— PO1: POS 1/1 followed by POS 1/2;

— PO2: POS 2/1 followed by POS 2/2.

In the example POS x/1 is always executed on work unit W1.

In the example POS x/2 is always executed on work unit W2.

The calculation of the KPIs takes place in two steps.

a) Determine KPI elements.

   The KPI elements can be determined based on the work unit logs

b) Calculate KPIs.

   The KPIs can be calculated based on the KPI elements.

The details are defined in “comments on the work unit logs”. The examples use “pieces” (Pcs) as item unit, however, any kind of item unit can be used.

4.2 KPIs for work unit

From work unit scope the following KPIs can be determined based on the work unit logs:

— Utilization efficiency;

— Setup ratio;

— Technical efficiency;

— Allocation efficiency;

— Availability;

— Effectiveness;

— Quality ratio;

— Overall equipment effectiveness index (OEE);

— Net equipment effectiveness index (NEE);

— Scrap ratio;

— Rework ratio;

— Actual to planned scrap ratio;

— MTBF;

© ISO 2018 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

— MTTF;

— MTTR;

— Direct energy consumption effectiveness;

— Direct net energy consumption effectiveness;

— Direct energy efficiency;

— Direct net energy efficiency.

Table 1 — Log of work unit 1

Determination of basics				
APT	=	[06:30 – 07:00] + [07:30 – 08:00] + [08:30 – 09:00] + [09:30 – 10:30] + [15:00 – 17:30] + [18:00 – 19:00] + [20:00 – 20:30]	=	390 min
AUST	=	[06:00 – 06:30] + [10:30 – 11:00] + [14:30 – 15:00] + [20:30 – 21:00]	=	120 min
ADET	=	[08:00 – 08:30] + [19:00 – 19:30] + [07:00 – 07:30] + [09:00 – 09:30] + [19:30 – 20:00]	=	150 min
TTR	=	[07:00 – 07:30] + [09:00 – 09:30] + [19:30 – 20:00]	=	90 min
PSDT	=	[00:00 – 06:00] + [22:00 – 24:00]	=	480 min
PDOT	=	[12:00 – 12:30] + [17:30 – 18:00]	=	60 min
PBT	=	1 440 min – PSDT – PDOT 1 440 min – 480 min – 60 min	=	900 min
AUPT	=	APT + AUST 390 min + 120 min	=	510 min
AUBT	=	APT + AUST + ADET = 390 min + 120 min + 150 min	=	660 min
GQ		$GQ_{POS\ 1/1} + GQ_{POS\ 2/1}$ 450 Pcs + 6 Pcs	=	456 Pcs
SQ		$SQ_{POS\ 1/1} + SQ_{POS\ 2/1}$ 40 Pcs + 2 Pcs	=	42 Pcs
RQ		$RQ_{POS\ 1/1} + RQ_{POS\ 2/1}$ 10 Pcs + 0 Pcs	=	10 Pcs
PQ		$PQ_{POS\ 1/1} + PQ_{POS\ 2/1}$ 500 Pcs + 8 Pcs	=	508 Pcs
PSQ		Planned scrap quantity in % × $PQ_{POS\ 1/1}$ + Planned scrap quantity in % × $PQ_{POS\ 2/1}$ 5 % × 500 Pcs + 25 % × 8 Pcs	=	27 Pcs
$PEDI_{POS\ 1/1}$	=	0,42 kWh	=	0,42 kWh
$PEDI_{POS\ 2/1}$	=	1,05 kWh	=	1,05 kWh
ADEC	=	$ADEC_{POS\ 1/1} + ADEC_{POS\ 2/1}$ 115 m^3 × 0,102 8 kWh/m^3 + 10,5 m^3 × 10 kWh/m^3 + 120 kWh + 4,5 m^3 × 0,102 8 kWh/m^3 + 0,45 m^3 × 10 kWh/m^3 + 4,5 kWh	=	246,28 kWh

© ISO 2018 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Table 1 *(continued)*

Calculation of KPIs				
Utilization efficiency	=	APT/AUBT		
	=	390 min/660 min	=	59,09 %
Setup ratio	=	AUST/AUPT		
	=	120 min/510 min	=	23,53 %
Technical efficiency	=	APT/(APT + ADET)		
	=	390/(390 + 150)	=	72,22 %
Allocation efficiency	=	AUBT/PBT		
	=	660 min/900 min	=	73,33 %
Availability	=	APT/PBT		
	=	390 min/900 min	=	43,33 %
Effectiveness	=	$Effectiveness_{POS\ 1/1}$ + $Effectiveness_{POS\ 2/1}$		
	=	($PRI_{POS\ 1/1}$ × $PQ_{POS\ 1/1}$ + $PRI_{POS\ 2/1}$ $PQ_{POS\ 2/1}$) /APT		
		(0,3 min/Pcs × 500 Pcs + 30 min/Pcs × 8 Pcs)/390 min	=	100,00 %
Quality ratio	=	($GQ_{POS\ 1/1}$ + $GQ_{POS\ 2/1}$)/($PQ_{POS\ 1/1}$ + $PQ_{POS\ 2/1}$)		
	=	(450 Pcs + 6 Pcs)/(500 Pcs + 8 Pcs)	=	89,76 %
OEE	=	Availability × Effectiveness × Quality ratio		
	=	43,33 % × 100 % × 89,76 %	=	38,89 %
NEE	=	AUPT/PBT × Effectiveness × Quality ratio		
	=	510 min/900 min × 100 % × 89,76 %	=	50,86 %
Scrap ratio	=	SQ/PQ		
	=	42 Pcs/508 Pcs	=	8,27 %
Rework ratio	=	RQ/PQ		
	=	10 Pcs/508 Pcs	=	1,97 %
Actual to planned scrap ratio	=	SQ/PSQ		
	=	42 Pcs/27 Pcs	=	155,56 %
MTBF	=	(AUST + APT + TTR)/(Number(FE) +1)		
	=	(120 min + 390 min + 90 min)/(3 +1)	=	150 min
MTTF	=	(AUST + APT)/(Number(FE) +1)		
	=	(120 min + 390 min)/(3 +1)	=	127,5 min
MTTR	=	TTR/(Number(FE) +1)		
	=	90 min/(3 +1)	=	22,5 min
Direct energy consumption effectiveness	=	($PDEI_{POS\ 1/1}$ × $PQ_{POS\ 1/1}$ + $PDEI_{POS\ 2/1}$ × $PQ_{POS\ 2/1}$)/ADEC		
	=	(0,42 kWh/Pcs × 500 Pcs + 1,05 kWh/Pcs × 8 Pcs)/246,28 kWh	=	88,68 %
Direct net energy consumption effectiveness	=	$PDEI_{POS\ 1/1}$ × $GQ_{POS\ 1/1}$ + $PDEI_{POS\ 2/1}$ × $GQ_{POS\ 2/1}$)/ADEC		
	=	(0,42 kWh/Pcs × 450 Pcs + 1,05 kWh/Pcs × 6 Pcs)/246,28 kWh	=	79,30 %

© ISO 2018 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Table 1 *(continued)*

Direct energy efficiency	=	ADEC/PQ		
	=	246,28 kWh/508 Pcs	=	0,485 kWh/Pcs
Direct net energy efficiency	=	ADEC/GQ		
	=	246,28 kWh/456 Pcs	=	0,540 kWh/Pcs

Table 2 — Log of Work unit 2

Determination of basics				
APT	=	[12:00 – 12:30] + [13:00 – 14:00] + [14:30 – 15:00] + [16:00 – 16:30] + [18:00 – 19:30] + [20:00 – 21:30]	=	330 min
AUST	=	[11:30 – 12:00] + [16:30 – 17:00] + [17:30 – 18:00] + [21:30 – 22:00]	=	120 min
ADET	=	[12:30 – 13:00] + [15:30 – 16:00] + [15:00 – 15:30]	=	90 min
TTR	=	[15:00 – 15:30]	=	30 min
PSDT	=	[00:00 – 06:00] + [22:00 – 24:00]	=	480 min
PDOT	=	[14:00 – 14:30] + [19:30 – 20:00]	=	60 min
PBT	=	1 440 min – PDBT – PDOT	=	900 min
		1 440 min – 480 min – 60 min		
AUPT	=	APT + AUST		
	=	330 min + 120 min	=	450 min
AUBT	=	APT + AUST + ADET		
	=	330 min + 120 min + 90 min	=	540 min
GQ		$GQ_{POS\ 1/2} + GQ_{POS\ 2/2}$		
	=	410 Pcs + 4 Pcs	=	414 Pcs
SQ		$SQ_{POS\ 1/2} + SQ_{POS\ 2/2}$		
	=	30 Pcs + 2 Pcs	=	32 Pcs
RQ		$RQ_{POS\ 1/2} + RQ_{POS\ 2/2}$		
	=	10 Pcs + 0 Pcs	=	10 Pcs
PQ		$PQ_{POS\ 1/2} + PQ_{POS\ 2/2}$		
	=	450 Pcs + 6 Pcs	=	456 Pcs
PSQ		Planned scrap quantity in % × $PQ_{POS\ 1/2}$ + Planned scrap quantity in % × $PQ_{POS\ 2/2}$		
	=	5 % × 450 + 25 % × 6 Pcs	=	24 Pcs
$PEDI_{POS\ 1/2}$	=	0,94 kWh	=	0,94 kWh
$PEDI_{POS\ 2/2}$	=	2,10 kWh	=	2,10 kWh
ADEC		$ADEC_{POS\ 1/2} + ADEC_{POS\ 2/2}$		
	=	210 m^3 × 0,102 8 kWh/m^3 + 18,7 m^3 × 10 kWh/m^3 + 222 kWh + 6,6 m^3 × 0,102 8 kWh/m^3 + 0,66 m^3 × 10 kWh/m^3 + 6,6 kWh	=	444,47 kWh
Calculation of KPIs				
Utilization efficiency	=	APT/AUBT		
	=	330 min/540 min	=	61,11 %
Setup ratio	=	AUST/AUPT		
	=	120 min/450 min	=	26,67 %

© ISO 2018 – All rights reserved

AVA Documents Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018

Table 2 *(continued)*

Technical efficiency	=	APT/(APT + ADET)		
	=	330 min/(330 min + 90 min)	=	78,57 %
Allocation efficiency	=	AUBT/PBT		
	=	540 min/900 min	=	60,00 %
Availability	=	APT/PBT		
	=	330 min/900 min	=	36,67 %
Effectiveness	=	$Effectiveness_{POS\ 1/2}$ + $Effectiveness_{POS\ 2/2}$		
		$PRI_{POS\ 1/2}$ × $PQ_{POS\ 1/2}$ + $PRI_{POS\ 2/2}$ × $PQ_{POS\ 2/2}$)/APT		
		(0,3 min/Pcs × 450 Pcs + 30 min/Pcs × 6 Pcs)/330 min	=	95,45 %
Quality ratio	=	($GQ_{POS\ 1/2}$ + $GQ_{POS\ 2/2}$)/($PQ_{POS\ 1/2}$ + $PQ_{POS\ 2/2}$)		
		(410 Pcs + 4 Pcs)/(450 Pcs + 6 Pcs)	=	90,79 %
OEE	=	Availability × Effectiveness × Quality ratio		
	=	36,67 % × 95,46 % × 90,79 %	=	31,78 %
NEE	=	AUPT/PBT × Effectiveness × Quality ratio		
	=	450 min/900 min × 95,46 % × 90,79 %	=	43,33 %
Scrap ratio	=	SQ/PQ		
	=	32 Pcs/456 Pcs	=	7,02 %
Rework ratio	=	RQ/PQ		
	=	10 Pcs/456 Pcs	=	2,19 %
Actual to planned scrap ratio	=	SQ/PSQ		
	=	32 Pcs/24 Pcs	=	133,33 %
MTBF	=	(AUST + APT + TTR)/(Number (FE) +1)		
	=	(120 min + 330 min + 30 min)/(1 +1)	=	240 min
MTTF	=	(AUST + APT)/(Number (FE) +1)		
	=	(120 min + 330 min)/(1 +1)	=	225 min
MTTR	=	TTR/(Number (FE) +1)		
	=	30 min/(1 +1)	=	15 min
Direct energy consumption effectiveness	=	($PDEI_{POS\ 1/2}$ × $PQ_{POS\ 1/2}$ + $PDEI_{POS\ 2/2}$ × $PQ_{POS\ 2/2}$)/ADEC		
	=	(0,94 kWh/Pcs × 450 Pcs + 2,10 kWh/Pcs × 6 Pcs)/444,47 kWh	=	98,00 %
Direct net energy consumption effectiveness	=	($PDEI_{POS\ 1/2}$ × $GQ_{POS\ ½}$ + $PDEI_{POS\ 2/2}$ × $GQ_{POS\ 2/2}$)/ADEC		
	=	(0,94 kWh/Pcs × 410 Pcs + 2,10 kWh/Pcs × 4 Pcs)/444,47 kWh	=	88,60 %
Direct energy efficiency	=	ADEC/PQ		
	=	444,47 kWh/456 Pcs	=	0,975 kWh/Pcs
Direct net energy efficiency	=	ADEC/GQ		
	=	444,47 kWh/414 Pcs	=	1,074 kWh/Pcs

© ISO 2018 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TR 22400-10:2018