PD ISO/TS 15143-3:2016

BSI Standards Publication

Earth-moving machinery and mobile road construction machinery — Worksite data exchange

Part 3: Telematics data

Documents
Document Sharing Hub

Full document details: PD ISO/TS 15143-3:2016

National foreword

This Published Document is the UK implementation of ISO/TS 15143-3:2016.

The UK participation in its preparation was entrusted by Technical Committee B/513, Construction equipment and plant and site safety, to Subcommittee B/513/1, Earth moving machinery (International).

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.
Published by BSI Standards Limited 2017

ISBN 978 0 580 93939 6
ICS 35.240.99; 53.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2017.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: PD ISO/TS 15143-3:2016

TECHNICAL SPECIFICATION

ISO/TS 15143-3

First edition
2016-12-01

Earth-moving machinery and mobile road construction machinery — Worksite data exchange —

Part 3: Telematics data

Engins de terrassement et machines mobiles de construction de routes — Échange de données sur le chantier —

Partie 3: Données télématiques

Reference number
ISO/TS 15143-3:2016(E)

Documents
Document Sharing Hub

© ISO 2016

Full document details: PD ISO/TS 15143-3:2016

COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub

Full document details: PD ISO/TS 15143-3:2016

Contents

Page

Foreword ... **vii**
Introduction ... **viii**
1 Scope ... **1**
2 Normative references ... **2**
3 Terms, definitions and abbreviated terms ... **2**
4 Data management and access control ... **4**
4.1 Minimum requesting period ... 4
4.2 Editing the data elements over time ... 5
4.3 Data element use case ... 5
4.4 Data element cross reference ... 5
4.5 Access authentication ... 5
5 Response formats ... **5**
6 XML Declaration links to definition segments ... **6**
7 Paging ... **6**
8 Discoverability ... **6**
8.1 General ... 6
8.2 Snapshot endpoint ... 6
8.2.1 Fleet snapshot ... 6
8.2.2 Single-element snapshot ... 7
8.3 Time series endpoint ... 8
8.3.1 General ... 8
8.4 Links ... 9
8.4.1 Reference attribute (rel) ... 9
8.4.2 Hypermedia reference URL (href) ... 9
9 Date and time formats ... **9**
10 Data fields summary ... **10**
11 Data field descriptions ... **12**
11.1 General ... 12
11.2 Machine header information ... 13
11.2.1 General ... 13
11.2.2 Telematics unit installation date ... 13
11.2.3 Equipment make ... 13
11.2.4 Equipment model ... 13
11.2.5 Equipment ID ... 13
11.2.6 Serial Number ... 13
11.2.7 OEM ISO Identifier (PIN or VIN) ... 13
11.3 Last known location ... 14
11.3.1 General ... 14
11.3.2 Date and time of location ... 14
11.3.3 Latitude of location ... 14
11.3.4 Longitude of location ... 14
11.3.5 Altitude of location ... 14
11.3.6 Unit of measure of altitude ... 14
11.3.7 Location Time Series Endpoint (Request) ... 14
11.3.8 Location Response Schema (Response) ... 15
11.4 Operating hours ... 15
11.4.1 General ... 15
11.4.2 Date and time of operating hours ... 15
11.4.3 Operating hours ... 15
11.4.4 Operating hours endpoint (Request) ... 15

AVA Documents
Document Sharing Hub

© ISO 2016 – All rights reserved

Full document details: PD ISO/TS 15143-3:2016

11.4.5 Operating hours schema (Response) 16
11.5 Cumulative fuel used (preferred) 16
11.5.1 General 16
11.5.2 Date and time of cumulative fuel used 16
11.5.3 Unit of measure of fuel used to date 16
11.5.4 Amount of fuel used to date 16
11.5.5 Cumulative fuel used endpoint (Request) 17
11.5.6 Cumulative fuel used schema (Response) 17
11.6 Fuel used in the preceding 24 hours (alternative, not preferred) 17
11.6.1 General 17
11.6.2 Date and time of fuel use in the preceding 24 hours 17
11.6.3 Unit of measure of fuel used in the preceding 24 hours 18
11.6.4 Fuel used in the preceding 24 hours 18
11.6.5 Fuel used in the preceding 24 hours endpoint (Request) 18
11.6.6 Fuel used in the preceding 24 hours schema (response) 18
11.7 Cumulative distance travelled 18
11.7.1 General 18
11.7.2 Date and time of distance 19
11.7.3 Unit of measure of distance 19
11.7.4 Cumulative distance travelled 19
11.7.5 Cumulative distance travelled endpoint (Request) 19
11.7.6 Cumulative distance travelled schema (response) 19
11.8 Caution codes referencing number 20
11.8.1 General 20
11.8.2 Date and time of code 20
11.8.3 IEC/ISO Symbol Reference Number identifier 20
11.8.4 Code description 20
11.8.5 Caution codes referencing number endpoint (Request) 20
11.8.6 Caution codes referencing number schema (response) 20
11.9 Cumulative idle operating hours 21
11.9.1 General 21
11.9.2 Date and time of cumulative idle operating hours 21
11.9.3 Cumulative idle operating hours 21
11.9.4 Cumulative idle operating hours endpoint (Request) 21
11.9.5 Cumulative idle operating hours schema (response) 22
11.10 Fuel remaining ratio 22
11.10.1 General 22
11.10.2 Date and time of percent fuel remaining 22
11.10.3 Fuel Remaining Ratio 22
11.10.4 Unit of measure for fuel tank capacity 22
11.10.5 Fuel tank capacity 22
11.10.6 Fuel remaining ratio endpoint (Request) 23
11.10.7 Fuel remaining ratio schema (response) 23
11.11 Percent of DEF remaining 23
11.11.1 General 23
11.11.2 Date and time of percent DEF remaining 23
11.11.3 Percent of DEF remaining 23
11.11.4 Unit of measure for DEF tank capacity 24
11.11.5 DEF tank capacity 24
11.11.6 Percent DEF remaining endpoint (Request) 24
11.11.7 Percent DEF remaining schema (response) 24
11.12 Engine condition 24
11.12.1 General 24
11.12.2 Date and time of engine condition 25
11.12.3 Engine Number 25
11.12.4 Engine condition 25
11.12.5 Engine condition endpoint (Request) 25
11.12.6 Engine condition schema (response) 25

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

11.13 Digital input state ... 25
11.13.1 General ... 25
11.13.2 Date and time of digital input set response ... 26
11.13.3 Digital input number ... 26
11.13.4 1Digital input state ... 26
11.13.5 Digital input state endpoint (Request) ... 26
11.13.6 Digital input state schema (response) ... 26
11.14 Cumulative power takeoff hours ... 27
11.14.1 General ... 27
11.14.2 Date and time of cumulative power takeoff ... 27
11.14.3 Cumulative power takeoff hours ... 27
11.14.4 Cumulative power takeoff hours endpoint (Request) ... 27
11.14.5 Cumulative power takeoff hours schema (response) ... 27
11.15 Average daily engine load factor ... 28
11.15.1 General ... 28
11.15.2 Date and time of average load factor ... 28
11.15.3 Average load factor for preceding 24 hour period ... 28
11.15.4 Average daily engine load factor endpoint (Request) ... 28
11.15.5 Average daily engine load factor schema (response) ... 28
11.16 Peak daily speed ... 29
11.16.1 General ... 29
11.16.2 Date and time of peak travel speed ... 29
11.16.3 Units of measure for speed ... 29
11.16.4 Peak speed for the preceding 24 h ... 29
11.16.5 Peak daily speed endpoint (Request) ... 29
11.16.6 Peak daily speed schema (response) ... 29
11.17 Cumulative load count ... 30
11.17.1 General ... 30
11.17.2 Date and time of load count ... 30
11.17.3 Cumulative load count ... 30
11.17.4 Cumulative load count endpoint (Request) ... 30
11.17.5 Cumulative load count schema (response) ... 30
11.18 Cumulative payload total ... 31
11.18.1 General ... 31
11.18.2 Date and time of cumulative payload ... 31
11.18.3 Unit of measure for payload ... 31
11.18.4 Cumulative payload ... 31
11.18.5 Cumulative payload total endpoint (Request) ... 31
11.18.6 Cumulative payload total schema (response) ... 31
11.19 Cumulative non-productive regeneration hours ... 32
11.19.1 General ... 32
11.19.2 Date and time for cumulative non-productive regeneration hours ... 32
11.19.3 Cumulative non-productive regeneration hours ... 32
11.19.4 Cumulative hours in non-productive regeneration endpoint (Request) ... 32
11.19.5 Cumulative hours in non-productive regeneration schema (response) ... 33
11.20 Cumulative idle non-operating hours ... 33
11.20.1 General ... 33
11.20.2 Date and time of cumulative idle nonoperating hours ... 33
11.20.3 Cumulative idle non-operating hours ... 33
11.20.4 Cumulative idle non-operating hours endpoint (Request) ... 33
11.20.5 Cumulative idle non-operating hours schema (response) ... 34
11.21 Data field descriptions for codes unique to each system ... 34
11.21.1 General ... 34
11.21.2 Diagnostic Trouble Code identifier ... 34
11.21.3 Date and time of code ... 35
11.21.4 Code severity ... 35
11.21.5 Code description ... 35
11.21.6 Unit of measure for ambient air temperature ... 35

AVA Documents
Document Sharing Hub

© ISO 2016 – All rights reserved

Full document details: PD ISO/TS 15143-3:2016

11.21.7 Ambient air temperature at time when code was triggered ... 35
11.21.8 Description of code source ... 35
11.21.9 Data field descriptions for codes unique to each system endpoint (Request) ... 36
11.21.10 ... Data field descriptions for codes unique to each system schema (response) ... 36

12 Data schemas ... 36
12.1 Common schema ... 36
12.2 Time series schema ... 36

13 Syntax errors ... 36

Annex A (informative) **Relationship between this document and ISO 15143-2 ... 38**

Annex B (informative) **Data support and collection ... 54**

Annex C (informative) **Common schema ... 55**

Annex D (informative) **Time series schema ... 59**

Bibliography ... 60

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 3, *Machine characteristics, electrical and electronic systems, operation and maintenance*.

This part of ISO 15143 is intended to be used in conjunction with ISO 15143-1 and ISO 15143-2.

A list of all parts in the ISO 15143 series can be found on the ISO website.

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

Introduction

This document is a data schema having the purpose of providing data directly from the equipment manufacturer or provider to the equipment owner in a standardized format for the use and convenience of equipment owners with mixed fleets of equipment.

It defines a set of web services that provide information about fleets of mobile equipment and their associated telematics data. The information about a fleet is provided as a resource, typically on the Internet, at a known Uniform Resource Location (URL). Any number of fleets can be represented, each with its own URL.

Clients can access these resources by sending HTTPS GET requests to the server at the given location. The server responds with an equipment information document whose vocabulary is defined in this document.

ISO/TC 127/SC 3 wishes to acknowledge the Association of Equipment Manufacturers and the Association of Equipment Management Professionals for their contributions to prior work on this subject.

The goal of this document is to provide direct access by end users to their specific fleet data, and not to enable third parties for data aggregation across end users or other purposes. The use of this document enables each end user or assigned third-party application developer to develop applications for purposes deemed appropriate by the end user.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

Earth-moving machinery and mobile road construction machinery — Worksite data exchange —

Part 3: Telematics data

1 Scope

This document specifies the communication schema designed to provide mobile machinery status data from a telematics provider's server to third-party client applications via the Internet. The data are collected from a mobile machine using telematics data-logging equipment and stored on a telematics provider's server. This document describes the communications records used to request data from the server and the responses from the server containing specified data elements to be used in the analysis of machine performance and health.

It is applicable to mobile earth-moving machinery as defined in ISO 6165 and mobile road construction machinery as defined in ISO 22242 equipped with location and time instrumentation.

It is not applicable to the on-board data collection, on-board communication protocol (e.g. CANbus) or wireless transmission of the mobile machinery data to the telematics provider's server *after* the data have been collected at the data logger. See Figure 1.



Figure 1 — Topography of conceptual mixed fleet telematics system within the scope of this document

© ISO 2016 – All rights reserved

Documents Document Sharing Hub

Full document details: PD ISO/TS 15143-3:2016

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3779, *Road vehicles — Vehicle identification number (VIN) — Content and structure*

ISO 6405-1, *Earth-moving machinery — Symbols for operator controls and other displays — Part 1: Common symbols*

ISO 6405-2, *Earth-moving machinery — Symbols for operator controls and other displays — Part 2: Specific symbols for machines, equipment and accessories*

ISO 8601, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO 10261, *Earth-moving machinery — Product identification numbering system*

ISO 15143-1:2010, *Earth-moving machinery and mobile road construction machinery — Worksite data exchange — Part 1: System architecture*

ISO 15143-2:2010, *Earth-moving machinery and mobile road construction machinery — Worksite data exchange — Part 2: Data dictionary*

ECMA-404, *The JSON Data Interchange Format*

IETFRFC 7231, *Hypertext Transfer Protocol (HTTP/1.1): Semantics and Context*

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms, definitions and abbreviated terms (see Table 1) apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at http://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
caution codes referencing number
ISO/IEC symbol registration number as defined in ISO 7000 and referenced in ISO 6405-1

Note 1 to entry: Caution codes referencing numbers are returned from the telematics provider server and refer to standardized symbols representing various conditions present on EMM.

3.2
construction worksite
location of the operation of a fleet of mobile equipment generally identified as construction machines where the machines are used to perform work

3.3
data element
instance of data transmitted by the OEM server to the third-party application adhering to the definition of the quantity or condition described by Clause 11 of this document

3.4
discoverability
requirement that the data be stored in such a manner that it can be accessed if necessary

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

3.5
endpoint
address or connection point to the provider's server for a specific API method

Note 1 to entry: Endpoints are associated by a URL.

3.6
end user
organization owning and or operating the mobile machinery

Note 1 to entry: The end user utilizes the telematics data for the purpose of managing the tasks associated with work performed on a construction worksite.

3.7
fault code
set of codes unique to each OEM related to diagnostic trouble codes as defined in SAE J1939-73

Note 1 to entry: Fault codes are defined by the OEM and might not be standardized. The third-party application developer needs to obtain fault code definitions from each OEM.

3.8
Internet media-type
two-part identifier for file formats on the Internet

3.9
link
element to allow the third party or end user to be directed to additional data or resources

3.10
make code
alphabetic string representing the OEM of a specific piece of equipment

3.11
model
alphanumeric string representing the machine form type and series as defined by the OEM

3.12
namespace
set of symbols that are used to organize objects of various kinds, so that these objects may be referred to by name

3.13
namespace URI
uniquely named elements and attributes in an XML document

Note 1 to entry: Namespaces are defined in a W3C recommendation. An XML instance might contain element or attribute names from more than one XML vocabulary.

3.14
serial number
alphanumeric string defined by the OEM identifying a specific piece of equipment

Note 1 to entry: The serial number is generally the PIN as defined in ISO 10261.

3.15
snapshot time
date and time at which the snapshot of the fleet was created

3.16
telematics provider
either OEM or third party providing telematics equipment or services

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

3.17
time series
sequence of data points, typically consisting of successive measurements made over a period of time

Note 1 to entry: Examples of a time series would be the geospatial position of a piece of equipment or the set of fault codes generated by a piece of equipment over a period of time.

3.18
version
integer that is used to distinguish different versions of the contract

3.19
XML declaration
processing instruction that identifies the document as being XML

Note 1 to entry: All XML documents should begin with an XML declaration, which should be situated at the first position of the first line in the XML document.

Table 1 — Abbreviations and acronyms

API	Application programming interface
DEF	Diesel exhaust fluid
EI	Electronic interface
FMI	Failure mode indicator
GPS	Global positioning system
HREF	Hypermedia reference URL
ID	Identification
IETF	Internet engineering task force
OEM	Original equipment manufacturer
PIN	Product identification number
REL	Reference attribute
SI	*Systeme internationale* (international system of units)
SOAP	Simple object access protocol
SPN	Suspect parameter number
URI	Uniform resource identifier
URL	Universal resource location
URN	Universal Resource Name
UTC	Universal Coordinated Time
UTF-8.EI	Unicode transformation format, 8 bit
VIN	Vehicle Identification Number
XML	Extensible Markup Language

4 Data management and access control

4.1 Minimum requesting period

The recommended minimum response period from the telematics provider server to the third-party application is one response per 15 min. The data provider may choose to provide the data less often.

The server supplies the last known data to the application independent of the update rate from the machine to the server. The actual call-in times from the machine can vary due to cell coverage, telematics settings, etc., so the last known data can be significantly older and can remain unchanged between server data transmissions to the application.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

4.2 Editing the data elements over time

The data set identified in this document is expected to be modified over time in a controlled fashion as set forth in ISO 15143-1:2010, A.2 with updated .XSD files to be posted at http://standards.iso.org/iso/15143/-3/ as they become available.

4.3 Data element use case

A use case as defined in ISO 15143-1 for each data element defined in this document is presented in Table A.2.

4.4 Data element cross reference

The data element names and attributes identified in this document have been harmonized with similar data elements defined in ISO 15143-2:2010, Table A.1 and further defined in ISO 15143-2:2010, Table A.2. The relationships between the data elements in this document and the related ones in ISO 15143-2 are presented in Annex A.

4.5 Access authentication

Implementers control access via OAuth Version 1.0A or OAuth Version 2.0 using HTTPS, as defined by the Internet engineering task force (IETF). Refer to http://www.ietf.org for additional information.

The telematics provider assigns security credential and access information when the end user registers the fleet. Each telematics provider has its own registration procedure. End users should contact the telematics provider for information on how to register for access to data via this document.

The response is a full snapshot of the fleet. If the fleet contains no equipment at the time of the snapshot, an empty document is returned. To prevent excessively frequent access, the provider may return “503 Service Unavailable” for requests that are more frequent than one per 15 min interval as expressed in 4.1.

OAuth provides client applications a secure delegated access to server resources on behalf of a resource owner. It specifies a process for resource owners to authorize third-party access to the server resources without sharing credentials. OAuth allows access tokens to be issued to third-party clients by an authorization server, with the approval of the resource owner, or end-user. The client then uses the access token to access the protected resources hosted by the resource server.

5 Response formats

This international standard recommends and describes the use of either of two representation formats: XML version 1.0 or JSON.

For examples in this document, XML version 1.0 is used. The recommended encoding is UTF-8. XML files are expected to be stand-alone documents. Each endpoint provides its own XML schema, with a common schema being located at http://standards.iso.org/iso/15143/-3/common.xsd. The file or stream that contains one XML document consists of zero or more records. Each record consists of several fields, which are detailed below. An XML document is sent without a wrapper (such as SOAP). Its Internet Media-Type is text/xml. XML is the preferred representation format.

JSON shall be compliant with the ECMA-404 standard representation. Naming conventions for JSON shall follow XML protocols.

If schema validation is required, use of the XML representation formats is recommended.

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

6 XML Declaration links to definition segments

XML documents shall begin with an XML declaration which includes the following attributes:

— Namespace 1;

— snapshotTime;

— version;

— Name Space URI.

XML Namespace: XML namespaces provide a simple method for qualifying element and attribute names used in Extensible Markup Language documents by associating them with namespaces identified by URI references.

Declaration Version specifies the version of the XML standard to which the XML document conforms.

The snapshot time is the date and time at which the snapshot of the fleet was created. Its format is described in 11.18.

URL identifies the Internet domain address. < Fleet snapshotTime="2015-05-29T10:57:19Z" version=**"1"** xmlns="http://standards.iso.org/iso/15143/-3"

7 Paging

Any endpoints that return more than one piece of equipment or list of telematics data shall be paged. This navigation is controlled by the page number parameter present on the endpoint URL. Each endpoint that provides paging shall also include links for easy navigation to the current, previous, next, and last pages. By default, a maximum of 100 records is returned per page.

8 Discoverability

8.1 General

Integrators using this document are encouraged to discover the data being supplied. For this reason, endpoints presented in this document contain sets of links that allow traversal of pages of data, as well as linking to other endpoints within the standard. This allows a program to travel these links and find the data that is supported for each implementation. There are two classifications of endpoints: snapshot (see 8.2) and time series (see 8.3). Snapshot endpoints return data for a fleet (see 8.2.1) or a single piece of equipment (see 8.2.2).

8.2 Snapshot endpoint

The set of snapshot endpoints listed in 8.2.1 and 8.2.2 use the common schema to provide a snapshot view of a fleet or an individual piece of equipment. A snapshot is a single point in time. Time-series data, such as fault codes and switch status, are not included in the snapshot view.

8.2.1 Fleet snapshot

The snapshot fleet endpoint is defined to be: URL:/Fleet/{pageNumber}. The snapshot fleet endpoint uses the Common Schema. See Annex A.

This endpoint provides a snapshot view of the fleet. This endpoint is paginated with a default of 100 records per page. See Annex C.

The detailed specification of each data element is listed in Clause 11.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

Fleet snapshot data elements defined in this document are listed here:

— Header information (EquipmentHeader);

— Last Known Location (Location);

— Operating Hours (CumulativeOperatingHours);

— Cumulative Fuel Used (FuelUsed);

— Fuel Used in the Preceding 24 hours (FuelUsedLast24);

— Cumulative Distance Travelled (Distance);

— Cumulative Idle Hours (CumulativeIdleHours);

— Fuel Remaining Ratio (FuelRemaining);

— DEF Remaining Ratio (DEFRemaining);

— Engine Condition (EngineStatus);

— Cumulative Power Take Off Hours (CumulativePowerTakeOffHours);

— Average Daily Engine Load Factor (AverageDailyLoadFactorLast24);

— Peak Daily Speed (MaximumSpeedLast24);

— Cumulative Load Count (CumulativeLoadCount);

— Cumulative Payload Total (CumulativePayloadTotals);

— Cumulative Nonproductive Regeneration Hours (CumulativeActiveRegenerationHours);

— Cumulative Non-Productive Idle Hours (CumulativeNonProductiveIdleHours).

8.2.2 Single-element snapshot

The single-element snapshot endpoint is defined to be: URL: /Fleet/Equipment/{identifier}.

The single-element snapshot uses the Common Schema. See Annex C.

The single-element snapshot provides the same data as the Fleet Snapshot Endpoint, but is limited to a single piece of equipment. This piece of equipment is identified by the inclusion of a PIN or VIN as parameters in the URL.

The PIN or VIN identifier is chosen depending upon the classification of the machine as earth-moving machinery according to ISO 6165 or mobile road construction machinery according to ISO 22242.

The single-element snapshot contains the data elements listed below describing a single piece of equipment. The details of each data element are provided in Clause 11.

Single-element snapshot data elements defined in this document are listed here:

— Header information (EquipmentHeader);

— Last Known Location (Location);

— Operating Hours (CumulativeOperatingHours);

— Cumulative Fuel Used (FuelUsed);

— Fuel Used in the Preceding 24 h (FuelUsedLast24);

— Cumulative Distance Travelled (Distance);

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

— Cumulative Idle Hours (CumulativeIdleHours);

— Fuel Remaining Ratio (FuelRemaining);

— DEF Remaining Ratio (DEFRemaining);

— Engine Condition (EngineStatus);

— Cumulative Power Take Off Hours (CumulativePowerTakeOffHours);

— Average Daily Engine Load Factor (AverageDailyLoadFactorLast24);

— Peak Daily Speed (MaximumSpeedLast24);

— Cumulative Load Count (CumulativeLoadCount);

— Cumulative Payload Total (CumulativePayloadTotals);

— Cumulative Nonproductive Regeneration Hours (CumulativeActiveRegenerationHours);

— Cumulative Non-Productive Idle Hours (CumulativeNonProductiveIdleHours).

8.3 Time series endpoint

8.3.1 General

Time series endpoints provide a view into telematics data for a single construction machine over the specified time.

The range of a time series is specified by its start date and time and end date and time.

These endpoints are designed to be discoverable so that the integrating system can follow links to sets of time series telematics data as dictated by the business need. A detailed description of these linkable telematics data endpoints can be found in Clause 11.

A time series endpoint is defined to be: URL: /Fleet/Equipment/{identifier}/{startDateUTC}/{endDateUTC}.

The set of time series endpoints use the time series schema and the common schema.

These endpoints provide telematics data for a single machine over the specified time range.

The single piece of equipment is identified by the inclusion of a PIN or VIN as the parameter {identifier} in the URL. A call to both of these endpoints shall return the available readings within the timeframe for the equipment specified.

The time series endpoints are

— Locations,

— CumulativeOperatingHr,

— CumulativeFuelUsed,

— FuelUsedinthepreceding24hr,

— Distance,

— CautionCodes,

— CumulativeIdleHours,

— EngineCondition remaining ratio,

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

— DEFremaining,

— EngineCondition,

— SwitchStatus,

— CumulativePowerTakeOffHours,

— AverageDailyEngineLoadFactor,

— PeakDailySpeed,

— CumulativeLoadCount,

— CumulativePayloadTotals,

— CumulativeNonproductiveRegenerationHours,

— CumulativeIdleNonoperatingHours, and

— FaultCode.

8.4 Links

Each endpoint that returns more than one piece of equipment or message shall include a set of links. These links are used to describe the metadata about the web service call. Each link shall contain a relationship (rel) and a hyperlink (href).

— **Links**

  — Relationship (rel)

  — Hyperlink (href)

8.4.1 Reference attribute (rel)

The relationship attribute describes the link. Paginated services shall include a collection of links that describe the current page (self), next page (next), and previous page (prev).

The time series summary endpoints contain links to the available telematics data for each piece of equipment. These links are referenced by the name of the type of telematics data (e.g. Location, Fault Code, Switch Status) and contain a URL to one of the time series telematics data endpoints.

8.4.2 Hypermedia reference URL (href)

The hypermedia reference URL (href) is a reference to another endpoint. These references are provided so that available data are discoverable by automated systems.

9 Date and time formats

All date and time stamps in an EI document are to be formatted as ISO 8601 “date and time” that includes the year, month, day, hour, minutes, and seconds. It does not include fractional seconds. If the information available to the server does not include minutes and seconds, the minutes and seconds are set to zero. It is expressed in universal coordinated time (UTC) with the use of the UTC indicator (“Z”).

Date and Time are expressed as: YYYY-MM-DDThh:mm:ssZ

NOTE In accordance with ISO 8601, minutes and seconds are optional.

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

10 Data fields summary

The data elements identified in this document are summarized in Table 2 with the supporting attributes in the order of presentation in the .XML response to a request. The parameters in parentheses in Table 2 are names of data elements and attributes found in the .XSD files.

Annex A contains a cross reference table that harmonizes data element names and value domain names defined in ISO 15143-2 with the provisions of this document. The data element and attribute names found in the .XSD listings in Clause 11 and on URN http://standards.iso.org/iso/15143/-3 are listed adjacent to data element names and value domain names defined in ISO 15143-2:2010, Tables A.1 and A.2.

Table 2 — Data elements and attributes

Data element	Attributes
Header information (EquipmentHeader)	— Telematics Unit Installation Date (UnitInstallDateTime) — Equipment Make (OEMName) — Equipment Model (Model) — Equipment ID (EquipmentID) — Serial Number (SerialNumber) — OEM ISO Number (PIN)[a]
Last known location (Location)	— Date and time (datetime) — Latitude of location (Latitude) — Longitude of location (Longitude) — Altitude of location (Altitude) — Units of Altitude (AltitudeUnits)
Operating hours (CumulativeOperatingHours)	— Date and time (datetime) — Cumulative operating hours (Hour)
Cumulative fuel used (FuelUsed)	— Date and time (datetime) — Unit of measure of fuel (FuelUnits) — Cumulative fuel used (FuelConsumed)
Fuel used in the preceding 24 hours (FuelUsedLast24)	— Date and time (datetime) — Unit of measure of fuel (FuelUnits) — Fuel used preceding 24 hrs (FuelConsumed)
Cumulative distance travelled (Distance)	— Date and time (datetime) — Unit of measure of distance (OdometerUnits) — Cumulative distance travelled (Odometer)
Caution Codes (CautionMessages)	— Date and time (datetime) — Caution codes referencing number identifier (Identifier) — Description of caution (Description)
Cumulative idle operating hours (CumulativeIdleHours)	— Date and time (datetime) — Cumulative idle hour (Hour)
Fuel remaining ratio (FuelRemaining)	— Date and time (datetime) — Fuel remaining ratio (Percent) — Unit of Measure of Fuel Tank (FuelTankCapacityUnits) — Fuel Tank Capacity (FuelTankCapacity)

[a] PIN and VIN are interchangeable and mutually exclusive. PIN is the name used in common.xsd

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

Table 2 *(continued)*

Data element	Attributes
DEF remaining ratio (DEFRemaining)	— Date and time (datetime) DEF remaining ratio (Percent) — Unit of Measure of DEF Tank (DEFTankCapacityUnits) — DEF Tank Capacity (DEFTankCapacity)
Engine condition (EngineStatus)	— Date and time (datetime) — Engine number (EngineNumber) — Engine running (Running)
Digital input state (SwitchStatus)	— Date and time (datetime) — Digital input number (SwitchNumber) — Is switch on or off (IsOn)
Cumulative power take off hours (CumulativePowerTakeOffHours)	— Date and time (datetime) — Cumulative power take off hours (Hour)
Average daily engine load factor (AverageLoadFactorLast24)	— Date and time (datetime) — Average daily load factor (LoadFactor)
Peak Daily Speed (MaximumSpeedLast24)	— Date and time (datetime) — Unit used for speed (SpeedUnits) — Peak speed (Speed)
Cumulative Load Count (CumulativeLoadCount)	— Date time (datetime) — Cumulative load count (Count)
Cumulative Payload Totals (CumulativePayloadTotals)	— Date and time (datetime) — Unit of measure for payload (weightuom) — Cumulative payload (Payload)
Cumulative Nonproductive Regeneration Hours (CumulativeActiveRegenerationHours)	— Date and time (datetime) — Cumulative regeneration hour (Hour)
Cumulative idle nonoperating hours (CumulativeNonProductiveIdleHours)	— Date and time (datetime) — Cumulative non productive idle (Hour)
Diagnostic Trouble Codes (DiagnosticTroubleCode)	— Diagnostic Trouble Code Identifier (CodeIdentifier) — Date and time (datetime) — Code severity (CodeSeverity) — Code description (CodeDescription) — Temperature units (temperatureunits) Ambient air temperature (airtemp) Description of Code Source (CodeSource)

[a] PIN and VIN are interchangeable and mutually exclusive. PIN is the name used in common.xsd

© ISO 2016 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016

11 Data field descriptions

11.1 General

Endpoints (requests) shall be sent from the third-party application to the telematics provider server; 11.2 to 11.21 contain examples of URL describing the endpoints. Illustrative examples of two optional URLs are listed below.

Option 1 URL: /Fleet/Equipment/ID/{OEM ISO identifier}/Locations/{startDateUTC}/{endDateUTC}/{pageNumber}

Option 2 URL: /Fleet/Equipment/MakeModelSerial/{makeCode}/{model}/{serialNumber}/Locations/{startDateUTC}/{endDateUTC}/{pageNumber}.

The format of Option 1 is preferred.

Option 1 is used when the machine is identified by a PIN or a VIN. Option 1 contains the argument /ID/{OEM ISO identifier}.

Option 2 is used when the machine is identified by serial number but a PIN or VIN is not available. Option 2 contains the argument /MakeModelSerial/{makeCode}/{model}/{serialNumber}.

Only Option 1 is listed in 11.2 to 11.21. However, Option 2 may be supported by the OEM if desired.

Each response field is described in detail in 11.2 to 11.21. Responses from the endpoints provide specific time series data. If a time range is not specified, the response should default to the last 14 consecutive days of data. Results are paginated with a default of 100 records per page.

The common schema referenced in each of the data elements listed in 11.2 to 11.21 are found in Annex C and are posted to URN http://standards.iso.org/iso/15143/-3, where the filename describes the data element.

NOTE This document avails decimal points where the text indicates XSD format.

© ISO 2016 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 15143-3:2016