



BSI Standards Publication

Determination of long-term flow of geosynthetic drains

National foreword

This Published Document is the UK implementation of [ISO/TS 18198:2023](#).

The UK participation in its preparation was entrusted to Technical Committee B/553, Geosynthetics.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 16161 8

ICS 59.080.70

Compliance with a Published Document cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION

ISO/TS 18198

First edition
2023-03-24

Determination of long-term flow of geosynthetic drains



Reference number
ISO/TS 18198:2023(E)

AVA Documents
Document Sharing Hub
© ISO 2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test equipment and procedures for determination of short-term in- plane water flow	1
4.1 Measurement of maximum hydraulic transmissivity and flow rate	1
4.2 Test equipment	2
4.2.1 Unidirectional flow	2
4.2.2 Index and performance tests	5
4.3 Normal compressive loading and seating time	5
4.4 Number of test specimens per sample per test	6
4.5 Hydraulic gradient	7
5 Determination of long-term flow performance	7
5.1 General	7
5.2 Reduction factors (R_F)	8
5.3 Reduction factor for intrusion ($R_{F,in}$ and $R_{F,GI}$)	9
5.4 Reduction factor for creep ($R_{F,cr}$)	10
5.4.1 General	10
5.4.2 Time-temperature superposition methods	11
5.5 Reduction factors for chemical clogging ($R_{F,CC}$) and biological clogging ($R_{F,BC}$)	12
5.6 Additional considerations	13
5.6.1 Design life	13
5.6.2 Design temperature	13
5.6.3 Installation damage	14
5.6.4 Durability of the polymers	14
6 Alternative procedures to determine Q_a	14
6.1 General	14
6.2 Long-term reduction of water flow capacity due to compressive creep by the BAM (Germany) method	14
6.3 Thickness-dependent short-term flow testing using SIM	17
6.4 Time dependent loading followed by flow capacity measurements	19
Bibliography	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 221, *Geosynthetics*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The most commonly used drainage geosynthetics are the geocomposites which are produced by laminating one or two geotextiles, with a filter function, onto a drainage core. Examples are included in [Figure 1](#).




Figure 1 — Examples of drainage cores

The components generally have the following characteristics under operating conditions:

- filtering component:
 - adequate permeability to gases and liquids in the direction perpendicular to the filter plane;
 - retention capacity of the soil particles;
- drainage core:
 - adequate permeability to gases and liquids in the direction planar to the drainage structure;
 - adequate compressive strength and creep resistance for the loads to be applied.

The geocomposites are often defined by the drainage cores: geomats (GMA), geonets (GNT), geospacers (GSP), multi-linear drains.

This page deliberately left blank

Determination of long-term flow of geosynthetic drains

1 Scope

This document specifies methods of deriving reduction factors for geosynthetic drainage materials to account for intrusion of filter geotextiles, compression creep, and chemical and biological degradation. It is intended to provide a link between the test data and the codes for design with geosynthetic drains.

The geosynthetics covered include those whose primary purpose is planar drainage, such as geonets, cusped cores only, or cusped cores combined with laminated filter geotextiles, and drainage liners, where the drainage core is made from polypropylene and high-density polyethylene. The majority of geosynthetic drains are geocomposites with geotextiles laminated to a drainage core and it is important, where possible, to consider the drainage behaviour of the geocomposite as a whole rather than the behaviour of the component parts in isolation.

This document does not cover the strength of overlaps or joints between geosynthetic drains nor whether these might be more or less durable than the basic material. It does not apply to geomembranes, for example, in landfills. It does not cover the effects of dynamic loading nor any change in mechanical properties due to soil temperatures below 0 °C, or the effects of frozen soil. This document does not cover uncertainty in the design of the drainage structures, nor the human or economic consequences of failure. Design guidance for geosynthetic drains is found in [ISO/TR 18228-4](#).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO 10318-1](#), *Geosynthetics — Part 1: Terms and definitions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in [ISO 10318-1](#) apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Test equipment and procedures for determination of short-term in-plane water flow

4.1 Measurement of maximum hydraulic transmissivity and flow rate

The primary function of geosynthetic drains is to convey or transmit fluid within the flow direction(s) of a drainage layer. The discharge capacity can be given in terms of:

- Specific flow rate, which is the discharge per unit width in the geosynthetic drain, under a specified hydraulic gradient, as per [Formula \(1\)](#):

$$Q = q / B \quad (1)$$