PD ISO/TS 22704:2022

BSI Standards Publication

# Mechanical vibration — Uncertainty of the measurement and evaluation of human exposure to vibration

Documents
Document Sharing Hub

Full document details: PD ISO/TS 22704:2022

# National foreword

This Published Document is the UK implementation of ISO/TS 22704:2022.

The UK participation in its preparation was entrusted to Technical Committee GME/21/6, Human exposure to mechanical vibration and shock.

A list of organizations represented on this committee can be obtained on request to its committee manager.

**Contractual and legal considerations**

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

This publication is not to be regarded as a British Standard.

© The British Standards Institution 2022
Published by BSI Standards Limited 2022

ISBN 978 0 539 12744 7

ICS 13.160

**Compliance with a Published Document cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 June 2022.

**Amendments/corrigenda issued since publication**

| Date | Text affected |
|---|---|

Documents
Document Sharing Hub

Full document details: PD ISO/TS 22704:2022

TECHNICAL SPECIFICATION

# ISO/TS 22704

First edition
2022-04

# Mechanical vibration — Uncertainty of the measurement and evaluation of human exposure to vibration

*Vibrations mécaniques — Incertitude de mesure et évaluation de l'exposition humaine aux vibrations*

Reference number
ISO/TS 22704:2022(E)

Documents
Document Sharing Hub

© ISO 2022

Full document details: PD ISO/TS 22704:2022

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland



© ISO 2022 – All rights reserved

Documents
Document Sharing Hub

Full document details: PD ISO/TS 22704:2022

# Contents

Page

**Foreword** ..... **iv**

**Introduction** ..... **v**

**1 Scope** ..... **1**

**2 Normative references** ..... **1**

**3 Terms and definitions** ..... **1**

**4 Considerations regarding the uncertainty of vibration measurements** ..... **7**
- 4.1 Measurement objectives and fixed parameters ..... 7
- 4.2 Types of uncertainties ..... 8
- 4.3 Measurement instrumentation uncertainty sources ..... 8

**5 Evaluation of the uncertainty** ..... **9**
- 5.1 Evaluation of the uncertainty through mathematical modelling ..... 9
- 5.2 Determination of the uncertainty from interlaboratory tests ..... 10
- 5.3 Determination (estimation) of uncertainties from field measurements ..... 10

**6 Presentation of results** ..... **11**

**7 Use of uncertainties** ..... **13**
- 7.1 General ..... 13
- 7.2 Use of uncertainties in comparisons ..... 13

**Annex A** (informative) **Uncertainty in the measurement of hand-arm vibration at the workplace — Example for determination of the measurement uncertainty of the vibration exposure during task-based measurements according to ISO 5349-2** ..... **14**

**Annex B** (informative) **Example for determination of the measurement uncertainty of emission measurements on hand-held and hand-guided machines** ..... **25**

**Annex C** (informative) **Typical errors** ..... **28**

**Annex D** (informative) **Statistical background** ..... **30**

**Bibliography** ..... **31**

© ISO 2022 – All rights reserved



Documents
Document Sharing Hub

Full document details: PD ISO/TS 22704:2022

# Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 4, *Human exposure to mechanical vibration and shock*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.


© ISO 2022 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

# Introduction

This document takes the form of a guide and describes how to deal with the uncertainty of vibration quantities associated with human exposure to vibrations.

The uncertainty arises from various sources. These uncertainties need to be distinguished from errors, such as when using measuring instruments or selecting the measurement strategy, which may falsify the measurand. Errors are not considered in this guide.

Calculations of measurement uncertainty are meaningful and valid only if all significant mistakes have been identified.

This document is intended to be used as a reference document for other standards. Examples of the application of the individual methods in practical situations are provided in the annexes. These examples are related to hand-arm vibration but the principles also apply for whole-body vibration.

© ISO 2022 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

Documents
Document Sharing Hub

# Mechanical vibration — Uncertainty of the measurement and evaluation of human exposure to vibration

## 1 Scope

This document specifies methods for determining the uncertainty of the measurement and evaluation of human exposure to vibration. It applies to measurements of vibration quantities (measurands), calculated following a relevant measurement model on the basis of directly measured values, to evaluate

a) human exposure to hand-transmitted vibration at the workplace,

b) vibration emission of hand-held and hand-guided machinery in a laboratory setting,

c) human exposure to whole-body vibration at the workplace, and

d) whole-body vibration emission of vehicles.

Examples of the application of the individual methods in practical situations are provided in the annexes.

In this document a measurement error is defined as the difference between a measured and a reference quantity value.

In this document "uncertainty" does not include errors that result from bad measurement strategies, faulty use of measurement equipment or other mistakes.

## 2 Normative references

The following document is referred to in the text in such a way that some or all of it's content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC Guide 99, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM)*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 99 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

© ISO 2022 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

**3.1**
**input quantity in a measurement model**
input quantity
$X$
quantity that must be measured, or a quantity, the value of which can be otherwise obtained, in order to calculate a measured quantity value of a measurand

EXAMPLE When evaluating the daily vibration exposure, vibration magnitude and exposure time are input quantities of a measurement model.

Note 1 to entry: An input quantity in a measurement model is often an output quantity of a measuring system.

Note 2 to entry: Indications, corrections and influence quantities can be input quantities in a measurement model.

Note 3 to entry: An estimated value for $X$ is $x$.

[SOURCE: ISO/IEC Guide 99:2007, 2.50, modified — example adapted and Note 3 added]

**3.2**
**output quantity in a measurement model**
output quantity
$Y$
quantity, the measured value of which is calculated using the values of input quantities in a measurement model

$$Y = f(X_1, X_2, \ldots) \tag{1}$$

Note 1 to entry: An estimated value for $Y$ is $y$.

[SOURCE: ISO/IEC Guide 99:2007, 2.51, modified — Formula and Note 1 added]

**3.3**
**arithmetic mean value**
$\overline{x}$
best estimated value for the expected value of the individual measured values when $N$ independent observations $x_{i,1}, x_{i,2}, \ldots, x_{i,N}$ are available for the *input quantity* (3.1), $X_i$:

$$\overline{x_i} = \frac{1}{N}\sum_{k=1}^{N} x_{i,k} \tag{2}$$

Note 1 to entry: The arithmetic mean value of the output quantity for $N$ independent observations is

$$\overline{y} = \frac{1}{N}\sum_{k=1}^{N} y_k \tag{3}$$

**3.4**
**variance**
$s^2$
measure for the scattering of the measured values when $N$ individual measured values are available for the variable $X_i$:

$$s_i^{\,2} = \frac{1}{N-1}\sum_{k=1}^{N}\left(x_{i,k} - \overline{x_i}\right)^2 \tag{4}$$

Note 1 to entry: This Formula produces an estimated value for the variance of the *measured values*.

Note 2 to entry: An estimated value for the variance of the *mean value* is


© ISO 2022 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

$$s^2(\overline{x_i}) = \frac{s_i^{\,2}}{N} \tag{5}$$

Note 3 to entry: The variance of the mean value is always smaller than the variance of the measured values.

**3.5**
**standard deviation**
*s*
positive square root of the *variance* (3.4)

Note 1 to entry: The standard deviation of the individual *measured values* is therefore

$$s_i = \sqrt{\frac{1}{N-1}\sum_{k=1}^{N}\left(x_{i,k} - \overline{x_i}\right)^2}\ s_i \tag{6}$$

The standard deviation of the measured values is a measure for the scattering of the measured values in a sample (measurement series) around their (arithmetic) mean value. It is also referred to as $s_{n-1}$ in standards to determine vibration emission values of machines (see Annex A).

Note 2 to entry: The standard deviation of the *mean value* is

$$s(\overline{x_i}) = \sqrt{\frac{1}{N(N-1)}\sum_{k=1}^{N}\left(x_{i,k} - \overline{x_i}\right)^2} \tag{7}$$

The standard deviation of the mean value is a measure for the accuracy of repeated measurements. Formula (7) is used when Type A evaluation is applied (see A.2).

**3.6**
**sensitivity coefficient**
$c_i$
partial derivative of the *output quantity* (3.2) according to $X_i$ at the location of the estimated values of the *input quantities* (3.1):

$$c_i = \left.\frac{\partial f}{\partial X_i}\right|_{x_1,\ldots,x_N} \tag{8}$$

Note 1 to entry: If the output quantity has a linear relation to the input quantity, $c_i$ is a constant that can have any greater or lesser value. The $X_i$ relation can also be selected in the model so that $c_i = 1$.

**3.7**
**uncertainty**
parameter assigned to the result of a measurement or calculation which identifies the scattering of the values that can sensibly be assigned to the measured or calculated variable

Note 1 to entry: The uncertainty does not necessarily have to be a standard deviation.

**3.8**
**standard uncertainty**
*u*
*uncertainty* (3.7) of the result of a measurement or calculation expressed as a *standard deviation* (3.5)

Note 1 to entry: The standard uncertainty $u(x)$ of a variable $x$ has the same unit as $x$. The relative standard uncertainty $u(x)/(x)$ is dimensionless.

© ISO 2022 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

**3.9**
**combined standard uncertainty**
$u_c$
*standard uncertainty* (3.7) of a result $y$ that is obtained from $L$ values of other variables, $X_i$

Note 1 to entry: The combined standard uncertainty is equal to the positive square root of a sum of terms, whereby the terms are variances or co-variances of these other variables $X_i$, weighted according to the sensitivity coefficients $c_i$.

For a mathematical model of the measurand $Y = f(X_i)$ with uncorrelated input quantities $X_i$, the following applies in the first approximation:

$$u_c(y) = \sqrt{\sum_{i=1}^{L} c_i^2 u^2(x_i)} \tag{9}$$

The standard uncertainties $u(x_i)$ can be determined according to two types of evaluation (Type A and Type B evaluation, see ISO/IEC Guide 98-3).

**3.10**
**coverage factor**
$k$
factor by which the *combined standard uncertainty* (3.9), $u_c$, is multiplied to obtain the expanded uncertainty $U$

**3.11**
**coverage interval**
interval containing the set of true quantity values of a measurand with a stated probability, based on the information available

Note 1 to entry: A coverage interval does not need to be centred on the chosen measured quantity value (see ISO/IEC Guide 98-3:2008/Suppl.1).

Note 2 to entry: A coverage interval should not be termed "confidence interval" to avoid confusion with the statistical concept (see ISO/IEC Guide 98-3:2008, 6.2.2).

Note 3 to entry: A coverage interval can be derived from an expanded measurement uncertainty (see ISO/IEC Guide 98-3:2008, 2.3.5).

[SOURCE: ISO/IEC Guide 99:2007, 2.36]

**3.12**
**coverage probability**
probability that the set of true quantity values of a measurand is contained within a specified coverage interval

Note 1 to entry: This definition pertains to the uncertainty approach as presented in the GUM.

Note 2 to entry: The coverage probability is also termed "level of confidence" in the GUM.

[SOURCE: ISO/IEC Guide 99:2007, 2.37]

**3.13**
**expanded uncertainty**
$U$
product of the *coverage factor* (3.10), $k$ and the *combined standard uncertainty* (3.9), $u_c$, which describes the range $y \pm U$ around the result $y$, which can be expected to comprise a majority of the distribution of those values that can be reasonably attributed to the result:

$$U = ku_c \tag{10}$$


© ISO 2022 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

Note 1 to entry: In EN 12096, the expanded uncertainty is indicated by the letter *K*. It is used in the determination of the measured vibration value *a* and also indicates the dispersion in the production of batches of machines. The value *K*, however, does not include all uncertainty components.

**3.14**
**test subject**
person exposed to the vibration that is determined by a measuring body

Note 1 to entry: The test subject is also referred to as the operator, operating personnel or exposed person.

**3.15**
**measuring personnel**
persons responsible for performing the measurements, in particular managing the measuring instruments

**3.16**
**measuring body**
organizational unit that is responsible for conducting the measurements, in particular managing the measuring instruments and personnel

**3.17**
**reproducibility conditions**
conditions where test results are obtained with the same method on identical test items in different measuring bodies by different *measuring personnel* (3.15) using different equipment

Note 1 to entry: The method can define operating conditions, type and number of test subjects, or measurement environments, for example.

Note 2 to entry: The measurement time or the measurement object can vary depending on the problem or aim of the measurement; for example, if the measurement object is a workpiece that changes during measurement or if the influence of aging of a machine is to be determined.

[SOURCE: ISO 5725-1:1994, 3.18, modified — "Laboratory" replaced by "measuring body", "operator" replaced by "measuring personnel"]

**3.18**
**in-situ conditions**
*reproducibility conditions* (3.17) in the same measurement environment

Note 1 to entry: The measurement environment is influenced, for example, by the ambient temperature which can influence the conditions of the measuring instrumentation and measurement object.

**3.19**
**repeatability conditions**
conditions where independent test results are obtained with the same method on identical test items in the same *measuring body* (3.16) and measurement environment by the same member of *measuring personnel* (3.15) using the same equipment within short intervals of time

[SOURCE: ISO 5725-1:1994, 3.14, modified — "Laboratory" replaced by "measuring body and measurement environment", "operator" replaced by "member of measuring personnel" and Note 1 deleted]

**3.20**
**reproducibility standard deviation**
**measuring body standard deviation**
$\sigma_L$
*standard deviation* (3.5) of results obtained under *reproducibility conditions* (3.17)

Note 1 to entry: The measuring body standard deviation is also referred to as the measuring body or laboratory deviation or scattering.

© ISO 2022 – All rights reserved

Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022

Note 2 to entry: Depending on the measuring method, it is not always possible to create the same conditions. For example, ISO 20643 requires three different test subjects for vibration emission measurements. The reproducibility standard deviation then includes the test subject standard deviation.

Note 3 to entry: The measuring body standard deviation principally consists of the standard deviation of the measuring instrument and the standard deviation that results from the measurement strategy that is used. It therefore also includes interpretations of the measurement standard, for example with regard to the points of the transducer coupling and locations of the measurement point.

**3.21**
**in-situ standard deviation**
$\sigma_s$
standard deviation of results obtained under *in-situ conditions* (3.18)

**3.22**
**repeatability standard deviation**
$\sigma_r$
standard deviation of results obtained under *repeatability conditions* (3.19)

Note 1 to entry: According to ISO 5349-2, at least three individual measurements should be made.

**3.23**
**interlaboratory test**
series of measurements performed by different laboratories or measuring bodies under *reproducibility conditions* (3.17)

Note 1 to entry: Interlaboratory tests (sometimes referred to as "Round robin tests") can have very different objectives. For example, to verify a measurement method, to determine measurement uncertainties or to benchmark for a particular measuring body.

**3.24**
**specified value**
vibration value that is specified in a technical rule or required by law or otherwise that is to be complied with

Note 1 to entry: Depending on the context, the specified value is referred to as the limit value, action value, guidance value or threshold limit value.

**3.25**
**production standard deviation**
*standard deviation* (3.5) of results obtained under the same conditions for different new products of the same type of device or machine in a series

Note 1 to entry: With the exception of the product to be measured (for example machine or vehicle), all other conditions (measuring instrument, measuring body, measuring personnel, test subjects, measuring conditions and the measurement method and, if relevant, also the in-situ conditions) are the same.

Note 2 to entry: The production standard deviation is also referred to as the product scattering in EN 12096. However, the product scattering can also include the deviation due to aging.

**3.26**
**test subject standard deviation**
*standard deviation* (3.5) of results obtained under the same conditions, but with different *test subjects* (3.14)

Note 1 to entry: With the exception of the test subject (for example machine user or vehicle driver, all other conditions (machine, vehicle, measuring instrument, measuring body, measuring personnel, measuring conditions and the measurement method and, if relevant, also the in-situ conditions) are the same.

Note 2 to entry: If the individual measurements are not performed promptly, changes can occur in the same test subject, for example change of mass, change of behaviour or improved skill.


© ISO 2022 – All rights reserved
Documents
Document Sharing Hub
Full document details: PD ISO/TS 22704:2022