

Fixture Flow Rate Comparison Cross-Linked Polyethylene (PEX) Piping and Copper Tubing

Prepared for

**Plastics Pipe Institute, Inc.
105 Decker Court, Suite 825
Irving, Texas 75062**

Prepared by

**The NAHB Research Center
400 Prince George's Blvd.
Upper Marlboro, MD 20774**

June 2008



*America's Housing Technology
and Information Resource*

**Disclaimer**

Neither the NAHB Research Center, Inc., nor any person acting on its behalf, makes any warranty, express or implied, with respect to the use of any information, apparatus, method, or process disclosed in this publication or that such use may not infringe privately owned rights, or assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method, or process disclosed in this publication, or is responsible for statements made or opinions expressed by individual authors.

Table of Contents

List of Tables.....	3
List of Figures	3
Executive Summary	5
Background	5
Test Setup – Copper Tubing	5
Test Method	7
Results and Discussion.....	7
Conclusion	11

List of Tables

Table 1 – <i>Pressure and Flow Test Set</i>	7
Table 2 – <i>PEX 100-foot Flow Data</i>	9
Table 3 – <i>Copper 100-foot Flow Data</i>	10

List of Figures

Figure 1 – <i>100' to Test Fixture</i>	6
Figure 2 – <i>60' to Test Fixture</i>	6
Figure 3 – <i>Test Shower Valve</i>	7
Figure 4 – <i>Total System Flow at 40 PSI</i>	8
Figure 5 – <i>Total System Flow at 60 PSI</i>	8
Figure 6 – <i>Total System Flow at 80 PSI</i>	9
Figure 7 – <i>Time to Hot Water</i>	10

