



AEROSPACE RECOMMENDED PRACTICE

ARP1482™**REV. C**

Issued	1978-12
Revised	1999-10
Reaffirmed	2019-05
Stabilized	2026-01

Superseding ARP1482B

Recommendations for Fuel and Oil System Schematics

RATIONALE

During SAE-AE5 committee on March 27, 2025, it was proposed, after a Five-Year Review, to stabilize the current version of ARP1482C.

STABILIZED NOTICE

This document has been declared "STABILIZED" by SAE AE-5A Aerospace Fuel, Inerting and Lubrication Sys Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2026 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 1-877-606-7323 (U.S. and Canada only)
Tel: 1-724-776-4970 (outside U.S. and Canada)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE ARP1482C

For more information on this standard, visit
<https://www.sae.org/standards/content/ARP1482C/>

**Documents**

Document Sharing Hub

1. SCOPE:

This document recommends and sets forth a set of symbols representing the components making up aircraft fuel and oil systems. The intended result is uniformity in system schematics so that they may be easily understood throughout the aerospace industry.

1.1 Purpose:

This document defines a standard set of symbols for use in functional schematics of aircraft fuel and oil systems and components.

2. REFERENCES:

2.1 SAE Publications:

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

AS1290	Graphic Symbols for Aircraft Hydraulic and Pneumatic Systems
AIR1615	Thesaurus for Fuel System Components
AIR1660	Fuel Level Control Valves/Systems

3. SCHEMATIC:

For purposes of this document, a schematic is defined as a diagram descriptive of the functions and flow paths of a system or component. Such a schematic is intended only to provide a general understanding of the system or component depicted in an easily understood format. As such, portrayal of the physical positions and aspects of the components is not required and may, in fact, be undesirable.

4. COMPONENTS:

The following figures set forth the basic component symbols, as well as modifiers that specify drives and accessories.

5. SPECIAL COMPONENTS:

It is recognized that most systems will require the occasional use of unique components not described in this document. Where possible, these should be represented by combinations of the symbols herein. The resulting combination for a given component should be surrounded by a dashed line, if necessary to make it clear that it is a single component. Several examples of composite symbols are presented in the figures.

6. PLUMBING:

Tubing and hoses should be represented by solid double lines. Each line should be identified as to function by use of the appropriate cross-hatch code described in the figures. It is recommended that line size (outside diameter for tubing, inside diameter for hose) be specified in the format ØX.XX, suffixed with the appropriate material/type letter code listed in this document.

7. LEGENDS:

It is recommended that each system schematic contain a legend identifying the nomenclature of all symbols used. Numerical codes should be used to relate the symbols in the legend to the appropriate locations on the schematic.

8. COMPONENT DRAWINGS:

It is recommended that each component drawing include a schematic of the component represented thereon.

9. OTHER SYMBOLS AND SYSTEMS:

Refer to SAE AS1290 for symbols relevant to actuators, control valves, and other components associated with hydraulic and pneumatic systems.

10. NOMENCLATURE:

Refer to SAE AIR1660 and AIR1615 for definitions of the nomenclature used herein.

PREPARED UNDER THE JURISDICTION OF
SAE COMMITTEE AE-5, AEROSPACE FUEL, OIL & OXIDIZER SYSTEMS






<u>CODES FOR ELECTRICAL DRIVES:</u> AC MOTOR ACM DC MOTOR DCM STEPPER MOTOR SM TORQUE MOTOR TM AC SOLENOID ACS DC SOLENOID DCS	<u>CHECK VALVE:</u> 
<u>CODES FOR PNEUMATIC DRIVES:</u> AIR TURBINE MOTOR ATM AIR PRESSURE MOTOR APM	<u>SHUTOFF VALVES:</u> MANUAL  ACTUATED, NORMALLY-OPEN  ACTUATED, NORMALLY-CLOSED 
<u>CODES FOR HYDRAULIC DRIVES:</u> FUEL TURBINE MOTOR FTM HYDRAULIC MOTOR HM FUEL PRESSURE MOTOR FPM	<u>ROTARY VALVES:</u> BASIC SYMBOL  EXAMPLE- 3 WAY, 2 POSITION, DC MOTOR ACTUATED 
<u>CODES/SYMBOLS FOR MECHANICAL DRIVES:</u> ENGINE DRIVEN ED FLOAT ACTUATED  MANUAL  GRAVITY ACTUATED 	<u>LEVEL CONTROL SHUTOFF VALVES:</u> BASIC SYMBOLS INTEGRAL  REMOTE PILOT-OPERATED  flow direction →
<u>MISCELLANEOUS CODES:</u> NORMALLY-OPEN NO NORMALLY-CLOSED NC	

FIGURE 1