



AEROSPACE STANDARD

AS1975SUP1™**REV. A**

Issued	2001-01
Reaffirmed	2013-01
Cancelled	2025-12

Superseded by AS1975

Hose Assembly, Polytetrafluoroethylene, Para-Aramid Reinforced,
3000/4000 psi, 275 °F, Standard Duty, Hydraulic, Aircraft Systems
(Supplement 1)

RATIONALE

This content has been completely superseded by AS1975, section 2.2.1.

CANCELLATION NOTICE

This technical report has been declared "CANCELLED" as of December 2025 and has been superseded by AS1975. By this action, this document will remain listed in the respective index, if applicable. Cancelled technical reports are available from SAE.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2025 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 1-877-606-7323 (U.S. and Canada only)
Tel: 1-724-776-4970 (outside U.S. and Canada)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE AS1975SUP1A

For more information on this standard, visit
<https://www.sae.org/standards/content/AS1975SUP1A/>

Documents

Standard Sharing Hub

1. SCOPE:

This supplement forms a part of AS1975, Hose Assembly, Polytetrafluoroethylene, Para-Aramid Reinforced, 3000/4000 psi, 275 °F, Standard Duty, Hydraulic, Aircraft Systems and shall be used to identify hose assembly standards citing this procurement specification.

2. REFERENCE DOCUMENTS:

CLASS 3000:

AS4568	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, Straight to Straight
AS4569	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, Straight to 45°
AS4570	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, Straight to 90°
AS4571	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, 45° to 90°
AS4572	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, 45° to 45°
AS4573	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Flareless, 90° to 90°
AS4574	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Beam Seal, Straight to Straight
AS4575	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Beam Seal, Straight to 45°
AS4576	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Beam Seal, Straight to 90°
AS4577	Hose Assembly, PTFE, Para-Aramid Reinforced, Standard Duty, 3000 psi, 275°F, Titanium Fittings, Beam Seal, 45° to 45°