

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


REV. C	FEDERAL SUPPLY CLASS 5310	
	RATIONALE THIS STANDARD IS TO BE CANCELLED AND SUPERSEDED BY AS6146. CANCELLATION NOTICE THIS TECHNICAL REPORT HAS BEEN DECLARED "CANCELLED" AS OF SEPTEMBER, 2020 AND HAS BEEN SUPERSEDED BY AS6146. BY THIS ACTION, THIS DOCUMENT WILL REMAIN LISTED IN THE RESPECTIVE INDEX, IF APPLICABLE. CANCELLED TECHNICAL REPORTS ARE AVAILABLE FROM SAE. UNLESS OTHERWISE SPECIFIED, PART INVENTORY MANUFACTURED TO PREVIOUS REVISIONS OF THE APPLICABLE DRAWING OR SPECIFICATION MAY BE PROCURED AND USED UNTIL STOCK IS DEPLETED.	
AS3067™	For more information on this standard, visit https://www.sae.org/standards/content/AS3067C/ THIRD ANGLE PROJECTION 	
CUSTODIAN: E-25		PROCUREMENT SPECIFICATION: NONE
	AEROSPACE STANDARD NUT, SELF-LOCKING, DOUBLE HEXAGON, REDUCED ENVELOPE, AS7251	AS3067™ REV. C



TABLE 1A

IDENTIFICATION NUMBER	THREAD T	A Inch	A (mm)	B Inch	B (mm)	C Inch	C (mm)	D Inch	D (mm)	E Inch	E (mm)
AS3067-08	.164-36UNJF-3B	.2188	5.558	.070	1.78	.294	7.46	.230-.250	5.85 - 6.35	.264	6.71
AS3067-09	.190-32UNJF-3B	.2500	6.350	.070	1.78	.355	9.01	.230-.250	5.85 - 6.35	.325	8.26
AS3067-10	.250-28UNJF-3B	.3125	7.938	.095	2.42	.450	11.43	.308-.328	7.83 - 8.33	.410	10.42
AS3067-11	.3125-24UNJF-3B	.3750	9.525	.108	2.75	.535	13.58	.340-.360	8.64 - 9.14	.495	12.58
AS3067-12	.375-24UNJF-3B	.4375	11.112	.147	3.74	.608	15.44	.438-.458	11.13-11.63	.559	14.20
AS3067-13	.4375-20UNJF-3B	.5625	14.288	.150	3.81	.692	17.57	.449-.469	11.41-11.91	.652	16.57
AS3067-14	.500-20UNJF-3B	.6250	15.875	.176	4.48	.786	19.96	.548-.568	13.92-14.42	.746	18.95
AS3067-15	.5625-18UNJF-3B	.6875	17.462	.205	5.21	.880	22.35	.613-.633	15.58-16.07	.840	21.34