

A REAFFIRMED STATUS IS GIVEN TO TECHNICAL REPORTS THAT HAVE BEEN REVIEWED BY THE TECHNICAL COMMITTEE AND DEEMED TO BE CURRENT WITH NO NEED FOR IMMEDIATE REVISION. NO CHANGES HAVE BEEN MADE TO THIS DOCUMENT AS A RESULT OF THIS REVIEW.



TABLE 1 - PART NUMBERS, DIMENSIONS, AND APPROX. MASS

PART NUMBER	L	G MIN	K MAX	APPROX MASS
				LB/100
AS3112-14	1.438	.030	.188	10.69
AS3112-15	1.500	.090	.250	10.99
AS3112-16	1.562	.152	.312	11.30
AS3112-17	1.625	.215	.375	11.61
AS3112-18	1.688	.278	.438	11.92
AS3112-19	1.750	.340	.500	12.22
AS3112-20	1.812	.402	.562	12.53
AS3112-21	1.875	.465	.625	12.84
AS3112-22	1.938	.528	.688	13.14
AS3112-23	2.000	.590	.750	13.45
AS3112-24	2.125	.715	.875	14.07
AS3112-25	2.250	.840	1.000	14.68
AS3112-26	2.375	.965	1.125	15.30
AS3112-27	2.500	1.090	1.250	15.91
AS3112-28	2.625	1.215	1.375	16.52
AS3112-29	2.750	1.340	1.500	17.14
AS3112-30	2.875	1.465	1.625	17.75
AS3112-31	3.000	1.590	1.750	18.37
AS3112-32	3.125	1.715	1.875	18.98
AS3112-33	3.250	1.840	2.000	19.60
AS3112-34	3.375	1.965	2.125	20.21
AS3112-35	3.500	2.090	2.250	20.83
AS3112-36	3.625	2.215	2.375	21.44
AS3112-37	3.750	2.340	2.500	22.05
AS3112-38	3.875	2.465	2.625	22.67
AS3112-39	4.000	2.590	2.750	23.28
AS3112-40	4.125	2.715	2.875	23.90
AS3112-41	4.250	2.840	3.000	24.51
AS3112-42	4.375	2.965	3.125	25.13
AS3112-43	4.500	3.090	3.250	25.74
AS3112-44	4.625	3.125	3.375	26.36
AS3112-45	4.750	3.340	3.500	26.97
AS3112-46	4.875	3.465	3.625	27.59
AS3112-47	5.000	3.590	3.750	28.20
AS3112-48	5.125	3.715	3.875	28.81
AS3112-49	5.250	3.840	4.000	29.43
AS3112-50	5.375	3.965	4.125	30.04
AS3112-51	5.500	4.090	4.250	30.66
AS3112-52	5.625	4.215	4.375	31.27
AS3112-53	5.750	4.340	4.500	31.89
AS3112-54	5.785	4.465	4.625	32.50
AS3112-55	6.000	4.590	4.750	33.12

NOTE: FOR SHORT BOLTS THREADED TO HEAD, REFER TO AS9505.

	AEROSPACE STANDARD	AS3112™ SHEET 2 OF 3	REV. B
	BOLT, MACHINE - HEXAGON HEAD, DRILLED 1 HOLE, PD SHANK, CRES (UNS S66286), .5000-20 UNJF-3A		



Documents

Document Sharing Hub