

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

FIGURE REDRAWN TO SHOW CORRECT THREAD END CHAMFER AND LIGHTENING HOLE DIMENSIONS TO AS1132.




TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	G MIN	K MAX	APPROX MASS LB/100	PART NO.	L	G MIN	K MAX	APPROX MASS LB/100
AS3151-03	.875-.895	.088	.198	3.51	AS3151-45	3.499-3.519	2.712	2.822	9.91
AS3151-04	.937-.957	.150	.260	3.67	AS3151-46	3.562-3.582	2.775	2.885	10.07
AS3151-05	.999-1.019	.212	.322	3.81	AS3151-47	3.625-3.645	2.838	2.948	10.23
AS3151-06	1.062-1.082	.275	.385	3.97	AS3151-48	3.687-3.707	2.900	3.010	10.37
AS3151-07	1.125-1.145	.338	.448	4.13	AS3151-49	3.749-3.769	2.962	3.072	10.53
AS3151-08	1.187-1.207	.400	.510	4.28	AS3151-50	3.812-2.832	3.025	3.135	10.69
AS3151-09	1.249-1.269	.462	.572	4.43	AS3151-51	3.875-3.895	3.088	3.198	10.84
AS3151-10	1.312-1.332	.525	.635	4.58	AS3151-52	3.937-3.957	3.150	3.260	10.98
AS3151-11	1.375-1.395	.588	.698	4.74	AS3151-53	3.999-4.019	3.212	3.322	11.14
AS3151-12	1.437-1.457	.650	.760	4.88	AS3151-54	4.062-4.082	3.275	3.385	11.30
AS3151-13	1.499-1.519	.712	.822	5.04	AS3151-55	4.125-4.145	3.338	3.448	11.44
AS3151-14	1.562-1.582	.775	.885	5.19	AS3151-56	4.187-4.207	3.400	3.510	11.60
AS3151-15	1.625-1.645	.838	.948	5.35	AS3151-57	4.249-4.269	3.462	3.572	11.75
AS3151-16	1.687-1.707	.900	1.010	5.50	AS3151-58	4.312-4.332	3.525	3.635	11.91
AS3151-17	1.749-1.769	.962	1.072	5.65	AS3151-59	4.375-4.395	3.588	3.698	12.05
AS3151-18	1.812-1.832	1.025	1.135	5.81	AS3151-60	4.437-4.457	3.650	3.760	12.21
AS3151-19	1.875-1.895	1.088	1.198	5.95	AS3151-61	4.499-4.519	3.712	3.822	12.35
AS3151-20	1.937-1.957	1.150	1.260	6.10	AS3151-62	4.562-4.582	3.775	3.885	12.51
AS3151-21	1.999-2.019	1.212	1.322	6.26	AS3151-63	4.625-4.645	3.838	3.948	12.67
AS3151-22	2.062-2.082	1.275	1.385	6.41	AS3151-64	4.687-4.707	3.900	4.010	12.82
AS3151-23	2.125-2.145	1.338	1.448	6.57	AS3151-65	4.749-4.769	3.962	4.072	12.97
AS3151-24	2.187-2.207	1.400	1.510	6.72	AS3151-66	4.812-4.832	4.025	4.135	13.12
AS3151-25	2.249-2.269	1.462	1.572	6.88	AS3151-67	4.875-4.895	4.088	4.198	13.28
AS3151-26	2.312-2.332	1.525	1.635	7.02	AS3151-68	4.937-4.957	4.150	4.260	13.42
AS3151-27	2.375-2.395	1.588	1.698	7.17	AS3151-69	4.999-5.019	4.212	4.322	13.58
AS3151-28	2.437-2.457	1.650	1.760	7.33	AS3151-70	5.062-5.082	4.275	4.385	13.73
AS3151-29	2.499-2.519	1.712	1.822	7.48	AS3151-71	5.125-5.145	4.338	4.448	13.89
AS3151-30	2.562-2.582	1.775	1.885	7.63	AS3151-72	5.187-5.207	4.400	4.510	14.04
AS3151-31	2.625-2.645	1.838	1.948	7.79	AS3151-73	5.249-5.269	4.462	4.572	14.19
AS3151-32	2.687-2.707	1.900	2.010	7.94	AS3151-74	5.312-5.332	4.525	4.635	14.35
AS3151-33	2.749-2.769	1.962	2.072	8.09	AS3151-75	5.375-5.395	4.588	4.698	14.49
AS3151-34	2.812-2.832	2.025	2.135	8.24	AS3151-76	5.437-5.457	4.650	4.760	14.65
AS3151-35	2.875-2.895	2.088	2.198	8.39	AS3151-77	5.499-5.519	4.712	4.822	14.80
AS3151-36	2.937-2.957	2.150	2.260	8.55	AS3151-78	5.562-5.582	4.775	4.885	14.95
AS3151-37	2.999-3.019	2.212	2.322	8.70					
AS3151-38	3.062-3.082	2.275	2.385	8.86					
AS3151-39	3.125-3.145	2.338	2.448	9.00					
AS3151-40	3.187-3.207	2.400	2.510	9.16					
AS3151-41	3.249-3.269	2.462	2.572	9.31					
AS3151-42	3.312-3.332	2.525	2.635	9.46					
AS3151-43	3.375-3.395	2.588	2.698	9.62					
AS3151-44	3.437-3.457	2.650	2.760	9.77					



AEROSPACE STANDARD

BOLT, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, CLOSE TOLERANCE SHANK,
AMS4967 (UNS R56400), 160 KSI, .4375-20 UNJF-3A

AS3151™
SHEET 2 OF 3

REV.
B



Documents

Document Sharing Hub