

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."



TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100	PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3174-03	.597- .617	.126	.198	.86	AS3174-30	2.284-2.304	1.812	1.885	2.18
AS3174-04	.659- .679	.188	.260	.91	AS3174-31	2.347-2.367	1.876	1.948	2.23
AS3174-05	.721- .741	.250	.322	.95	AS3174-32	2.409-2.429	1.938	2.010	2.28
AS3174-06	.784- .804	.312	.385	1.01	AS3174-33	2.471-2.491	2.000	2.072	2.32
AS3174-07	.847- .867	.376	.448	1.06	AS3174-34	2.534-2.554	2.062	2.135	2.38
AS3174-08	.909- .929	.438	.510	1.11	AS3174-35	2.597-2.617	2.126	2.198	2.43
AS3174-09	.971- .991	.500	.572	1.15	AS3174-36	2.659-2.679	2.188	2.260	2.48
AS3174-10	1.034-1.054	.562	.635	1.20	AS3174-37	2.721-2.741	2.250	2.322	2.52
AS3174-11	1.097-1.117	.626	.698	1.25	AS3174-38	2.784-2.804	2.312	2.385	2.58
AS3174-12	1.159-1.179	.688	.760	1.29	AS3174-39	2.847-2.867	2.376	2.448	2.62
AS3174-13	1.221-1.241	.750	.822	1.35	AS3174-40	2.909-2.929	2.438	2.510	2.67
AS3174-14	1.284-1.304	.812	.885	1.40	AS3174-41	2.971-2.991	2.500	2.572	2.72
AS3174-15	1.347-1.367	.876	.948	1.45	AS3174-42	3.034-3.054	2.562	2.635	2.77
AS3174-16	1.409-1.429	.938	1.010	1.49	AS3174-43	3.097-3.117	2.626	2.698	2.82
AS3174-17	1.471-1.491	1.000	1.072	1.54	AS3174-44	3.159-3.179	2.688	2.760	2.86
AS3174-18	1.534-1.554	1.062	1.135	1.60	AS3174-45	3.221-3.241	2.750	2.822	2.91
AS3174-19	1.597-1.617	1.126	1.198	1.64	AS3174-46	3.284-3.304	2.812	2.885	2.97
AS3174-20	1.659-1.679	1.188	1.260	1.69	AS3174-47	3.347-3.367	2.876	2.948	3.01
AS3174-21	1.721-1.741	1.250	1.322	1.74	AS3174-48	3.409-3.429	2.938	3.010	3.06
AS3174-22	1.784-1.804	1.312	1.385	1.79	AS3174-49	3.471-3.491	3.000	3.072	3.11
AS3174-23	1.847-1.867	1.376	1.448	1.84	AS3174-50	3.534-3.554	3.062	3.135	3.17
AS3174-24	1.909-1.929	1.438	1.510	1.89	AS3174-51	3.597-3.617	3.126	3.198	3.21
AS3174-25	1.971-1.991	1.500	1.572	1.94	AS3174-52	3.659-3.679	3.188	3.260	3.26
AS3174-26	2.034-2.054	1.562	1.635	1.98	AS3174-53	3.721-3.741	3.250	3.322	3.31
AS3174-27	2.097-2.117	1.626	1.698	2.03	AS3174-54	3.784-3.804	3.312	3.385	3.35
AS3174-28	2.159-2.179	1.688	1.760	2.08	AS3174-55	3.847-3.867	3.376	3.448	3.40
AS3174-29	2.221-2.241	1.750	1.822	2.13					



AEROSPACE STANDARD

BOLT, MACHINE - DOUBLE HEX EXTENDED
WASHER HEAD, DRILLED, CLOSE TOL SHANK,
AMS5643 (UNS S17400), 140 KSI, .1900-32 UNJF-3A

AS3174™
SHEET 2 OF 3

REV.
B
Documents



Document Sharing Hub