

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
B

AS34041™

FEDERAL SUPPLY CLASS
5935

RATIONALE

AS34041B HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF SAE AS50151.





FIGURE 1 – CONNECTOR CONFIGURATIONS (CLASSES D, L, U & W ENVIRONMENT RESISTANT)

For more information on this standard, visit
<https://www.sae.org/standards/content/AS34041B>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8C1

PROCUREMENT SPECIFICATION: AS50151



AEROSPACE STANDARD

CONNECTORS, RECEPTACLE, ELECTRIC,
JAM NUT MOUNTING, FRONT RELEASE,
CRIMP CONTACT, AN TYPE

AS34041™
SHEET 1 OF 4

REV.
B

Documents

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1 - DIMENSIONS

SIZE	L MAX.		M ± .005	N + .000 - .005	O + .015 - .000	S ± .005	T ± .010 FLATS	Z ± .005
	SIZE 16 & 12 CONTACTS	SIZE 8, 4 & 0 CONTACTS						
8S	2.031	N/A	.720	.500	.505	1.072	.865	.326
10S				.625	.630	1.193	.990	.385
10SL				.625	.630	1.193	.990	.385
12S				.750	.755	1.317	1.050	.448
12	2.125		.966	.750	.755	1.317	1.050	.448
14S	2.031		.720	.875	.880	1.443	1.175	.510
14	2.125		.966	.875	.880	1.443	1.175	.510
16S	2.031		.720	1.000	1.005	1.567	1.300	.573
16	2.125	2.500	.966	1.000	1.005	1.567	1.300	.573
18				1.125	1.130	1.693	1.425	.635
20				1.250	1.255	1.817	1.550	.698
22				1.375	1.380	1.943	1.550	.760
24				1.500	1.505	2.067	1.800	.823
28				1.750	1.755	2.317	1.925	.948
32				2.000	2.005	2.567	2.175	1.073
36				2.250	2.255	2.817	2.550	1.198
40				2.500	2.505	3.061	2.800	1.323
44				2.750	2.755	3.311	3.050	1.448
48				3.000	3.005	3.561	3.300	1.573

**AEROSPACE STANDARD**
 CONNECTORS, RECEPTACLE, ELECTRIC,
 JAM NUT MOUNTING, FRONT RELEASE,
 CRIMP CONTACT, AN TYPE

AS34041™
 SHEET 2 OF 4
REV.**B****Documents**

Document Sharing Hub