

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
A

AS3508™

FEDERAL SUPPLY CLASS
5340

RATIONALE

REVISE THREAD SPECIFICATION TO AS8879. ADD MAX RAD TO BOTTOM OF CBORE, ADD ANSI Y14.5M-1982. REVISE COUNTERBORE DEPTH, DIM F, FOR HOLES WITH SERRATIONS, REVISE DIM B TOLERANCE, ADD NOTE FOR FULL THREAD DEPTH IN BLIND HOLES, GENERAL EDITORIAL UPDATE INCLUDING FIGURE 1 REDRAWN UPDATED AND TABLE 1 FORMAT UPDATED.

AS3508A HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1 - INSERT INSTALLATION HOLE PREPARATION

For more information on this standard, visit
<https://www.sae.org/standards/content/AS3508A/>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: NONE



AEROSPACE STANDARD

INSERT - THIN WALL,
SHORT AND LONG
HOLE PREPARATION FOR

AS3508™
SHEET 1 OF 3

REV.
A

Copyright © 2026 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 1-877-606-7323 (U.S. and Canada only)
Fax: 724-776-0790

Tel: 1-724-776-4970 (outside U.S. and Canada)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1A - IDENTIFICATION NUMBERS AND DIMENSIONS A, ØB, ØC, ØD, ØE, F, AND G

AS IDENT NUMBER	A THREAD AS8879	ØB TAP HOLE	ØC	ØD SERRATION MAJOR Ø	ØE	F CBORE DEPTH WITH SERRATIONS /5/	F CBORE DEPTH WITHOUT SERRATIONS /5/	G SERRATION DEPTH /5/
AS3508-01	.2500-28 UNJF-3B	.220-.226	.249-.254	.264-.269	.291-.303	.096-.107	.077-.087	.067-.087
AS3508-02	.3125-24 UNJF-3B	.280-.286	.311-.316	.334-.339	.358-.370	.096-.107	.077-.087	.067-.087
AS3508-03	.3750-24 UNJF-3B	.342-.348	.374-.379	.400-.405	.425-.437	.096-.107	.077-.087	.067-.087
AS3508-04	.4375-20 UNJF-3B	.403-.409	.436-.441	.457-.462	.480-.492	.128-.138	.108-.118	.098-.118
AS3508-05	.5000-20 UNJF-3B	.467-.473	.499-.504	.523-.528	.547-.559	.128-.138	.108-.118	.098-.118
AS3508-06	.5625-24 UNJEF-3B	.530-.536	.561-.566	.580-.585	.606-.618	.128-.138	.108-.118	.098-.118

TABLE 1B - AS IDENT NUMBERS AND DIMENSIONS H, J, AND ØK

AS IDENT NUMBER	H MIN THREAD DEPTH FOR AS3504 /8/	H MIN THREAD DEPTH FOR AS3505 /8/	J	ØK MIN BOSS DIA FOR AS3504 /6/	ØK MIN BOSS DIA FOR AS3505 /6/
AS3508-01	.325	.510	20	.410	.490
AS3508-02	.415	.630	24	.470	.550
AS3508-03	.505	.755	29	.540	.620
AS3508-04	.595	.910	34	.600	.680
AS3508-05	.695	1.035	39	.660	.740
AS3508-06	.785	1.160	44	.720	.800



AEROSPACE STANDARD

 INSERT - THIN WALL,
 SHORT AND LONG
 HOLE PREPARATION FOR

 AS3508™
 SHEET 2 OF 3

REV. A



Documents

Document Sharing Hub