

REV.
A

AS38999/40

CANCELLATION NOTICE

THIS DOCUMENT HAS BEEN DECLARED "CANCELLED" AS OF SEPTEMBER 2000. BY THIS ACTION, THIS DOCUMENT WILL REMAIN LISTED IN THE NUMERICAL SECTION OF THE AEROSPACE STANDARDS INDEX.


NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION DOD-C-38999/40, AMENDMENT 3 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE DOD-C-38999/40, AMENDMENT 3. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

THIRD ANGLE PROJECTION



ISSUED 1998-08 CANCELLED 2000-09

PREPARED BY SAE SUBCOMMITTEE AE-8C1

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

CONNECTORS, ELECTRICAL, CIRCULAR, MINIATURE, HIGH DENSITY, QUICK DISCONNECT (BAYONET, THREADED, AND BREECH COUPLING), ENVIRONMENTAL RESISTANT, REMOVABLE CRIMP AND HERMETIC SOLDER CONTACTS, RECEPTACLE, WALL MOUNTING FLANGE, BREECH COUPLING, REMOVABLE CRIMP CONTACTS, SERIES IV, METRIC


AS38999/40
SHEET 1 OF 3

REV.
A

REV.
A

AS38999/40

THE COMPLETE REQUIREMENTS FOR PROCURING THE CONNECTORS DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF SPECIFICATION MIL-C-38999.



Shell Size	Shell Size Code	P DIA	R BSC	S	T DIA	V	W	Z MAX
11	B	3.5 3.1	10.31	26.7 25.6	20.15 19.76	20.8 19.2	2.6 2.1	32.0
13	C		11.51	29.1 28.0	23.35 22.96			
15	D		12.31	31.5 30.4	26.52 26.13			
17	E		13.49	33.9 32.8	29.72 29.33			
19	F		14.68	37.1 36.0	32.87 32.48			
21	G		15.88	40.2 39.1	36.05 35.66			
23	H	4.0 3.6	17.46	43.4 42.3	39.22 38.83	3.4 2.9		
25	J		19.05	46.6 45.5	42.40 42.01			

NOTE: Dimensions are in millimeters.

FIGURE 1. RECEPTACLE, CLASSES C, F, K, S, AND W. (CLASS K SHALL NOT BE FOR AIR FORCE USE).

REQUIREMENTS:

DIMENSIONS AND CONFIGURATIONS: SEE FIGURE 1. INTERFACE DIMENSIONS SHALL CONFORM TO MIL-C-38999.

THIS CONNECTOR MATES WITH: DOD-C-38999/46 AND /47.

MAIN KEY COLOR: BLUE.

FOR INSERT ARRANGEMENTS: SEE MIL-STD-1560.

AEROSPACE STANDARD

CONNECTORS, ELECTRICAL, CIRCULAR, MINIATURE, HIGH DENSITY, QUICK DISCONNECT (BAYONET, THREADED, AND BREECH COUPLING), ENVIRONMENTAL RESISTANT, REMOVABLE CRIMP AND HERMETIC SOLDER CONTACTS, RECEPTACLE, WALL MOUNTING FLANGE, BREECH COUPLING, REMOVABLE CRIMP CONTACTS, SERIES IV, METRIC