

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
B

AS39029™/71

FEDERAL SUPPLY CLASS
5935

RATIONALE


AS39029/71B IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULT IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. QUALIFIED SUPPLIERS ARE STILL MAINTAINED.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8C1 CONNECTORS COMMITTEE AND WILL NO LONGER BE SUBJECT TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

For more information on this standard, visit
<https://www.sae.org/standards/content/AS39029/71B/>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8C1

PROCUREMENT SPECIFICATION: AS39029



AEROSPACE STANDARD

CONTACTS, ELECTRICAL CONNECTOR, PIN, REMOVABLE,
SOLDERLESS WRAPPOST TERMINATION (FOR MIL-DTL-38999
SERIES I, II, III, AND IV, MIL-DTL-24308, MIL-DTL-83733,
AND MIL-DTL-55302/69 CONNECTORS)

AS39029™/71

REV.
B



Documents

Copyright © 2026 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 1-877-606-7323 (U.S. and Canada only)

Fax: 724-776-0790


Tel: 1-724-776-4970 (outside U.S. and Canada)

Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

NOTICE

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF SAE AS39029.



BIN CODE	A	B	C
390	.205 (5.21) .200 (5.08)	.344 (8.74) .338 (8.59)	.538 (13.67) REF
391	.306 (7.77) .302 (7.67)	.237 (6.02) .231 (5.87)	.538 (13.67) REF
392	.355 (9.02) .340 (8.64)	.340 (8.64) REF	.685 (17.40) .675 (17.15)

FIGURE 1 - CONFIGURATION AND DIMENSIONS



AEROSPACE STANDARD

CONTACTS, ELECTRICAL CONNECTOR, PIN, REMOVABLE,
SOLDERLESS WRAPPOST TERMINATION (FOR MIL-DTL-38999
SERIES I, II, III, AND IV, MIL-DTL-24308, MIL-DTL-83733,
AND MIL-DTL-55302/69 CONNECTORS)

AS39029™/71
SHEET 1 OF 3

REV.
B



Documents

Document Sharing Hub