

AS4215

FEDERAL SUPPLY CLASS
4730

RATIONALE

AS4215 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1 - FITTING, BEAM SEAL, EXTERNAL THREAD, EXTERNAL SWAGE TUBE END

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS4215 /16/ SIZE CODE	NOMINAL TUBE SIZE	A ±.015	B +.000 -.003	C	D	G BORE DEPTH ±.015	H	J	V /3/	AA /2/	LB/EA MAX CRES	LB/EA MAX TI
03	.188	1.129	.275	.195 - .198	.361	.773	.371 - .378	.896	.170 - .220	.13	.0170	.0100
04	.250	1.306	.338	.257 - .260	.424	.938	.434 - .441	1.031	.190 - .240	.22	.0230	.0130
05	.312	1.349	.413	.319 - .322	.486	.955	.496 - .503	1.074	.200 - .250	.22	.0330	.0190
06	.375	1.356	.480	.382 - .385	.549	1.000	.558 - .565	1.061	.220 - .270	.22	.0450	.0250
08	.500	2.078	.655	.508 - .511	.736	1.578	.746 - .753	1.770	.410 - .435	.50	.0840	.0360
10	.625	2.104	.787	.633 - .636	.861	1.577	.871 - .878	1.732	.410 - .435	.50	.0800	.0510
12	.750	2.184	.929	.758 - .761	1.048	1.587	1.058 - 1.065	1.772	.365 - .390	.50	.181	.103
16	1.000	2.630	1.257	1.008 - 1.011	1.476	1.748	1.484 - 1.516	2.170	.325 - .350	.50	.259	.147
20	1.250	2.819	1.489	1.258 - 1.262	1.599	1.850	1.609 - 1.641	2.362	.325 - .350	.50	.436	.249
24	1.500	2.759	1.786	1.513 - 1.517	2.095	1.975	2.105 - 2.145	2.217	.325 - .350	.50	.646	.368

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS4215>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: /6/ AS4459



AEROSPACE STANDARD

FITTING, ADAPTER, BEAM SEAL, EXTERNAL THREAD
EXTERNAL SWAGE TUBE END, HYDRAULIC,
3000 PSI

AS4215
SHEET 1 OF 2

Documents

Copyright 2015 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

NOTES:

- /1/ MATERIAL:
 - a. CODE LETTER "-": 21-6-9 CRES BAR PER AMS 5656
 - b. CODE LETTER "E": COMMERCIALLY PURE TITANIUM BAR PER AMS 4921
2. HEAT TREATMENT: PER PROCUREMENT SPECIFICATIONS.
- /3/ FINISH:
 - a. MATERIAL CODE LETTER "-": PASSIVATE THE WHOLE PART PER QQ-P-35 TYPE VII. PTFE COAT (COLOR GREEN) FITTING ID TO "V" DEPTH. OVERSPRAY ON /Y/ PERMISSIBLE.
 - b. MATERIAL CODE LETTER "E": PTFE COAT (COLOR BLACK) EXTERNAL OD AS NOTED AND THE ID TO "V" DEPTH. ϕ AA FREE OF PTFE COATING. SOLID FILM LUBRICATE AS NOTED. FLUORIDE PHOSPHATE COAT THREADS (ENTIRE PART OPTIONAL) PER AMS 2486.
- /4/ FILL OUTER GROOVE WITH SILICONE ELASTOMER.
- /5/ SOLID FILM LUBRICANT: APPLY PER AS1701.
- /6/ PROCUREMENT SPECIFICATIONS: AS4459 AND MIL-F-85421. THIS PART SHALL BE QUALIFIED TO THE PROCUREMENT SPECIFICATIONS IN A COMPLETE ASSEMBLY. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.
7. PACKAGING: INDIVIDUALLY PACKAGE IN CLEAN CONTAINER WITH IDENTIFICATION PER AS4459.
8. SPECIFIC DIMENSIONS AND TOLERANCES NOT DEFINED ON THIS STANDARD SHALL BE SPECIFIED AND CONTROLLED BY THE MANUFACTURER. THE MANUFACTURER IS RESPONSIBLE TO INSURE COMPATIBILITY WITH THE ASSEMBLY AND COMPLIANCE WITH THE REQUIREMENTS OF THE APPLICABLE PROCUREMENT SPECIFICATIONS.
9. INTENDED USE: PER AS4459.
- /10/ IDENTIFICATION: PARTS SHALL BE IDENTIFIED IN THE AREA SHOWN PER AS4459.
11. INTERPRETATION OF DRAWING PER ARP4296.
12. SURFACE TEXTURE: SYMBOLS PER ANSI Y14.36; REQUIREMENT PER ANSI/ASME B46.1. UNLESS OTHERWISE SPECIFIED, MACHINED SURFACES TO BE 125 μ in Ra.
13. BREAK EDGES .003 TO .015 UNLESS OTHERWISE SPECIFIED.
14. DIMENSIONING AND TOLERANCING: ASME Y14.5M-1994
15. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS $\pm$.010, ANGULAR DIMENSIONS $\pm$ 2°.
- /16/ EXAMPLE OF PART NUMBER: AS4215 E 08 W N

BASIC PART NUMBER _____	N = EXTERIOR PTFE NOT REQUIRED (TITANIUM ONLY)
MATERIAL CODE LETTER /1/ _____	
SIZE CODE _____	BLANK = EXTERIOR PTFE REQUIRED
TUBE SIZE IN _____	W = TWO SAFETY WIRE HOLES REQUIRED
.062 in INCREMENTS	
(08 = .500 in)	X = SAFETY WIRE HOLES OPTIONAL