

AS4219

FEDERAL SUPPLY CLASS
4730

RATIONALE

AS4219 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1 - ELBOW, 45°, BEAM SEAL, BULKHEAD

TABLE 1 - DIMENSIONS AND WEIGHTS

BASIC NO. AS4219 /16/ SIZE CODE	NOMINAL TUBE SIZE	A ±.015	B ±.015	C	D +.000 -.003	F ±.015	G BORE DEPTH +.030 -.000	V /3/	AA /2/	LB/EA MAX CRES	LB/EA MAX TI
03	.188	.915	1.130	.195 - .198	.275	.325	.773	.170 - .220	.13	.0350	.0200
04	.250	1.065	1.118	.257 - .260	.338	.390	.915	.190 - .240	.22	.0550	.0320
05	.312	1.195	1.242	.319 - .322	.413	.465	.955	.200 - .250	.22	.0750	.0430
06	.375	1.276	1.392	.382 - .385	.480	.545	.990	.220 - .270	.22	.0980	.0570
08	.500	1.799	1.569	.508 - .511	.655	.705	1.493	.410 - .435	.50	.191	.109
10	.625	1.940	1.667	.633 - .636	.787	.861	1.533	.410 - .435	.50	.294	.167
12	.750	2.047	2.053	.758 - .761	.929	1.036	1.603	.365 - .390	.50	.399	.227
16	1.000	2.575	2.074	1.008 - 1.011	1.257	1.380	1.748	.325 - .350	.50	.694	.395
20	1.250	2.684	2.440	1.258 - 1.262	1.489	1.692	1.850	.325 - .350	.50	.944	.555
24	1.500	2.778	2.788	1.513 - 1.517	1.786	1.880	1.975	.325 - .350	.50	1.71	.981

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS4219>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: /6/ AS4459



AEROSPACE STANDARD

FITTING, ELBOW, 45°, BEAM SEAL,
BULKHEAD, EXTERNAL SWAGE TUBE
END, HYDRAULIC, 3000 PSI

AS4219
SHEET 1 OF 2

Documents

NOTES:

- /1/ MATERIAL:
- CODE LETTER "A": 21-6-9 CRES BAR OR FORGINGS PER AMS 5656
 - CODE LETTER "E": COMMERCIALLY PURE TITANIUM BAR OR FORGINGS PER AMS 4921
2. HEAT TREATMENT: PER PROCUREMENT SPECIFICATIONS.
- /3/ FINISH:
- MATERIAL CODE LETTER "A": PASSIVATE THE WHOLE PART PER QQ-P-35 TYPE VII. PTFE COAT (COLOR GREEN) FITTING ID TO "V" DEPTH. OVERSPRAY ON /Y/ PERMISSIBLE.
 - MATERIAL CODE LETTER "E": PTFE COAT (COLOR BLACK) EXTERNAL OD AS NOTED AND THE ID TO "V". ϕ AA FREE OF PTFE COATING. SOLID FILM LUBRICATE AS NOTED. FLUORIDE PHOSPHATE COAT THREADS (ENTIRE PART OPTIONAL) PER AMS 2486.
- /4/ FILL OUTER GROOVE WITH SILICONE ELASTOMER.
- /5/ SOLID FILM LUBRICANT: APPLY PER AS1701.
- /6/ PROCUREMENT SPECIFICATIONS: AS4459 AND MIL-F-85421. THIS PART SHALL BE QUALIFIED TO THE PROCUREMENT SPECIFICATIONS IN A COMPLETE ASSEMBLY. USERS OF THIS STANDARD ARE ADVISED TO CONTROL SOURCE APPROVAL(S) BY STANDARD PAGE SUPPLEMENT SHEET OR SIMILAR MEANS.
7. PACKAGING: INDIVIDUALLY PACKAGE IN CLEAN CONTAINER WITH IDENTIFICATION PER AS4459.
8. SPECIFIC DIMENSIONS AND TOLERANCES NOT DEFINED ON THIS STANDARD SHALL BE SPECIFIED AND CONTROLLED BY THE MANUFACTURER. THE MANUFACTURER IS RESPONSIBLE TO INSURE COMPATIBILITY WITH THE ASSEMBLY AND COMPLIANCE WITH THE REQUIREMENTS OF THE APPLICABLE PROCUREMENT SPECIFICATIONS.
9. INTENDED USE: PER AS4459.
- /10/ IDENTIFICATION: PARTS SHALL BE IDENTIFIED IN THE AREA SHOWN PER AS4459.
11. INTERPRETATION OF DRAWING PER ARP4296.
12. SURFACE TEXTURE: SYMBOLS PER ANSI Y14.36; REQUIREMENT PER ANSI/ASME B46.1. UNLESS OTHERWISE SPECIFIED, MACHINED SURFACES TO BE 125 μ in Ra.
13. BREAK EDGES .003 TO .015 UNLESS OTHERWISE SPECIFIED.
14. DIMENSIONING AND TOLERANCING: ASME Y14.5M-1994
15. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS $\pm$.010, ANGULAR DIMENSIONS $\pm$ 2°.
- /16/ EXAMPLE OF PART NUMBER: AS4219 E 08 N

BASIC PART NUMBER _____

MATERIAL CODE LETTER /1/ _____

_____ N = EXTERIOR PTFE NOT REQUIRED (TITANIUM ONLY)

_____ BLANK = EXTERIOR PTFE REQUIRED

_____ SIZE CODE
TUBE SIZE IN
.062 in INCREMENTS
(08 = .500 in)



AEROSPACE STANDARD

FITTING, ELBOW, 45°, BEAM SEAL,
BULKHEAD, EXTERNAL SWAGE TUBE
END, HYDRAULIC, 3000 PSI

AS4219

SHEET 2 OF 2



Documents

Document Sharing Hub