



AEROSPACE STANDARD

AS4510™/1**REV. A**

Issued 1996-05
Reaffirmed 2013-01
Stabilized 2025-09

Superseding AS4510/1

Fittings, Weld to 24° Cone Flareless, Fluid Connection

RATIONALE

This technical report is being stabilized because it covers technology, products, or processes which are mature and not likely to change in the foreseeable future.

STABILIZED NOTICE

This document has been declared "STABILIZED" by SAE G-3, Aerospace Couplings, Fittings, Hose, Tubing Assemblies Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2025 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE AS4510_1A

For more information on this standard, visit
<https://www.sae.org/standards/content/AS4510/1A/>

**Documents**

Document Sharing Hub

1. SCOPE:

1.1 Scope:

This SAE Aerospace Standard (AS) establishes the requirements for fluid fittings that combine both weld fitting end and 24° cone flareless fitting end connections for use in all types of fluid systems.

1.2 Classification:

Fittings shall be furnished in the types and styles designated by the applicable AS and other engineering standard drawings.

2. REFERENCES:

2.1 Applicable Documents:

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1.1 SAE Publications: Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

AS4444	Fittings, 24° Cone Flareless, Fluid Connection, 5000 psi
AS4510	Fittings, Weld, Fluid Connection, 5000 psi