


SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. C	FEDERAL SUPPLY CLASS 4720	
	RATIONALE THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.	
AS4573™		
SAE values your input. To provide feedback on this Technical Report, please visit http://standards.sae.org/AS4573C THIRD ANGLE PROJECTION 		
CUSTODIAN: G-3/G-3D		PROCUREMENT SPECIFICATION: AS1975 /2/
	AEROSPACE STANDARD HOSE ASSEMBLY, PTFE, PARA-ARAMID REINFORCED, STANDARD DUTY, 3000 PSI, 275 °F, TITANIUM FITTINGS, FLARELESS, 90° TO 90°	AS4573™ REV. C

ISSUED 1992-06 REVISED 2001-01 REAFFIRMED 2015-04 STABILIZED 2018-03




FIGURE 1 - HOSE ASSEMBLY, 90° ELBOW TO 90° ELBOW




FIGURE 2 - ELBOWS ORIENTATION



AEROSPACE STANDARD
 HOSE ASSEMBLY, PTFE, PARA-ARAMID
 REINFORCED, STANDARD DUTY, 3000 PSI, 275 °F,
 TITANIUM FITTINGS, FLARELESS, 90° TO 90°

AS4573™
 SHEET 1 OF 4

REV.



Documents

Document Sharing Hub