



AEROSPACE STANDARD

AS4875™/2**REV. A**

Issued 1995-05
Reaffirmed 2015-07
Revised 2016-06

Superseding AS4875/2

(R) Fittings, Flanged to Beaded, Fluid Connection

RATIONALE

This revision updated reference specifications, added PRI QML requirements, and general editorial revision.

1. SCOPE

This SAE Aerospace Standard (AS) establishes the requirements for fluid fittings that combine both flanged fitting ends and beaded hose connections for use in all types of fluid systems.

1.1 Classification

Fittings shall be furnished in the types and styles designated by the applicable MS and other engineering standard drawings. This specification is the same as MIL-F-5509 as applicable to flanged to beaded fittings except for updated materials and process specifications and industry coordinated general improvements. It is intended to serve as a procurement specification for the fittings described herein and in Section 6.

2. APPLICABLE DOCUMENTS

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Telephone: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), Web address: www.sae.org.

AS4843	Fittings, Beaded, Fluid Connection
AS4875	Fittings, Straight Threaded Boss of Flanged, Fluid Connection
AS5132	Fitting End - Hose Connection, Design Standard

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2016 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

Full document details: SAE AS4875_2A

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS4875/2A>

Documents

Document Sharing Hub

2.2 PRI Publications

Available from Performance Review Institute, 161 Thorn Hill Road, Warrendale, PA 15086-7527, Tel: 724-772-1616, www.pri-network.org.

AC7112 Nadcap Audit Criteria for Fluid Systems Component Manufacturers

AC7112/2 Nadcap Audit Criteria for Fittings and other Machined Components

PD1100 Nadcap Program Requirements

3. TECHNICAL REQUIREMENTS

3.1 Qualification

3.1.1 Manufacturer Qualification

A manufacturer producing a product shall be listed in a Performance Review Institute (PRI) Qualified Manufacturers List (QML). PRI accreditation to this procurement specification shall be in accordance with the requirements of PD1100, AC7112, and AC7112/2. See www.eAuditNet.com.

3.2 Material

See AS4875.

3.3 Heat Treatment

See AS4875.

3.4 Finish

See AS4875.

3.5 Design and Fabrication

The design and fabrication of the fittings shall be in accordance with the applicable drawings. The beaded ends of fittings shall be in accordance with AS5132. The beaded fitting ends shall meet the requirements of AS4843 as applicable.

3.6 Identification of Product

See AS4875.

3.7 Workmanship

See AS4875 for the flanged ends and fitting bodies and AS4843 for the beaded ends.

4. QUALITY ASSURANCE PROVISIONS

See AS4875 for the flanged ends and fitting bodies and AS4843 for the beaded ends.

5. PREPARATION FOR DELIVERY

See AS4875.