

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


REV.
B

AS5164™

RATIONALE

FEDERAL SUPPLY CLASS
4730


USAGE RESTRICTION NOTE ADD TO SHEET 1. CADMIUM WARNING NOTE ADDED. OPTIONAL MATERIALS ADDED TO NOTE 1. QML STATEMENT REVISED. INTENDED USE NOTE REVISED, NOTE 9 REVISED TO REFLECT CURRENT SPECIFICATION CALLOUT. REVISION INDICATOR NOTE REVISED. NOTE 16 ADDED. GENERAL NON-TECHNICAL UPDATES INCORPORATED.



NOT RECOMMENDED IN PART /16/

For more information on this standard, visit
<https://www.sae.org/standards/content/AS5164B/>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS4875/1 /4/



AEROSPACE STANDARD

FITTING, CONNECTOR, MULTIPLE
FLUID PRESSURE LINE, 45°

AS5164™
SHEET 1 OF 4

REV.
B

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1A - DIMENSIONS A - F

BASIC NO. AS5164 /14/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879 CLASS 3A	A ±.023	C ±.005	D ±.005	E	F ±.001
04	.250	.4375-20 UNJF	1.023	.692	.474	.562	.439
05	.312	.5000-20 UNJF	1.023	.755	.536	.625	.501
06	.375	.5625-18 UNJF	1.085	.817	.599	.750	.564
08	.500	.7500-16 UNJF	1.335	1.005	.786	.937	.751
10	.625	.8750-14 UNJF	1.491	1.130	.911	1.125	.876
12	.750	1.0625-12 UNJ	1.648	1.318	1.099	1.375	1.063
16	1.000	1.3125-12 UNJ	1.866	1.568	1.349	1.687	1.313

TABLE 1B - DIMENSIONS G - V AND WEIGHTS

BASIC NO. AS5164 /14/ SIZE CODE	G	H ±.010	K	V	LB/EA APPROX REF AL	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
04	.437	.750	.375	.797-.815	.0268	.0770	.0425
05	.437	.750	.500	.797-.815	.0221	.0633	.0349
06	.500	.875	.500	.985-1.003	.0387	.111	.0614
08	.500	1.125	.750	1.173-1.191	.0627	.180	.0994
10	.625	1.375	.812	1.355-1.380	.0989	.284	.157
12	.625	1.625	1.000	1.668-1.693	.163	.469	.259
16	.812	2.125	1.500	2.042-2.072	.269	.772	.426

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- a. DASH AS CODE LETTER - TYPE 4130 CARBON STEEL FORGING OR BAR PER AMS-S-6758 OR AMS6370; OR TYPE 4140 PER AMS6349 OR AMS6382.
- b. CODE LETTER D - TYPE 2014-T6 ALUMINUM ALLOY FORGING PER AMS-QQ-A-367 OR AMS4133; OR TYPE 2024-T6 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6 OR TYPE 2024-T851 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/6 OR AMS4339.
- c. CODE LETTER J - TYPE 304 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5639.
- d. CODE LETTER K - TYPE 316 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5648.
- e. CODE LETTER R - TYPE 321 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5645.
- f. CODE LETTER T - TYPE 6AL-4V TITANIUM ALLOY FORGING OR BAR PER AMS4928.
- g. CODE LETTER W - TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS-QQ-A-367 OR AMS4141; OR TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9; OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124.

	AEROSPACE STANDARD		AS5164™ SHEET 2 OF 4	REV. B
	FITTING, CONNECTOR, MULTIPLE FLUID PRESSURE LINE, 45°			

 Documents


Documents

Document Sharing Hub