

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS5756™/1

FEDERAL SUPPLY CLASS
6145


RATIONALE

AS5756/1 IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULTS IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. THE CABLES ARE USED FOR REPLACEMENT ONLY. A QUALIFIED SUPPLIER IS STILL MAINTAINED.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8D WIRE AND CABLE COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

For more information on this standard, visit
<https://www.sae.org/standards/content/AS5756/1C/>



CUSTODIAN: AE-8D		PROCUREMENT SPECIFICATION: AS5756	
	AEROSPACE STANDARD CABLE, POWER, ELECTRICAL, 600 VOLTS, PORTABLE, SINGLE CONDUCTOR, NON-OZONE RESISTANT		AS5756™/1
			REV. C

ISSUED 2004-06 REVISED 2023-05 STABILIZED 2023-06

NOTICE

THE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE LATEST ISSUE OF AS5756.




FIGURE 1 - CONDUCTOR EXAMPLE

REQUIREMENTS (REFER TO AS5756 AND TABLE 1):

1. CONSTRUCTION:
 - a. FIRST: COPPER CONDUCTOR (REFER TO TABLE 1 OF AS5756 FOR REQUIREMENTS). SIZES 10 AWG AND SMALLER SHALL BE TIN-COATED, SIZES 8 AWG AND LARGER SHALL BE UNCOATED.
 - b. SECOND: SEPARATOR, REQUIRED WHERE UNCOATED CONDUCTORS ARE USED, OPTIONAL WHERE TIN-COATED CONDUCTORS ARE USED.
 - c. THIRD: INSULATION OF SYNTHETIC OR NATURAL RUBBER (SEE TABLE 1 FOR THICKNESS), COLORED BLACK.
 - d. FOURTH: JACKET OF SYNTHETIC OR NATURAL RUBBER (SEE TABLE 1 FOR THICKNESS), COLORED BLACK. CABLE SURFACE MARKING REQUIRED.
 - e. INSULATION AND JACKET MAY BE COMBINED AT MANUFACTURER'S OPTION.
2. OZONE RESISTANCE: NOT REQUIRED.
3. CABLE TEMPERATURE RATING: -54 TO +90 °C (-65 TO +194 °F).

	AEROSPACE STANDARD	AS5756™/1 SHEET 1 OF 2	REV. 6
	CABLE, POWER, ELECTRICAL, 600 VOLTS, PORTABLE, SINGLE CONDUCTOR, NON-OZONE RESISTANT		



Documents

Document Sharing Hub