SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

SAE AS5960SUP1

Issued 2012-09

Hose Assembly, Polytetrafluoroethylene, Metallic Braid Reinforced, 5080 psi (35,000 kPa), 400°F (204°C), Aircraft Hydraulic Systems (Supplement 1)

RATIONALE

To document the hose assembly standards citing this specification.

1. SCOPE

This supplement forms a part of the Aerospace Standard AS5960, Hose Assembly, Polytrafluoroethyloene, Metallic Braid Reinforced, 5080 psi (35,000 kPa), 400°F (204°C), Aircraft Hydraulic Systems, and shall be used to identify hose assembly standards citing this procurement specification.

2. APPLICABLE DOCUMENTS

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

AS5961 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, Straight to Straight

AS5962 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, Straight to 45° Elbow

AS5963 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, Straight to 90° Elbow

AS5964 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, 45° Elbow to 45° Elbow

AS5965 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, 45° Elbow to 90° Elbow

AS5966 Hose Assembly, Polytetrafluoroethylene, Cres Braid Reinforced, 400°F, 5080 psi, Flareless, 90° Elbow to 90° Elbow

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: http://www.sae.org

SAE values your input. To provide feedback on this Technical Report, please visit http://www.sae.org/technical/standards/AS5960SUP1

AVA Documents Document Sharing Hub

Full document details: SAE AS5960SUP1

3. NOTES

3.1 A change bar (I) located in the left margin is for the convenience of the user in locating areas where technical revisions, not editorial changes, have been made to the previous issue of this document. An (R) symbol to the left of the document title indicates a complete revision of the document, including technical revisions. Change bars and (R) are not used in original publications, nor in documents that contain editorial changes only.

PREPARED BY SAE SUBCOMMITTEE G-3D, AEROSPACE HOSE OF
COMMITTEE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE AND TUBING ASSEMBLIES

Documents
Document Sharing Hub

Full document details: SAE AS5960SUP1