

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
B

AS6075™

FEDERAL SUPPLY CLASS
4730

RATIONALE

QML STATEMENT REVISED. "INTENDED USE" NOTE REVISED. NOTES 6A AND 6B DELETED. GENERAL UPDATES INCORPORATED.





FIGURE 1 - FITTING, BOLT

For more information on this standard, visit
<https://www.sae.org/standards/content/AS6075B/>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3

PROCUREMENT SPECIFICATION: AS4841 /4/



AEROSPACE STANDARD

FITTING, BOLT, FLARED,
37° SPHERICAL

AS6075™
SHEET 1 OF 4

REV.
B

Copyright © 2020 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1A - DIMENSIONS

BASIC NO. AS6075 /13/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879 CLASS 3A	A	B ±.010	C	D	E ±.010	F ±.002
04	.250	.4375-20 UNJF	1.922	.668	.438	1.188	.781	.433
05	.312	.5000-20 UNJF	1.922	.730	.438	1.188	.781	.496
06	.375	.5625-18 UNJF	2.125	.792	.469	1.344	.875	.558
08	.500	.7500-16 UNJF	2.594	.980	.562	1.688	1.094	.746
10	.625	.8750-14 UNJF	3.000	1.103	.594	1.969	1.250	.871
12	.750	1.0625-12 UNJ	3.484	1.352	.656	2.312	1.468	1.058
16	1.000	1.3125-12 UNJ	4.094	1.603	.656	2.812	1.687	1.308

TABLE 1B - DIMENSIONS AND WEIGHTS

BASIC NO. AS6075 /13/ SIZE CODE	H	J ±.005	L	M	N	LB/EA APPROX REF AL	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
04	.678 - .691	.474	.344	.188	.168-.175	.0287	.0825	.0455
05	.740 - .753	.536	.406	.219	.230-.237	.0343	.0985	.0543
06	.802 - .815	.599	.469	.250	.293-.301	.0448	.129	.0710
08	.990-1.003	.786	.625	.312	.387-.395	.0937	.269	.148
10	1.113-1.128	.911	.750	.375	.480-.488	.138	.397	.219
12	1.363-1.380	1.099	.938	.438	.604-.614	.230	.662	.365
16	1.613-1.630	1.349	1.188	.625	.839-.851	.359	1.03	.569

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- a. CODE LETTER F - TYPE 4130 PER AMS6370 OR TYPE 4140 PER AMS6382.
- b. CODE LETTER J - TYPE 304 CORROSION RESISTANT STEEL BAR PER AMS-QQ-S-763 OR AMS5639.
- c. CODE LETTER K - TYPE 316 CORROSION RESISTANT STEEL BAR PER AMS-QQ-S-763 OR AMS5648.
- d. CODE LETTER R - TYPE 321 CORROSION RESISTANT STEEL BAR PER AMS-QQ-S-763 OR AMS5645.
- e. CODE LETTER T - TYPE 6Al-4V TITANIUM ALLOY BAR PER AMS4928.
- f. CODE LETTER W - TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9 OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124.

	AEROSPACE STANDARD		AS6075™ SHEET 2 OF 4	REV. B
	FITTING, BOLT, FLARED, 37° SPHERICAL			



