

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
B

AS6095™

FEDERAL SUPPLY CLASS
4730

RATIONALE

GRAPHICS REDRAWN TO SHOW PROPER REPRESENTATION OF SPHERICAL DESIGN END AS5309 STYLE G. OPTIONAL MATERIAL SPECIFICATIONS ADDED. QML STATEMENT REVISED. INTENDED USE NOTE 6 REVISED. GENERAL UPDATES INCORPORATED.





FIGURE 1 - FITTING, CONNECTOR, TEE

For more information on this standard, visit
<https://www.sae.org/standards/content/AS6095B>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS4875/1 /4/



AEROSPACE STANDARD

FITTING, 37° SPHERICAL FLARED,
CONNECTOR, MULTIPLE
FLUID PRESSURE LINE, TEE

AS6095™
SHEET 1 OF 4

REV.
B

Copyright © 2021 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: +1 724-776-4970 (outside USA)
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1A - DIMENSIONS A-F

BASIC NO. AS6095 /13/ SIZE CODE	(NOMINAL TUBE SIZE)	T THREAD PER AS8879 CLASS 3A	A ±.023	C ±.005	D ±.005	E	F ±.001
04	.250	.4375-20 UNJF	1.148	.692	.474	.562	.439
05	.312	.5000-20 UNJF	1.148	.755	.536	.625	.501
06	.375	.5625-18 UNJF	1.273	.817	.599	.750	.564
08	.500	.7500-16 UNJF	1.460	1.005	.786	.937	.751
10	.625	.8750-14 UNJF	1.680	1.130	.911	1.125	.876
12	.750	1.0625-12 UNJ	2.023	1.318	1.099	1.375	1.063
16	1.000	1.3125-12 UNJ	2.398	1.568	1.349	1.687	1.313

TABLE 1B - DIMENSIONS G-V AND WEIGHTS

BASIC NO. AS6095 /13/ SIZE CODE	G	H ±.010	K	V	LB/EA APPROX REF AL	LB/EA APPROX REF STEEL	LB/EA APPROX REF TI
04	.437	.750	.375	.797-.815	.0334	.0958	.0528
05	.437	.750	.500	.797-.815	.0301	.0863	.0476
06	.500	.875	.500	.985-1.003	.0492	.141	.0779
08	.500	1.125	.750	1.173-1.191	.0822	.236	.130
10	.625	1.375	.812	1.355-1.380	.130	.374	.206
12	.625	1.625	1.000	1.668-1.693	.224	.642	.354
16	.812	2.125	1.500	2.042-2.072	.366	1.05	.580

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS A PLATING MATERIAL. CONSULT OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM'S USE.

/1/ MATERIAL:

- CODE LETTER F: TYPE 4130 ALLOY STEEL FORGING OR BAR PER AMS-S-6758 OR AMS6370; OR TYPE 4140 PER AMS6349 OR AMS6382.
- CODE LETTER J: TYPE 304 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5639.
- CODE LETTER K: TYPE 316 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5648.
- CODE LETTER R: TYPE 321 CORROSION RESISTANT STEEL FORGING OR BAR PER AMS-QQ-S-763 OR AMS5645.
- CODE LETTER T: TYPE 6Al-4V TITANIUM ALLOY FORGING OR BAR PER AMS4928.
- CODE LETTER W: TYPE 7075-T73 ALUMINUM ALLOY FORGING PER AMS-QQ-A-367 OR AMS4141; OR TYPE 7075-T73 ALUMINUM ALLOY BAR PER AMS-QQ-A-225/9; OR TYPE 7075-T7351 ALUMINUM ALLOY BAR PER AMS4124.

/2/ HEAT TREATMENT:

- MATERIAL CODE LETTER F: REFER TO HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- MATERIAL CODE LETTER W: REFER TO ELECTRICAL CONDUCTIVITY AND HARDNESS REQUIREMENT PER PROCUREMENT SPECIFICATION.
- OTHER MATERIAL CODE LETTERS: NONE.

	AEROSPACE STANDARD		AS6095™ SHEET 2 OF 4	REV. B
	FITTING, 37° SPHERICAL FLARED, CONNECTOR, MULTIPLE FLUID PRESSURE LINE, TEE			

