

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV.
C

AS7928™/15

FEDERAL SUPPLY CLASS
5940

RATIONALE


AS7928/15C IS BEING STABILIZED BECAUSE THE PROCESSES/PRODUCT IS CONSIDERED MATURE AND THE COMMITTEE DOES NOT ANTICIPATE FUTURE TECHNICAL CHANGES. STABILIZATION DOES NOT IMPLY THE PROCESS OR PRODUCT IS UNACCEPTABLE FOR APPLICATIONS FOR WHICH IT IS DESIGNED. ANY TECHNICAL CHANGES NOTED BY A SUPPLIER OR USER WHICH RESULTS IN A PRODUCT OR REQUIREMENT CHANGE WILL BE ADDRESSED BY A NEW REVISION. THERE IS NO QUALIFIED SUPPLIER.

STABILIZED NOTICE

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE AE-8C2 TERMINATING DEVICES AND TOOLING COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

For more information on this standard, visit
<https://www.sae.org/standards/content/AS7928/15C/>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8C2

PROCUREMENT SPECIFICATION: AS7928



AEROSPACE STANDARD

TERMINAL, LUG, CRIMP STYLE, COPPER, UNINSULATED,
FLAG TONGUE, SIZES 22-10, TYPE I, CLASS I, FOR 150 °C
TOTAL CONDUCTOR TEMPERATURE

AS7928™/15

REV.
C



Documents

Document Sharing Hub

Copyright © 2024 SAE International
All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, or used for text and data mining, AI training, or similar technologies, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada) Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790 Email: CustomerService@sae.org SAE WEB ADDRESS: <http://www.sae.org>

NOTICE

THE COMPLETE REQUIREMENTS FOR PROCURING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS DOCUMENT AND THE LATEST ISSUE OF AS7928.




FIGURE 1 - FLAG TERMINAL (SEE APPLICATION NOTES)

TABLE 1 - AS7928/15 FLAG TERMINAL DIMENSIONS

DASH NO.	WIRE SIZE	STUD SIZE	A MAX	B MIN	C MIN	D		E	
						MIN	MAX	MIN	MAX
-1	22-14	6	.566	.300	.218	.030	.034	.146	.165
-2		8	.566	.300	.218	.030	.034	.146	.165
-3		10	.566	.300	.218	.030	.034	.146	.165
-4	12-10	6	.651	.300	.250	.038	.042	.206	.219
-5		8	.651	.300	.250	.038	.042	.206	.219
-6		10	.651	.300	.250	.038	.042	.206	.219



AEROSPACE STANDARD

TERMINAL, LUG, CRIMP STYLE, COPPER, UNINSULATED,
FLAG TONGUE, SIZES 22-10, TYPE I, CLASS I, FOR 150 °C
TOTAL CONDUCTOR TEMPERATURE

AS7928™/15
SHEET 1 OF 3

REV.



Documents

Document Sharing Hub